

Page 1 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 21.08.2025 / 0029
Replacing version dated / version: 18.07.2025 / 0028
Valid from: 21.08.2025
PDF print date: 22.08.2025
Octane Plus

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Octane Plus

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Additives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

LIQUI MOLY UK
1310 Solihull Parkway
Birmingham Business Park
B37 7YB Solihull
Tel: +44 121 796 5365

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	2	H330-Fatal if inhaled.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

2.2 Label elements

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 21.08.2025 / 0029

Replacing version dated / version: 18.07.2025 / 0028

Valid from: 21.08.2025

PDF print date: 22.08.2025

Octane Plus

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H330-Fatal if inhaled. H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P260-Do not breathe vapours or spray. P271-Use only outdoors or in a well-ventilated area. P273-Avoid release to the environment.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P331-Do NOT induce vomiting.

P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Tricarbonyl(methylcyclopentadienyl)manganese

Hydrocarbons, C10-C13, aromatics, >1% naphthalene

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	---
content %	75-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

Hydrocarbons, C10-C13, aromatics, >1% naphthalene	
Registration number (REACH)	01-2119451151-53-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	926-273-4
CAS	(64742-94-5)
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Tricarbonyl(methylcyclopentadienyl)manganese	
Registration number (REACH)	01-2119495971-23-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	235-166-5
CAS	12108-13-3
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 1, H330 Acute Tox. 2, H310 Acute Tox. 3, H301 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	ATE (oral): 100 mg/kg ATE (dermal): 196,7 mg/kg ATE (as inhalation, Dusts or mist): 0,005 mg/l/4h ATE (as inhalation, Vapours): 0,1235 mg/l/4h

Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	601-052-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	202-049-5
CAS	91-20-3
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	ATE (oral): 490 mg/kg

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap. Call a doctor immediately, keep datasheet at hand

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Irritation of the eyes

Product removes fat.

Dermatitis (skin inflammation)

Danger of aspiration.

Lung damage

headaches

irritation of the respiratory tract

nausea

Dizziness

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Foam

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Metal oxides

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Full protection

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

If air supply is not sufficient, wear protective breathing apparatus.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

Page 5 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 21.08.2025 / 0029
Replacing version dated / version: 18.07.2025 / 0028
Valid from: 21.08.2025
PDF print date: 22.08.2025
Octane Plus

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Suction measures at the workplace or on the processing machines required.
Keep away from sources of ignition - Do not smoke.
Take measures against electrostatic charging, if appropriate.
Avoid inhalation, and contact with eyes or skin.
Handle and open container with care.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep locked away.
Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Solvent resistant floor
Do not store with oxidizing agents.
Store in a well ventilated place.
Store cool.
Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.
Observe the instructions for good working practice and the recommendations for risk assessment.
Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
800 mg/m³

GE	Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
WEL-TWA: 800 mg/m3		WEL-STEL: ---		---
Monitoring procedures:		- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)		
BMGV: ---		Other information: (OEL acc. to RCP-method, paragraphs 84-87, FH40)		

CE	Chemical Name	Naphthalene		
WEL-TWA: 500 mg/m3 (Aromatics) (WEL-TWA), 10 ppm (50 mg/m3) (EU)		WEL-STEL: ---	---	
Monitoring procedures:		- Compur - KITA-153 U(C) (551 182) - NIOSH 5506 (POLYNUCLEAR AROMATIC HYDROCARBONS by HPLC) - 1998 - NIOSH 5515 (POLYNUCLEAR AROMATIC HYDROCARBONS by GC) - 1994 - OSHA 35 (Napthalene) - 1982		
BMGV: ---		Other information: ---		

Hydrocarbons, C10-C13, aromatics, >1% naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m3	

Tricarbonyl(methylcyclopentadienyl)manganese						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,21	µg/l	
	Environment - marine		PNEC	0,021	µg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,062	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,11	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,11	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,6	mg/kg bw/day	

Naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	2,4	µg/l	
	Environment - marine		PNEC	0,24	µg/l	
	Environment - sewage treatment plant		PNEC	2,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,0672	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,0672	mg/kg dry weight	
	Environment - soil		PNEC	0,0533	mg/kg dry weight	
	Environment - sporadic (intermittent) release		PNEC	0,02	mg/l	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,57	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction

(2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |

| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

If applicable

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0,4

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If the workplace limit value is exceeded.

Filter A P3 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

Page 8 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 21.08.2025 / 0029
Replacing version dated / version: 18.07.2025 / 0028
Valid from: 21.08.2025
PDF print date: 22.08.2025
Octane Plus

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow, Clear
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Combustible.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	>61 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	n.a.
Kinematic viscosity:	<=7 mm ² /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,8118 g/ml (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidising liquids:	There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Octane Plus

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value

Acute toxicity, by inhalation:	ATE	2,5-3,74	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	0,1-0,15	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4951	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, mucous membrane irritation

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Aspiration hazard:						Yes

Tricarbonyl(methylcyclopentadienyl)manganese						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	100	mg/kg			
Acute toxicity, by oral route:	LD50	100	mg/kg			
Acute toxicity, by dermal route:	ATE	196,7	mg/kg			
Acute toxicity, by dermal route:	LD50	196,7	mg/kg			
Acute toxicity, by inhalation:	ATE	0,1235	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	0,005	mg/l/4h			Dusts or mist
Acute toxicity, by inhalation:	LC50	0,1235	mg/l/4h			Vapours
Skin corrosion/irritation:		2,79		Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative

Naphthalene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	490	mg/kg			
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat		
Acute toxicity, by inhalation:	LD50	>0,4	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Respiratory or skin sensitisation:				Guinea pig		No (skin contact)
Reproductive toxicity:	NOAEL	120	mg/kg	Rabbit	OECD 414 (Prenatal Developmental Toxicity Study)	Female
Reproductive toxicity:	LOAEL	50	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Female
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	LOAEL	400	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	1000	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	0,011	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours

Symptoms:						lack of appetite, ataxia, breathing difficulties, unconsciousness, diarrhoea, cornea opacity, headaches, cramps, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea and vomiting., sweating, Reddening, eyes, reddened
-----------	--	--	--	--	--	--

11.2. Information on other hazards

Octane Plus						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Other information:						Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Octane Plus							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.

12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:	AOX						According to the recipe, contains no AOX.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: No

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		10-2500				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymena pyriformis		
Water solubility:							Product floats on the water surface.

Tricarbonyl(methylcyclopentadienyl)manganese							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,21	mg/l	Cyprinus carpio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	0,83	mg/l	Daphnia magna		EPA OTS 797.1300
12.1. Toxicity to algae:	EC50	48h	1,7	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	growth rate
12.1. Toxicity to algae:	EC50	48h	0,41	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	biomass
12.2. Persistence and degradability:		56d	4	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable

12.2. Persistence and degradability:		60d	0	%		OECD 308 (Aerobic and Anaerobic Transformation in Aquatic Sediment Systems)	
12.3. Bioaccumulative potential:	Log Pow		3,7				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,99	mg/l	Pimephales promelas		Does not conform with EU classification.
12.1. Toxicity to fish:	LC50	96h	0,51	mg/l			
12.1. Toxicity to fish:	LC50	96h	0,11	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	>60d	0,6	mg/l	Daphnia pulex		
12.1. Toxicity to daphnia:	EC50	48h	1,6-24,1	mg/l	Daphnia magna		
12.1. Toxicity to algae:	LC50	4h	2,96	mg/l	Selenastrum capricornutum		
12.1. Toxicity to algae:	ErC50	72h	0,4	mg/l	Skeletonema costatum		
12.2. Persistence and degradability:		28d	2	%			Not readily biodegradable
12.3. Bioaccumulative potential:	BCF	28d	40-300				Lowfish
12.4. Mobility in soil:	Koc		817				
12.4. Mobility in soil:	Koc		240-1300				
Other information:	BOD5		0	%			
Other information:	COD		22	%			
Other information:	Log Pow		3,3				

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 04 other organic solvents, washing liquids and mother liquors

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 21.08.2025 / 0029

Replacing version dated / version: 18.07.2025 / 0028

Valid from: 21.08.2025

PDF print date: 22.08.2025

Octane Plus

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	2810
14.2. UN proper shipping name:	UN 2810 TOXIC LIQUID, ORGANIC, N.O.S. (TRICARBONYL(METHYLCYCLOPENTADIENYL)MANGANESE)
14.3. Transport hazard class(es):	6.1
14.4. Packing group:	III
14.5. Environmental hazards:	environmentally hazardous
Tunnel restriction code:	E
Classification code:	T1
LQ:	5 L
Transport category:	2



Transport by sea (IMDG-code)

14.1. UN number or ID number:	2810
14.2. UN proper shipping name:	UN 2810 TOXIC LIQUID, ORGANIC, N.O.S. (TRICARBONYL(METHYLCYCLOPENTADIENYL)MANGANESE)
14.3. Transport hazard class(es):	6.1
14.4. Packing group:	III
14.5. Environmental hazards:	environmentally hazardous
Marine Pollutant:	Yes
EmS:	F-A, S-A



Transport by air (IATA)

14.1. UN number or ID number:	2810
14.2. UN proper shipping name:	UN 2810 Toxic liquid, organic, n.o.s. (TRICARBONYL(METHYLCYCLOPENTADIENYL)MANGANESE)
14.3. Transport hazard class(es):	6.1
14.4. Packing group:	III
14.5. Environmental hazards:	Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Naphthalene

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
H2		50	200
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Page 15 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 21.08.2025 / 0029
Replacing version dated / version: 18.07.2025 / 0028
Valid from: 21.08.2025
PDF print date: 22.08.2025
Octane Plus

Directive 2010/75/EU (VOC): 96,5 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 15
Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 2, H330	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H310 Fatal in contact with skin.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H330 Fatal if inhaled.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Acute Tox. — Acute toxicity - inhalation
Asp. Tox. — Aspiration hazard
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Acute Tox. — Acute toxicity - dermal
Acute Tox. — Acute toxicity - oral
Aquatic Acute — Hazardous to the aquatic environment - acute
Carc. — Carcinogenicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 21.08.2025 / 0029

Replacing version dated / version: 18.07.2025 / 0028

Valid from: 21.08.2025

PDF print date: 22.08.2025

Octane Plus

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight

mg/kg wwt mg/kg wet weight

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 21.08.2025 / 0029

Replacing version dated / version: 18.07.2025 / 0028

Valid from: 21.08.2025

PDF print date: 22.08.2025

Octane Plus

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.