



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ DCT
SYNTHETIC BLEND GEAR OIL

Product code : 868207

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH208 Contains C14-C18 alpha-olefin epoxide, reaction products with boric acid. May
produce an allergic reaction.



SAFETY DATA SHEET

Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

EUH210 Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 80,00 - < 90,00
Mineral Oil	Mixture 01-2119484627-25-xxxx 01-2119471299-27-xxxx 01-2119487077-29-xxxx 01-2119480132-48-xxxx	Asp. Tox.1; H304	>= 5,00 - < 10,00
Isooctadecanoic acid, reaction products with tetraethylenepentamine	68784-17-8 701-204-9	Skin Irrit.2; H315 Eye Irrit.2; H319	>= 1,00 - < 2,50
C14-C18 alpha-olefin epoxide, reaction products with boric acid	939-580-3 01-2119976364-28-xxxx	Skin Sens.1B; H317	>= 0,50 - < 1,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

- advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash contaminated clothing before re-use.
If on skin, rinse well with water.
Remove contaminated clothing. If irritation develops, get medical attention.
- In case of eye contact : If eye irritation persists, consult a specialist.
Protect unharmed eye.
Remove contact lenses.
Flush eyes with water as a precaution.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

point of release.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Use personal protective equipment.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

7.1 Precautions for safe handling

- Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Avoid contact with skin and eyes.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not smoke. When using do not eat or drink.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection



SAFETY DATA SHEET

Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	: Choose body protection according to the amount and concentration of the dangerous substance at the work place. Safety shoes Impervious clothing Wear as appropriate:
Respiratory protection	: No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: oily
Odour Threshold	: No data available
pH	: Not applicable
Pour point	: < 0 °C
Boiling point/boiling range	: No data available No data available
Flash point	: 160 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0,849 g/cm ³ (15,6 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	34 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition	:	No data available
---------------	---	-------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
excessive heat

10.5 Incompatible materials



SAFETY DATA SHEET

Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

Materials to avoid : Strong oxidizing agents
halogens
Halogenated compounds

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: No mortality observed at this dose.

Components:

Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched,:

Acute oral toxicity : (Rat, male and female): 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Assessment: No adverse effect has been observed in acute oral toxicity tests.

Components:



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

POLYMER:

Acute oral toxicity : LD50 (Rat): > 16.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit
Result: No skin irritation

Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched,:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Irritating to skin.
GLP: yes

POLYMER:

Species: Rabbit
Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Slight, transient irritation
Remarks: Expected based on components.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit
Result: No eye irritation

Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched,:

Species: Rabbit
Method: OECD Test Guideline 405
Result: Irritating to eyes.



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

GLP: yes

POLYMER:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched,):

POLYMER:

Test Type: Buehler Test

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

POLYMER:

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity -

: Classified based on DMSO extract content < 3% (Regulation

Assessment

(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

May be fatal if swallowed and enters airways.

Mineral Oil:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

	Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR: ≥ 1.000 mg/l Exposure time: 14 d Species: <i>Oncorhynchus mykiss</i> (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: <i>Daphnia</i> (water flea) Test substance: WAF Method: OECD Test Guideline 211
Isooctadecanoic acid, reaction products with tetraethylenepentamine Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information. Not classified based on available information.
Long-term (chronic) aquatic hazard	: This product has no known ecotoxicological effects. Not classified based on available information.
C14-C18 alpha-olefin epoxide, reaction products with boric acid Toxicity to fish	: LL50 (<i>Oncorhynchus mykiss</i> (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: semi-static test Test substance: WAF Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Remarks: No toxicity at the limit of solubility
Toxicity to algae	: EL50 (<i>Pseudokirchneriella subcapitata</i> (algae)): > 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Remarks: No toxicity at the limit of solubility



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

12.2 Persistence and degradability

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based
Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

C14-C18 alpha-olefin epoxide, reaction products with boric acid
Biodegradability : Result: Not readily biodegradable.
Biodegradation: 26,7 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

Isooctadecanoic acid, reaction products with tetraethylenepentamine
Partition coefficient: n- : log Pow: 45,8 (25 °C)
octanol/water

C14-C18 alpha-olefin epoxide, reaction products with boric acid
Partition coefficient: n- : log Pow: 9,4
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life., An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

13.1 Waste treatment methods

- Product : Send to a licensed waste management company.
Do not contaminate ponds, waterways or ditches with chemical or used container.
The product should not be allowed to enter drains, water courses or the soil.
- Contaminated packaging : Do not re-use empty containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Dispose of as unused product.
Empty remaining contents.
-

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that : Not applicable



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), AIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : 000000233790

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.



SAFETY DATA SHEET

Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands

ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP : Classification, Labelling and Packaging

CSA : Chemical Safety Assessment

CSR : Chemical Safety Report

DNEL : Derived No Effect Level.

EINECS : European Inventory of Existing Commercial Chemical Substances.

ELINCS : European List of Notified Chemical Substances

PEC : Predicted Effect Concentration

PEL : Permissible Exposure Limits



SAFETY DATA SHEET
Valvoline™ DCT SYNTHETIC BLEND GEAR
OIL

Version: 8.1

Revision Date: 25.02.2021

Print Date: 14/09/2022

PNEC : Predicted No Effect Concentration

R-phrase : Risk phrase

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK : German Water Hazard Class