

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier

SCHRAUBENSICHERUNG HOCHFEST
Article number: 920250, 92005, 92010, 92050

1.2 Relevant identified uses of the substance or mixture and uses advised against
1.2.1 Relevant uses

Sealing material

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company PETEC Verbindungstechnik GmbH
 Wüstenbuch 26
 96132 Schlüsselfeld / GERMANY
 Phone +49 (0) 9555 80994-0
 Fax +49 (0) 9555-80994-25
 Homepage www.petec.de
 E-mail info@petec.de

Address enquiries to

Technical information info@petec.de
Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification
2.1 Classification of the substance or mixture

Eye Irrit. 2: H319 Causes serious eye irritation.
 Skin Sens. 1: H317 May cause an allergic skin reaction.
 Aquatic Chronic 4: H413 May cause long lasting harmful effects to aquatic life.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms

Signal word

WARNING

Contains:

Methacrylic acid, monoester with Propan-1,2-diole
 2-Hydroxyethyl methacrylate

Hazard statements

H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P280 Wear protective gloves / protective clothing / eye protection / face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
 P337+P313 If eye irritation persists: Get medical advice / attention.
 P501 Dispose of contents/container in accordance with local/national regulation.

2.3 Other hazards
Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
60 - 85	Bisphenol A ethoxylate dimethacrylate CAS: 41637-38-1, EINECS/ELINCS: Polymer, Reg-No.: 01-2119980659-17 GHS/CLP: Aquatic Chronic 4: H413
10 - 30	Methacrylic acid, monoester with Propan-1,2-diole CAS: 27813-02-1, EINECS/ELINCS: 248-666-3, Reg-No.: 01-2119490226-37-XXXX GHS/CLP: Eye Irrit. 2: H319 - Skin Sens. 1: H317
5 - 10	2-Hydroxyethyl methacrylate CAS: 868-77-9, EINECS/ELINCS: 212-782-2, EU-INDEX: 607-124-00-X, Reg-No.: 01-2119490169-29-XXXX GHS/CLP: Skin Irrit. 2: H315 - Skin Sens. 1: H317 - Eye Irrit. 2: H319
1 - < 3	(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triylo)tri-2,1-ethanediyli triacrylate CAS: 40220-08-4, EINECS/ELINCS: 254-843-6 GHS/CLP: Eye Dam. 1: H318
< 1	Cumene hydroperoxide CAS: 80-15-9, EINECS/ELINCS: 201-254-7, EU-INDEX: 617-002-00-8, Reg-No.: 01-2119475796-19 GHS/CLP: Org. Perox. E: H242 - Acute Tox. 3: H331 - Acute Tox. 4: H302 H312 - STOT RE 2: H373 - Skin Corr. 1B: H314 - Aquatic Chronic 2: H411 - STOT SE 3: H335
< 1	Ethylene glycol CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX GHS/CLP: Acute Tox. 4: H302 - STOT RE 2: H373

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
 For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change soaked clothing immediately.

Inhalation

Ensure supply of fresh air.
 In the event of symptoms seek medical treatment.

Skin contact

In case of contact with skin wash off immediately with soap and water.
 Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.

Ingestion

Do not induce vomiting.
 Rinse out mouth and give plenty of water to drink.
 Get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects
 Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
 Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Dry powder.
Foam.
Carbon dioxide.

Extinguishing media that must not be used Full water jet

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Carbon dioxide (CO₂)

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, universal absorbent, diatomaceous earth).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.
Keep away from open flames, hot surfaces and sources of ignition.
Do not eat, drink or smoke when using this product.
Wash hands before breaks and after work.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.
Contaminated work clothing should not be allowed out of the workplace.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.
Keep container tightly closed.
Keep container in a well-ventilated place.
Keep in a cool place. Store in a dry place.
Protect from heat/overheating.
Recommended storage temperature: 5-25 °C (41-77 °F).

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection**8.1 Control parameters****Ingredients with occupational exposure limits to be monitored (GB)**

Substance
Ethylene glycol
CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
Long-term exposure: 20 ppm, 52 mg/m ³ , Vapour, particulate: 10 mg/m ³
Short-term exposure (15-minute): 40 ppm, 104 mg/m ³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES
Ethylene glycol
CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
Eight hours: 20 ppm, 52 mg/m ³ , H
Short-term (15-minute): 40 ppm, 104 mg/m ³

DNEL

Substance
Ethylene glycol, CAS: 107-21-1
Industrial, dermal, Long-term - systemic effects: 106 mg/m ³ .
Industrial, inhalative, Long-term - local effects: 35 mg/m ³ .
general population, dermal, Long-term - systemic effects: 53 mg/m ³ .
general population, inhalative, Long-term - local effects: 7 mg/m ³ .
Cumene hydroperoxide, CAS: 80-15-9
Industrial, inhalative, Long-term - systemic effects: 6 mg/m ³ (AF=5,25).
Bisphenol A ethoxylate dimethacrylate, CAS: 41637-38-1
Industrial, dermal, Long-term - systemic effects: 2 mg/kg bw/d (AF=300).
Industrial, inhalative, Long-term - systemic effects: 3,52 mg/m ³ .
general population, oral, Long-term - systemic effects: 0,5 mg/kg bw/d (AF=600).
general population, inhalative, Long-term - systemic effects: 0,87 mg/m ³ .
general population, dermal, Long-term - systemic effects: 1 mg/kg bw/d (AF=600).

PNEC

Substance
Ethylene glycol, CAS: 107-21-1
freshwater, 10 mg/L.
seawater, 1 mg/L.
sediment (freshwater), 37 mg/kg.
soil, 1,53 mg/kg.
sewage treatment plants (STP), 199,5 mg/kg.
sediment (seawater), 3,7 mg/kg.
Cumene hydroperoxide, CAS: 80-15-9
soil, 0,003 mg/kg dw.
sediment (seawater), 0,002 mg/kg dw.
sediment (freshwater), 0,023 mg/kg dw.
sewage treatment plants (STP), 0,35 mg/l (AF=1).
seawater, 0 mg/l (AF=10000).
freshwater, 0,003 mg/l (AF=1000).
Bisphenol A ethoxylate dimethacrylate, CAS: 41637-38-1

There are no PNEC values established for the substance.,

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	safety glasses (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,5 mm; Butyl rubber, >480 min (EN 374-1/-2/-3). > 0,5 mm; Viton, >480 min (EN 374-1/-2/-3). Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Do not inhale gases/vapours. Avoid contact with eyes and skin.
Respiratory protection	If ventilation is insufficient, wear respiratory protection. Short term: filter apparatus, filter A. (DIN EN 14387)
Thermal hazards	not applicable
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	red
Odor	pungent
Odour threshold	No information available.
pH-value	No information available.
pH-value [1%]	No information available.
Boiling point [°C]	No information available.
Flash point [°C]	> 100
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/ml]	1,1
Bulk density [kg/m³]	not applicable
Solubility in water	virtually insoluble
Partition coefficient [n-octanol/water]	No information available.
Viscosity	~ 550 mPas (25°C)
Relative vapour density determined in air	No information available.
Evaporation speed	No information available.
Melting point [°C]	No information available.
Autoignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

Reactions with reducing agents.

Reactions with various metals.

10.4 Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Sensitive to air.

10.5 Incompatible materials

See SECTION 10.3.

10.6 Hazardous decomposition products

In the event of fire: See SECTION 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Substance
Ethylene glycol, CAS: 107-21-1
LD50, dermal, mouse: > 3500 mg/kg.
LD50, oral, Rat: 7712 mg/kg.
LC50, inhalative, Rat: > 2,5 mg/l 6h.
LDLo, oral, Human: ca. 1600 mg/kg.
Methacrylic acid, monoester with Propan-1,2-diole, CAS: 27813-02-1
LD50, dermal, Rabbit: > 5000 mg/kg.
LD50, oral, Rat: > 2000 mg/kg (OECD 401).
Cumene hydroperoxide, CAS: 80-15-9
LD50, dermal, Rabbit: 133,6 mg/kg.
LD50, oral, Rat: 382 mg/kg.
Bisphenol A ethoxylate dimethacrylate, CAS: 41637-38-1
LD50, dermal, Rat: > 2000 mg/kg bw.
LD50, oral, Rat: > 35 000 mg/kg bw.

Serious eye damage/irritation	Toxicological data of complete product are not available. Irritant Calculation method
Skin corrosion/irritation	Toxicological data of complete product are not available. No classification. Calculation method
Respiratory or skin sensitisation	Toxicological data of complete product are not available. May cause an allergic skin reaction. Calculation method
Specific target organ toxicity — single exposure	Toxicological data of complete product are not available. No classification. Calculation method
Specific target organ toxicity — repeated exposure	Toxicological data of complete product are not available. Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Toxicological data of complete product are not available. Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Toxicological data of complete product are not available. Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Toxicological data of complete product are not available. Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	Toxicological data of complete product are not available. The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

SECTION 12: Ecological information

12.1 Toxicity

Substance
Ethylene glycol, CAS: 107-21-1
LC50, (96h), Pimephales promelas: 72860 mg/l.
EC50, (96h), Selenastrum capricornutum: 6500 - 13000 mg/l.
EC50, (48h), Daphnia magna: > 100 mg/l OECD 202.
Methacrylic acid, monoester with Propan-1,2-diole, CAS: 27813-02-1
LC50, (48h), Leuciscus idus: 493 mg/l (DIN 38412).
EC50, (72h), Pseudokirchneriella subcapitata: 97,2 mg/l (OECD 201).
EC50, (48h), Daphnia magna: 380 mg/l (OECD 202).
NOEC, (72h), Pseudokirchneriella subcapitata: 97,2 mg/l (OECD 201).
NOEC, (21d), Daphnia magna: 24,1 mg/l (OECD 202).
Cumene hydroperoxide, CAS: 80-15-9
LC50, (96h), Oncorhynchus mykiss: 3,9 mg/l.
EC50, (48h), Daphnia magna: 18,84 mg/l.
Bisphenol A ethoxylate dimethacrylate, CAS: 41637-38-1
EL50, (48h), Daphnia magna: > 100 mg/l.
LL50, (96h), Rainbow trout: > 100 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the authorities if necessary.

Waste no. (recommended) 080409*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110*

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2017).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4

- Observe employment restrictions for people Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.

- VOC (2010/75/CE) not determined

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**16.1 Hazard statements
(SECTION 03)**

H335 May cause respiratory irritation.
 H411 Toxic to aquatic life with long lasting effects.
 H314 Causes severe skin burns and eye damage.
 H302+H312 Harmful if swallowed or in contact with skin.
 H331 Toxic if inhaled.
 H242 Heating may cause a fire.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H302 Harmful if swallowed.
 H318 Causes serious eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H413 May cause long lasting harmful effects to aquatic life.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@/TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information**Customs Tariff**

not determined

Classification procedure

Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)
 Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)
 Aquatic Chronic 4: H413 May cause long lasting harmful effects to aquatic life. (Calculation method)

Modified position

SECTION 16 been added: GENERAL REVIEW

Safety Data Sheet 1907/2006/EC - REACH (GB)

SCHRAUBENSICHERUNG HOCHFEST

Article number 920250, 92005, 92010, 92050

PETEC Verbindungstechnik GmbH

96132 Schlüsselfeld



Date printed 18.07.2017, Revision 11.04.2017

Version 02. Supersedes version: 01

Page 12 / 12

Copyright: Chemiebüro®