



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 14

LOCTITE SF 7085 SUPERFOAM

SDS No. : 173436

V006.0

Revision: 26.08.2019

printing date: 12.05.2022

Replaces version from: 23.06.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7085 SUPERFOAM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Solvent cleaner

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable aerosols

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

Category 1

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Danger

Hazard statement:

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

Precautionary statement:

P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P211 Do not spray on an open flame or other ignition source.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 P102 Keep out of reach of children.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General chemical description:**

Cleaner

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-RegNo. | content | Classification |
|---|-------------------------------|------------|--|
| Butane, n- (<0.1 % butadiene) 106-97-8 | 203-448-7 01-2119474691-32 | 3- < 10 % | Flam. Gas 1 H220 Press. Gas |
| 1-Methoxy-2-propanol 107-98-2 | 203-539-1 01-2119457435-35 | 3- < 10 % | Flam. Liq. 3 H226 STOT SE 3 H336 |
| Tetrapotassium pyrophosphate 7320-34-5 | 230-785-7 01-2119489369-18 | 1- < 2,5 % | Eye Irrit. 2 H319 Acute Tox. 4 H302 |
| Propane 74-98-6 | 200-827-9 01-2119486944-21 | 1- < 2,5 % | Flam. Gas 1 H220 Press. Gas |

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to Detergent Regulation 648/2004/EC

| | |
|----------|------------------------|
| 5 - 15 % | aliphatic hydrocarbons |
| < 5 % | phosphates |
| | anionic surfactants |
| | non-ionic surfactants |
| contains | Perfumes |

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Move to fresh air.

Seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Fire fighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

Remove sources of ignition.

Ensure adequate ventilation.

See advice in section 8

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

Wipe up using absorbent material.

Store in a partly filled, closed container until disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

Keep away from sources of ignition - no smoking.

Vapours should be extracted to avoid inhalation.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

7.3. Specific end use(s)

Solvent cleaner

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|------------|-------------------------|-----------------------------------|---|------------------------|
| Butane 106-97-8 [BUTANE] | 750 | 1.810 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Butane 106-97-8 [BUTANE] | 600 | 1.450 | Time Weighted Average (TWA): | | EH40 WEL |
| 1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPAN-2-OL] | 150 | 560 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| 1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPAN-2-OL] | | | Skin designation: | Can be absorbed through the skin. | EH40 WEL |
| 1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPAN-2-OL] | 100 | 375 | Time Weighted Average (TWA): | | EH40 WEL |
| 1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2] | 100 | 375 | Time Weighted Average (TWA): | Indicative | ECTLV |
| 1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2] | 150 | 568 | Short Term Exposure Limit (STEL): | Indicative | ECTLV |

Occupational Exposure LimitsValid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|------------|-------------------------|-----------------------------------|---|------------------------|
| Butane 106-97-8 [BUTANE] | 1.000 | | Time Weighted Average (TWA): | | IR_OEL |
| 1-Methoxypropan-2-ol 107-98-2 [PROPYLENE GLYCOL MONOMETHYL ETHER] | 100 | 375 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| 1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2] | 100 | 375 | Time Weighted Average (TWA): | Indicative | ECTLV |
| 1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2] | 150 | 568 | Short Term Exposure Limit (STEL): | Indicative | ECTLV |
| 1-Methoxypropan-2-ol 107-98-2 [PROPYLENE GLYCOL MONOMETHYL ETHER] | 150 | 568 | Short Term Exposure Limit (STEL): | 15 minutes Indicative OELV | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|------------------------------------|--------------------|------------|-----|------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| 1-Methoxy -2-propanol 107-98-2 | aqua (freshwater) | | 10 mg/l | | | | |
| 1-Methoxy -2-propanol 107-98-2 | aqua (marine water) | | 1 mg/l | | | | |
| 1-Methoxy -2-propanol 107-98-2 | aqua (intermittent releases) | | 100 mg/l | | | | |
| 1-Methoxy -2-propanol 107-98-2 | sediment (freshwater) | | | | 52,3 mg/kg | | |
| 1-Methoxy -2-propanol 107-98-2 | sediment (marine water) | | | | 5,2 mg/kg | | |
| 1-Methoxy -2-propanol 107-98-2 | Soil | | | | 4,59 mg/kg | | |
| 1-Methoxy -2-propanol 107-98-2 | sewage treatment plant (STP) | | 100 mg/l | | | | |
| Tetrapotassium pyrophosphate 7320-34-5 | aqua (freshwater) | | 0,05 mg/l | | | | |
| Tetrapotassium pyrophosphate 7320-34-5 | aqua (marine water) | | 0,005 mg/l | | | | |
| Tetrapotassium pyrophosphate 7320-34-5 | aqua (intermittent releases) | | 0,5 mg/l | | | | |
| Tetrapotassium pyrophosphate 7320-34-5 | sewage treatment plant (STP) | | 50 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|-----------------------|----------------------|--|------------------|-------------|---------|
| 1-Methoxy -2-propanol 107-98-2 | Workers | Inhalation | Acute/short term exposure - local effects | | 553,5 mg/m3 | |
| 1-Methoxy -2-propanol 107-98-2 | Workers | dermal | Long term exposure - systemic effects | | 183 mg/kg | |
| 1-Methoxy -2-propanol 107-98-2 | Workers | Inhalation | Long term exposure - systemic effects | | 369 mg/m3 | |
| 1-Methoxy -2-propanol 107-98-2 | General population | dermal | Long term exposure - systemic effects | | 78 mg/kg | |
| 1-Methoxy -2-propanol 107-98-2 | General population | Inhalation | Long term exposure - systemic effects | | 43,9 mg/m3 | |
| 1-Methoxy -2-propanol 107-98-2 | General population | oral | Long term exposure - systemic effects | | 33 mg/kg | |
| 1-Methoxy -2-propanol 107-98-2 | Workers | inhalation | Acute/short term exposure - systemic effects | | 553,5 mg/m3 | |
| Tetrapotassium pyrophosphate 7320-34-5 | Workers | inhalation | Long term exposure - systemic effects | | 44,08 mg/m3 | |
| Tetrapotassium pyrophosphate 7320-34-5 | General population | inhalation | Long term exposure - systemic effects | | 10,87 mg/m3 | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|----------------------------|------------------------------------|
| Appearance | liquid aerosol yellow |
| Odor | characteristic |
| Odour threshold | No data available / Not applicable |
| pH | 9,50 - 10,50 |
| () | |
| Melting point | No data available / Not applicable |
| Solidification temperature | No data available / Not applicable |
| Initial boiling point | 0 °C (32 °F) |
| Flash point | -60 °C (-76 °F) |
| Evaporation rate | No data available / Not applicable |
| Flammability | No data available / Not applicable |
| Explosive limits | No data available / Not applicable |
| Vapour pressure | 23 hPa |
| (20 °C (68 °F)) | |
| Relative vapour density: | No data available / Not applicable |

| | |
|--|------------------------------------|
| Density (20 °C (68 °F)) | 0,9700 - 0,9850 g/cm3 |
| Bulk density | No data available / Not applicable |
| Solubility | No data available / Not applicable |
| Solubility (qualitative) (Solvent: Water) | Not miscible or difficult to mix |
| Solubility (qualitative) (Solvent: Acetone) | Miscible |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |
| Decomposition temperature | No data available / Not applicable |
| Viscosity | No data available / Not applicable |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Oxidising properties | No data available / Not applicable |

9.2. Other information

| | |
|----------------------|-------------------|
| Ignition temperature | 365,0 °C (689 °F) |
|----------------------|-------------------|

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reaction with strong bases

Reaction with strong acids.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information**General toxicological information:**

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

11.1. Information on toxicological effects**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|---------------|--------------------------|---------|--|
| 1-Methoxy-2-propanol 107-98-2 | LD50 | 3.739 mg/kg | rat | EU Method B.1 (Acute Toxicity (Oral)) |
| Tetrapotassium pyrophosphate 7320-34-5 | LD50 | > 300 - < 2.000 mg/kg | rat | OECD Guideline 420 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|---------------|---------------|---------|--|
| 1-Methoxy -2-propanol 107-98-2 | LD50 | > 2.000 mg/kg | rat | EU Method B.3 (Acute Toxicity (Dermal)) |
| Tetrapotassium pyrophosphate 7320-34-5 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|--|---------------|--------------|-----------------|------------------|---------|---|
| Butane, n- (<0.1 % butadiene) 106-97-8 | LC50 | 274200 ppm | gas | 4 h | rat | not specified |
| 1-Methoxy -2-propanol 107-98-2 | LC50 | 55 mg/l | vapour | 4 h | rat | not specified |
| Tetrapotassium pyrophosphate 7320-34-5 | LC50 | > 1,1 mg/l | dust | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| Propane 74-98-6 | LC50 | > 800000 ppm | gas | 15 min | rat | not specified |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|----------------|------------------|---------|--|
| 1-Methoxy -2-propanol 107-98-2 | not irritating | 4 h | rabbit | EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion) |
| Tetrapotassium pyrophosphate 7320-34-5 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|----------------|------------------|---------|---|
| 1-Methoxy -2-propanol 107-98-2 | not irritating | | rabbit | EU Method B.5 (Acute Toxicity: Eye Irritation / Corrosion) |
| Tetrapotassium pyrophosphate 7320-34-5 | Category II | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|--|-----------------|---------------------------------------|------------|--|
| 1-Methoxy -2-propanol 107-98-2 | not sensitising | Guinea pig maximisation test | guinea pig | EU Method B.6 (Skin Sensitisation) |
| Tetrapotassium pyrophosphate 7320-34-5 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|--|----------|--|--|----------------------------|--|
| Butane, n- (<0.1 % butadiene) 106-97-8 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Butane, n- (<0.1 % butadiene) 106-97-8 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| 1-Methoxy -2-propanol 107-98-2 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 1-Methoxy -2-propanol 107-98-2 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| 1-Methoxy -2-propanol 107-98-2 | negative | mammalian cell gene mutation assay | without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Tetrapotassium pyrophosphate 7320-34-5 | negative | bacterial reverse mutation assay (e.g Ames test) | with | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Propane 74-98-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Propane 74-98-6 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Butane, n- (<0.1 % butadiene) 106-97-8 | negative | | | Drosophila melanogaster | not specified |
| Butane, n- (<0.1 % butadiene) 106-97-8 | negative | inhalation: gas | | rat | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| 1-Methoxy -2-propanol 107-98-2 | negative | intraperitoneal | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Tetrapotassium pyrophosphate 7320-34-5 | negative | oral: feed | | mouse | OECD Guideline 485 (Genetic Toxicology: Mouse Heritable Translocation Assay) |
| Tetrapotassium pyrophosphate 7320-34-5 | negative | oral: unspecified | | rat | OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |
| Propane 74-98-6 | negative | | | Drosophila melanogaster | not specified |
| Propane 74-98-6 | negative | inhalation: gas | | rat | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|-----------------------------------|------------------|-------------------------|---|---------|-------------|--|
| 1-Methoxy -2-propanol 107-98-2 | not carcinogenic | inhalation: vapour | 2 y 6 hr/day, 5 days/wk | rat | male/female | OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|--|---|----------------------------|-------------------------|---------|--|
| Butane, n- (<0.1 % butadiene) 106-97-8 | NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l | screening | inhalation: gas | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test) |
| 1-Methoxy -2-propanol 107-98-2 | NOAEL P 300 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm | Two generation study | inhalation: vapour | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| Propane 74-98-6 | NOAEL P 21,6 mg/l NOAEL F1 21,6 mg/l | screening | inhalation: gas | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|--|-----------------|-------------------------|--|---------|---|
| Butane, n- (<0.1 % butadiene) 106-97-8 | | inhalation: gas | 28 d | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| 1-Methoxy -2-propanol 107-98-2 | NOAEL 1000 ppm | inhalation | 13 weeks 6 hours/day; 5 days/week | rat | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |
| 1-Methoxy -2-propanol 107-98-2 | NOAEL 919 mg/kg | oral: gavage | 35 d 5 d/w | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |
| Tetrapotassium pyrophosphate 7320-34-5 | NOAEL 500 mg/kg | oral: gavage | 90 d Once a day, 5 days a week | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Propane 74-98-6 | | inhalation: gas | 28 d 6 h/d, 7 d/w | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-------------|---------------|---------------------|---|
| Butane, n- (< 0.1 % butadiene) 106-97-8 | LC50 | 27,98 mg/l | 96 h | | not specified |
| 1-Methoxy-2-propanol 107-98-2 | LC50 | 20.800 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Tetrapotassium pyrophosphate 7320-34-5 | LC50 | > 100 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-------------|---------------|---------------|---|
| Butane, n- (< 0.1 % butadiene) 106-97-8 | EC50 | 14,22 mg/l | 48 h | | not specified |
| 1-Methoxy-2-propanol 107-98-2 | EC50 | 23.300 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Tetrapotassium pyrophosphate 7320-34-5 | EC50 | > 100 mg/l | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------|---------------|---|--|
| Butane, n- (< 0.1 % butadiene) 106-97-8 | EC50 | 7,71 mg/l | 96 h | | not specified |
| 1-Methoxy-2-propanol 107-98-2 | EC50 | > 1.000 mg/l | 7 d | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Tetrapotassium pyrophosphate 7320-34-5 | EC50 | > 100 mg/l | 72 h | not specified | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|--------------|---------------|---------|--|
| 1-Methoxy-2-propanol 107-98-2 | EC0 | > 1.000 mg/l | 30 min | | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Tetrapotassium pyrophosphate 7320-34-5 | EC0 | 750 mg/l | 30 min | | not specified |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|----------------------------------|-----------------------|-----------|---------------|------------------|---|
| 1-Methoxy-2-propanol 107-98-2 | readily biodegradable | aerobic | 90 % | 29 d | OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test) |

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|----------------------------------|--------|-------------|---------------|
| 1-Methoxy-2-propanol 107-98-2 | -0,49 | | not specified |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT/ vPvB |
|---|---|
| Butane, n- (<0.1 % butadiene) 106-97-8 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 1-Methoxy-2-propanol 107-98-2 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Tetrapotassium pyrophosphate 7320-34-5 | According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances. |
| Propane 74-98-6 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

| | |
|------|------|
| ADR | 1950 |
| RID | 1950 |
| ADN | 1950 |
| IMDG | 1950 |
| IATA | 1950 |

14.2. UN proper shipping name

| | |
|------|---------------------|
| ADR | AEROSOLS |
| RID | AEROSOLS |
| ADN | AEROSOLS |
| IMDG | AEROSOLS |
| IATA | Aerosols, flammable |

14.3. Transport hazard class(es)

| | |
|------|-----|
| ADR | 2.1 |
| RID | 2.1 |
| ADN | 2.1 |
| IMDG | 2.1 |
| IATA | 2.1 |

14.4. Packing group

ADR
RID
ADN
IMDG
IATA

14.5. Environmental hazards

| | |
|------|----------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|-----------------------------------|
| ADR | not applicable Tunnelcode: (D) |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 10 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.