

# SAFETY DATA SHEET STP® Start-Stop Diesel Engine Cleaner

According to Regulation (EC) No 1907/2006, Annex II, as amended.

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name STP® Start-Stop Diesel Engine Cleaner

Product number 75200

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Fuel additive.

**Uses advised against**No specific uses advised against are identified.

## 1.3. Details of the supplier of the safety data sheet

**Supplier** Energizer Trading Ltd

Sword House Totteridge Road High Wycombe HP13 6DG

UK

Tel: +44 845 602 1995 euregulatory@energizer.com

## 1.4. Emergency telephone number

Emergency telephone +44 1495 350234

Monday - Thursday: 0830 - 1700

Friday: 0830 - 1530

National emergency telephone Product information has been submitted to the UK National Poisons Information Service

**number** (NPIS) and is accessible to medical health professionals.

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

**Health hazards** Asp. Tox. 1 - H304

Environmental hazards Not Classified

**Human health** Pneumonia may be the result if vomited material containing solvents reaches the lungs.

## 2.2. Label elements

Hazard pictograms



# STP® Start-Stop Diesel Engine Cleaner

Signal word Danger

Hazard statements H304 May be fatal if swallowed and enters airways.

**Precautionary statements** P102 Keep out of reach of children.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label

information

EUH066 Repeated exposure may cause skin dryness or cracking.

**Contains** Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics, Hydrocarbons, C10-

C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Distillates (petroleum), hydrotreated

heavy paraffinic

Supplementary precautionary P405 Store locked up.

statements

## 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%

50 - 100%

aromatics

CAS number: 64742-47-8 EC number: 926-141-6 REACH registration number: 01-

2119456620-43-XXXX

Classification

Asp. Tox. 1 - H304

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <

5 - <10%

2% aromatics

CAS number: — EC number: 918-481-9

Classification

Flam. Liq. 3 - H226 Asp. Tox. 1 - H304

2-ethylhexan-1-ol 2.5 - <5%

CAS number: 104-76-7 EC number: 203-234-3 REACH registration number: 01-

2119487289-20-XXXX

Classification

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

STOT SE 3 - H335

# STP® Start-Stop Diesel Engine Cleaner

## Distillates (petroleum), hydrotreated heavy paraffinic

1 - < 2.5%

CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-

2119484627-25-XXXX

Classification

Asp. Tox. 1 - H304

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing.

**Inhalation** If throat irritation or coughing persists, proceed as follows. Remove person to fresh air and

keep comfortable for breathing. Get medical attention if symptoms are severe or persist.

**Ingestion** Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if

symptoms are severe or persist.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at

least 15 minutes. Get medical attention if symptoms are severe or persist after washing.

**Eye contact** Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

## 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** Prolonged or repeated exposure to vapours in high concentrations may cause the following

adverse effects: Drowsiness. Dizziness.

Ingestion May cause discomfort if swallowed. Entry into the lungs following ingestion or vomiting may

cause chemical pneumonitis.

**Skin contact** Prolonged skin contact may cause redness and irritation.

**Eye contact** May cause irritation.

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. Keep affected person under observation.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

## 5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

## STP® Start-Stop Diesel Engine Cleaner

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters

Use protective equipment appropriate for surrounding materials. Wear positive-pressure selfcontained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and

gloves) will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all Personal precautions

ignition sources if safe to do so. Avoid contact with skin and eyes.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. No smoking,

sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage

must be properly labelled with correct contents and hazard symbol.

## 6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

> Section 8 of this safety data sheet. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Keep away from heat, sparks and open

flame. Provide adequate ventilation.

Advice on general occupational hygiene Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take

precautionary measures against static discharges.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

## 8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

## Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-47-8)

PNEC Not determined.

Not determined.

2-ethylhexan-1-ol (CAS: 104-76-7)

**DNEL** Workers - Inhalation; Long term systemic effects: 12.8 mg/m³

Workers - Inhalation; Long term local effects: 53.2 mg/m³ Workers - Inhalation; Short term local effects: 53.2 mg/m³ Workers - Dermal; Long term systemic effects: 23 mg/kg/day

General population - Inhalation; Long term systemic effects: 2.3 mg/m³ General population - Inhalation; Long term local effects: 26.6 mg/m³ General population - Inhalation; Short term local effects: 26.6 mg/m³ General population - Dermal; Long term systemic effects: 11.4 mg/kg/day General population - Oral; Long term systemic effects: 1.1 mg/kg/day

PNEC Fresh water; 0.017 mg/l

Fresh water, Intermittent release; 0.17 mg/l

marine water; 0.002 mg/l

STP; 10 mg/l

Sediment (Freshwater); 0.284 mg/kg Sediment (Marinewater); 0.028 mg/kg

Soil; 0.047 mg/kg Oral; 55 mg/kg

## Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

PNEC - Oral; 9.33 mg/kg

## 8.2. Exposure controls

## Protective equipment





Appropriate engineering controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Do not smoke in work area. Wash promptly with soap and water if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.

# STP® Start-Stop Diesel Engine Cleaner

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective

equipment is suitable for its intended use and is 'CE'-marked.

**Environmental exposure** 

controls

Keep container tightly sealed when not in use.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

**Appearance** Liquid.

Dark brown. Colour Odour Characteristic. Odour threshold Not determined. Not determined. pН Not relevant.

Melting point

Initial boiling point and range Not determined.

74°C Flash point

**Evaporation rate** Not determined.

Not determined. **Evaporation factor** 

Not relevant. Flammability (solid, gas)

Upper/lower flammability or

explosive limits

Not relevant.

Not relevant.

Vapour pressure Not determined.

Vapour density Not determined.

0.8237 Relative density

**Bulk density** 822.2 kg/m3

Partition coefficient Not determined.

**Auto-ignition temperature** Not relevant.

Viscosity 2.974 cSt @ 40°C

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

Not considered to be explosive.

9.2. Other information

**Explosive properties** 

**Decomposition Temperature** 

Other information No information required.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

## 10.2. Chemical stability

# STP® Start-Stop Diesel Engine Cleaner

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

products

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

None at ambient temperatures. Thermal decomposition or combustion products may include

the following substances: Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>)

Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 335.01

Skin corrosion/irritation

**Skin corrosion/irritation**Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

**Genotoxicity - in vivo**Based on available data the classification criteria are not met.

Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

**STOT - single exposure** Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

# STP® Start-Stop Diesel Engine Cleaner

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Kinematic viscosity ≤ 20.5 mm<sup>2</sup>/s. May be fatal if swallowed and enters airways.

Skin contact Repeated exposure may cause skin dryness or cracking.

Toxicological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

15,000.0

**Species** Rat

Notes (oral LD₅o) REACH dossier information. Read-across data.

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 3,160.0

mg/kg)

**Species** Rabbit

REACH dossier information. Read-across data. Notes (dermal LD₅₀)

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC50 vapours mg/l)

4,951.0

**Species** Rat

Notes (inhalation LC50) REACH dossier information. Read-across data.

ATE inhalation (vapours

mg/l)

4,951.0

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2).

Oedema score: Very slight oedema - barely perceptible (1). REACH dossier

information. Read-across data.

Serious eye damage/irritation

Serious eye Dose: 0.1 ml, 1 second, Rabbit Not irritating. REACH dossier information. Read-

damage/irritation across data.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier

information. Read-across data.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Read-across data.

Chromosome aberration: Negative. REACH dossier information. Read-across data. Genotoxicity - in vivo

Carcinogenicity

Carcinogenicity NOAEC 1100 mg/m³, Inhalation, Mouse REACH dossier information. Read-across

data.

Reproductive toxicity

Reproductive toxicity -

Fertility, One-generation study - NOAEL 750 mg/kg/day, Oral, Rat F1 REACH

fertility dossier information. Read-across data.

Reproductive toxicity -

Maternal toxicity: - NOAEL: >= 5220 mg/m³, Inhalation, Rat REACH dossier

development information.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC > 10400 mg/m³, Inhalation, Rat REACH dossier information. Read-across

data.

Aspiration hazard

Aspiration hazard 2.4 cSt @ 20°C Asp. Tox. 1 - H304

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) LD<sub>50</sub> >5000 mg/kg, Oral, Rat REACH dossier information. Read-across data.

Acute toxicity - dermal

Notes (dermal LD₅o) LD₅o >2000 mg/kg, Dermal, Rat REACH dossier information. Read-across data.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) LC<sub>50</sub> >4951 mg/m³, Inhalation, Rat REACH dossier information. Read-across data.

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2).

Oedema score: No oedema (0). REACH dossier information. Read-across data.

Serious eye damage/irritation

Serious eye Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Read-across data. Not

damage/irritation irritating.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier

information. Read-across data.

Germ cell mutagenicity

**Genotoxicity - in vitro**Gene mutation: Negative. REACH dossier information. Read-across data.

**Genotoxicity - in vivo** Chromosome aberration: Negative. REACH dossier information. Read-across data.

Carcinogenicity

Carcinogenicity NOAEC >= 138 mg/m³, Inhalation, Rat REACH dossier information. Read-across

data.

Reproductive toxicity

development

**Reproductive toxicity -** Fertility - NOAEC >=2200 mg/m³, Inhalation, Rat P REACH dossier information.

fertility Read-across data.

**Reproductive toxicity -** Developmental toxicity: - NOAEL: >= 5220 mg/m³, Inhalation, Rat REACH dossier

information.

# STP® Start-Stop Diesel Engine Cleaner

Aspiration hazard

Aspiration hazard 1.8 cSt @ 20°C/68°F REACH dossier information.

2-ethylhexan-1-ol

Acute toxicity - oral

Acute toxicity oral (LD50

3.290.0

mg/kg)

**Species** Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 3,290.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 3,000.0

mg/kg)

**Species** Rat

Notes (dermal LD50) REACH dossier information.

3.000.0 ATE dermal (mg/kg)

Acute toxicity - inhalation

ATE inhalation (vapours

11.0

mg/l)

Skin corrosion/irritation

Animal data Primary dermal irritation index: 6.75 Dose: 0.5 ml, 4 hours, Rabbit REACH dossier

information. Highly irritating.

Serious eye damage/irritation

Serious eye

Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Irritating.

damage/irritation

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information.

Carcinogenicity

Carcinogenicity NOAEL 500 mg/kg/day, Oral, Rat REACH dossier information.

Reproductive toxicity

Reproductive toxicity -

Developmental toxicity: - NOAEL: 2520 mg/kg/day, Dermal, Rat REACH dossier

development information.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 250 mg/kg/day, Oral, Rat REACH dossier information.

Aspiration hazard

Aspiration hazard 4.3 mPa s @ 40°C/104°F REACH dossier information.

Distillates (petroleum), hydrotreated heavy paraffinic

Acute toxicity - oral

Notes (oral LD₅₀)  $LD_{50} > 5000$  mg/kg, Rat, REACH dossier information.

## STP® Start-Stop Diesel Engine Cleaner

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) LD<sub>50</sub> > 2000 mg/kg, Rabbit, REACH dossier information.

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 24 hours, Rabbit Erythema/eschar score: Very slight erythema -

barely perceptible (1). Oedema score: Very slight oedema - barely perceptible (1).

REACH dossier information. Not irritating.

Serious eye damage/irritation

Serious eye

damage/irritation

Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Not irritating.

Skin sensitisation

**Skin sensitisation** Buehler test - Guinea pig: Not sensitising. REACH dossier information.

Germ cell mutagenicity

**Genotoxicity - in vitro** Chromosome aberration: Negative. REACH dossier information.

**Genotoxicity - in vivo** Chromosome aberration: Negative. REACH dossier information.

Carcinogenicity

Carcinogenicity REACH dossier information. No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Reproductive toxicity -

fertility

Screening - NOAEL ≥ 1000 mg/kg/day, Dermal, Mouse P REACH dossier

information.

Reproductive toxicity -

development

Maternal toxicity: - LOAEL: 125 mg/kg/day, Dermal, Rat REACH dossier

information.

Aspiration hazard

**Aspiration hazard** 1.99 - 847 cSt @ 40°C REACH dossier information.

## SECTION 12: Ecological information

## 12.1. Toxicity

**Toxicity** Not considered toxic to fish. However, large or frequent spills may have hazardous effects on

the environment.

## Ecological information on ingredients.

## Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute aquatic toxicity

Acute toxicity - fish LL<sub>50</sub>, 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)

REACH dossier information.

Acute toxicity - aquatic

EL<sub>50</sub>, 48 hours: > 1000 mg/l, Daphnia magna

invertebrates

REACH dossier information.

Acute toxicity - aquatic plants

EL<sub>50</sub>, 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata REACH dossier information.

Chronic aquatic toxicity

Chronic toxicity - fish early

NOELR, 28 days: 0.173 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

QSAR

REACH dossier information.

## STP® Start-Stop Diesel Engine Cleaner

Chronic toxicity - aquatic NOELR, 21 days: 1.22 mg/l, Daphnia magna

invertebrates **QSAR** 

REACH dossier information.

## Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute aquatic toxicity

Acute toxicity - fish LL<sub>50</sub>, 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)

REACH dossier information.

Acute toxicity - aquatic

invertebrates

EL<sub>50</sub>, 48 hours: > 1000 mg/l, Daphnia magna

REACH dossier information.

Acute toxicity - aquatic

plants

EL<sub>50</sub>, 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata

REACH dossier information.

Acute toxicity -

microorganisms

EL<sub>50</sub>, 48 hours: > 1000 mg/l, Tetrahymena pyriformis

REACH dossier information.

OSAR

Chronic aquatic toxicity

life stage

Chronic toxicity - fish early NOELR, 28 days: 0.101 mg/l, Oncorhynchus mykiss (Rainbow trout)

REACH dossier information.

**QSAR** 

Chronic toxicity - aquatic

invertebrates

NOELR, 21 days: 0.176 mg/l, Daphnia magna

REACH dossier information.

**QSAR** 

2-ethylhexan-1-ol

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 17.1 mg/l, Leuciscus idus (Golden orfe)

REACH dossier information.

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 39 mg/l, Daphnia magna

REACH dossier information.

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: 11.5 mg/l, Scenedesmus subspicatus

REACH dossier information.

Distillates (petroleum), hydrotreated heavy paraffinic

Acute aquatic toxicity

Acute toxicity - fish LL<sub>50</sub>, 96 hours: > 100 mg/l, Pimephales promelas (Fat-head Minnow)

NOEL, 96 hours: ≥ 100 mg/l, Pimephales promelas (Fat-head Minnow)

REACH dossier information.

Acute toxicity - aquatic

invertebrates

LL<sub>50</sub>, 24, 48, 72, 96 hours: > 10000 mg/l, Gammarus pulex

REACH dossier information.

Acute toxicity - aquatic

plants

NOEL, 72 hours: ≥ 100 mg/l, Pseudokirchneriella subcapitata

REACH dossier information.

NOEL, 10 minutes: > 1.93 mg/l, Photobacterium phosphoreum Acute toxicity -

microorganisms REACH dossier information.

Chronic aquatic toxicity

# STP® Start-Stop Diesel Engine Cleaner

Chronic toxicity - aquatic NOEL, 21 days: 10 mg/l, Daphnia magna

**invertebrates** REACH dossier information.

## 12.2. Persistence and degradability

Persistence and degradability No data available.

## Ecological information on ingredients.

## Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Biodegradation** Water - Degradation ~ 5%: 3 days

Water - Degradation 69: 28 days REACH dossier information.

Readily biodegradable but failing the 10-day window.

## Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation Water - Degradation 80%: 28 days

REACH dossier information.

Read-across data.

Readily biodegradable but failing the 10-day window.

## 2-ethylhexan-1-ol

Biodegradation Water - Degradation 79 - 99.9%: 2 weeks

REACH dossier information.

The substance is readily biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

## Ecological information on ingredients.

## Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Partition coefficient Scientifically unjustified. REACH dossier information.

## Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of

this product.

## 2-ethylhexan-1-ol

**Bioaccumulative potential** BCF: 25.33, REACH dossier information.

Partition coefficient log Pow: 2.9 REACH dossier information.

## 12.4. Mobility in soil

**Mobility** The product is soluble in water.

## Ecological information on ingredients.

## Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Mobility** The product has poor water-solubility.

# STP® Start-Stop Diesel Engine Cleaner

Surface tension 26.4 mN/m @ 25°C

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

**Mobility** The product contains organic solvents which will evaporate easily from all surfaces.

The product contains substances which are insoluble in water and which sediment

in water systems.

**Surface tension** 25.3 mN/m @ 25°C/77°F REACH dossier information.

2-ethylhexan-1-ol

**Surface tension** 47 mN/m @ 20°C/68°F REACH dossier information.

## 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

## Ecological information on ingredients.

## Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria. assessment

## 12.6. Other adverse effects

Other adverse effects Not determined.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

## SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

## 14.1. UN number

Not applicable.

## 14.2. UN proper shipping name

Not applicable.

## 14.3. Transport hazard class(es)

No transport warning sign required.

## 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

## Environmentally hazardous substance/marine pollutant

No.

## 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

ATE: Acute Toxicity Estimate.

DNEL: Derived No Effect Level.

LC<sub>50</sub>: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

BCF: Bioconcentration Factor.

Classification procedures according to Regulation (EC) 1272/2008

Asp. Tox. 1 - H304: Calculation method., Expert judgement.

Revision comments Section 1: Identification of the substance/mixture and of the company/undertaking // 1.3.

Details of the supplier of the safety data sheet.

Revision date 19/03/2020

Revision 2

Supersedes date 26/06/2017

SDS number 1056

Hazard statements in full H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.