

SAFETY DATA SHEET STP® Emissions Reducer – Petrol

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STP® Emissions Reducer – Petrol

Product number 78400

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fuel additive.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Energizer Trading Ltd

Sword House Totteridge Road High Wycombe HP13 6DG

UK

Tel: +44 845 602 1995 euregulatory@energizer.com

1.4. Emergency telephone number

Emergency telephone +44 1495 350234

Monday - Thursday: 0830 - 1700

Friday: 0830 - 1530

National emergency telephone Product information has been submitted to the UK National Poisons Information Service

number (NPIS) and is accessible to medical health professionals.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 3 - H412

Human health Pneumonia may be the result if vomited material containing solvents reaches the lungs.

2.2. Label elements

Hazard pictograms



STP® Emissions Reducer - Petrol

Signal word Danger

Hazard statements H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P102 Keep out of reach of children.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label

information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics, Hydrocarbons, C10,

aromatics, >1% naphthalene

Supplementary precautionary

P273 Avoid release to the environment.

statements P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%

50 - 100%

aromatics

CAS number: 64742-47-8 EC number: 926-141-6 REACH registration number: 01-

2119456620-43-XXXX

Classification

Asp. Tox. 1 - H304

Hydrocarbons, C10, aromatics, >1% naphthalene

2 - <5%

CAS number: — EC number: 919-284-0 REACH registration number: 01-

2119463588-24-XXXX

This is a complex mixture of constituents, a UVCB substance of variable composition. To prevent over-classification the Carc. 2 – H351 has been removed from the registered classification as it is applied to the constituent chemical Naphthalene (CAS 91-20-3).

Classification

STOT SE 3 - H336 Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

Polyolefin alkyl phenol alkyl amine

1 - < 2.5%

CAS number: —

Classification

Skin Irrit. 2 - H315

STP® Emissions Reducer - Petrol

Alkaryl polyether

CAS number: —

1 - <2.5%

Classification

Aquatic Chronic 3 - H412

1,2,4-Trimethylbenzene

CAS number: 95-63-6

EC number: 202-436-9

Classification
Flam. Liq. 3 - H226
Acute Tox. 4 - H332

Skin Irrit. 2 - H315
Eye Irrit. 2 - H319
STOT SE 3 - H335
Aquatic Chronic 2 - H411

Naphthalene 0.025 - <0.25%

CAS number: 91-20-3 EC number: 202-049-5 M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Flam. Sol. 2 - H228 Acute Tox. 4 - H302 Carc. 2 - H351

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Mesitylene 0.025 - <0.25%

Classification

Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411

Cumene <0.025%

CAS number: 98-82-8 EC number: 202-704-5

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing.

Inhalation If throat irritation or coughing persists, proceed as follows. Remove person to fresh air and

keep comfortable for breathing. Get medical attention if symptoms are severe or persist.

Ingestion Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if

symptoms are severe or persist.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at

least 15 minutes. Get medical attention if symptoms are severe or persist after washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Prolonged or repeated exposure to vapours in high concentrations may cause the following

adverse effects: Drowsiness. Dizziness.

Ingestion May cause discomfort if swallowed. Entry into the lungs following ingestion or vomiting may

cause chemical pneumonitis.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact May cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and

gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all

ignition sources if safe to do so. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. No smoking,

sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section

13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

Section 8 of this safety data sheet. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Keep away from heat, sparks and open

flame. Provide adequate ventilation.

Advice on general occupational hygiene

Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take

precautionary measures against static discharges.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

1,2,4-Trimethylbenzene

Long-term exposure limit (8-hour TWA): WEL 25 ppm 125 mg/m³

Mesitylene

Long-term exposure limit (8-hour TWA): WEL 25 ppm 125 mg/m³

Cumene

Long-term exposure limit (8-hour TWA): WEL 25 ppm 125 mg/m³ Short-term exposure limit (15-minute): WEL 50 ppm 250 mg/m³

WEL = Workplace Exposure Limit. Sk = Can be absorbed through the skin.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-47-8)

DNEL Not determined.PNEC Not determined.

Hydrocarbons, C10, aromatics, >1% naphthalene

DNEL Workers - Inhalation; Long term systemic effects: 151 mg/m³

Workers - Dermal; Long term systemic effects: 12.5 mg/kg/day General population - Inhalation; Long term systemic effects: 32 mg/m³ General population - Dermal; Long term systemic effects: 7.5 mg/kg/day General population - Oral; Long term systemic effects: 7.5 mg/kg/day

PNEC Not determined.

Hydrocarbons, C9, aromatics

DNEL Workers - Inhalation; Long term systemic effects: 150 mg/m³

Workers - Dermal; Long term systemic effects: 25 mg/kg/day

General population - Inhalation; Long term systemic effects: 32 mg/m³ General population - Dermal; Long term systemic effects: 11 mg/kg/day General population - Oral; Long term systemic effects: 11 mg/kg/day

PNEC Not determined.

2-ethylhexan-1-ol (CAS: 104-76-7)

DNEL Workers - Inhalation; Long term systemic effects: 12.8 mg/m³

Workers - Inhalation; Long term local effects: 53.2 mg/m³ Workers - Inhalation; Short term local effects: 53.2 mg/m³ Workers - Dermal; Long term systemic effects: 23 mg/kg/day

General population - Inhalation; Long term systemic effects: 2.3 mg/m³ General population - Inhalation; Long term local effects: 26.6 mg/m³ General population - Inhalation; Short term local effects: 26.6 mg/m³ General population - Dermal; Long term systemic effects: 11.4 mg/kg/day General population - Oral; Long term systemic effects: 1.1 mg/kg/day

PNEC Fresh water; 0.017 mg/l

Fresh water, Intermittent release; 0.17 mg/l

marine water; 0.002 mg/l

STP; 10 mg/l

Sediment (Freshwater); 0.284 mg/kg Sediment (Marinewater); 0.028 mg/kg

Soil; 0.047 mg/kg Oral; 55 mg/kg

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment.

STP® Emissions Reducer - Petrol

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles

or face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Do not smoke in work area. Wash promptly with soap and water if skin becomes

contaminated. Wash at the end of each work shift and before eating, smoking and using the

toilet.

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective

equipment is suitable for its intended use and is 'CE'-marked.

Environmental exposure

controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Colourless to pale yellow.

Odour Characteristic. Kerosene.

Odour threshold Not determined.

pH Not determined.

Melting point Not relevant.

Initial boiling point and range Not determined.

Flash point 74.5°C

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) Not relevant.

Upper/lower flammability or

explosive limits

Not relevant.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 0.8137

Bulk density 812.2 kg/m³

Partition coefficient Not determined.

Auto-ignition temperature Not relevant.

Decomposition Temperature Not relevant.

STP® Emissions Reducer - Petrol

Viscosity Not determined.

Explosive properties Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None at ambient temperatures. Thermal decomposition or combustion products may include

the following substances: Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD50) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC50) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

STP® Emissions Reducer - Petrol

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Genotoxicity - in vivoBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Kinematic viscosity ≤ 20.5 mm²/s. May be fatal if swallowed and enters airways.

Skin contact Repeated exposure may cause skin dryness or cracking.

Toxicological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

15,000.0

Species Rat

Notes (oral LD₅o) REACH dossier information. Read-across data.

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,160.0

mg/kg)

Species

Rabbit

Notes (dermal LD₅₀) REACH dossier information. Read-across data.

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

Acute toxicity inhalation

4,951.0

(LC50 vapours mg/l)

Species Rat

Notes (inhalation LC50) REACH dossier information. Read-across data.

ATE inhalation (vapours

4,951.0

mg/l)

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2).

Oedema score: Very slight oedema - barely perceptible (1). REACH dossier

information. Read-across data.

STP® Emissions Reducer – Petrol

Serious eye damage/irritation

Serious eye Dose: 0.1 ml, 1 second, Rabbit Not irritating. REACH dossier information. Read-

damage/irritation across data.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier

information. Read-across data.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Read-across data.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Read-across data.

Carcinogenicity

Carcinogenicity NOAEC 1100 mg/m³, Inhalation, Mouse REACH dossier information. Read-across

data.

Reproductive toxicity

Reproductive toxicity -

fertility

Fertility, One-generation study - NOAEL 750 mg/kg/day, Oral, Rat F1 REACH

dossier information. Read-across data.

Reproductive toxicity -

development

Maternal toxicity: - NOAEL: >= 5220 mg/m³, Inhalation, Rat REACH dossier

information.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC > 10400 mg/m³, Inhalation, Rat REACH dossier information. Read-across

data

Aspiration hazard

Aspiration hazard 2.4 cSt @ 20°C Asp. Tox. 1 - H304

Hydrocarbons, C10, aromatics, >1% naphthalene

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

5,558.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 5,558.0

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Very slight erythema - barely

perceptible (1). Oedema score: No oedema (0). REACH dossier information.

Serious eye damage/irritation

Serious eye

damage/irritation

Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Not irritating.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier

information. Read-across data.

STP® Emissions Reducer - Petrol

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. REACH dossier information.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity -

Three-generation study - NOAEC >= 1500 ppm, Inhalation, Rat REACH dossier information. Read-across data.

fertility

Reproductive toxicity - development

Developmental toxicity: - NOAEL: > 450 mg/kg/day, Oral, Rat REACH dossier

information. Read-across data.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC > 0.38 mg/l, Inhalation, Rat REACH dossier information.

Aspiration hazard

Aspiration hazard 1.38 cSt @ 20°C/68°F REACH dossier information.

Polyolefin alkyl phenol alkyl amine

Acute toxicity - oral

Notes (oral LD50) LD50 >5000 mg/kg, Oral, Rat Read-across data.

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rat Read-across data.

Skin corrosion/irritation

Animal data Irritating to skin. (@ >50%)

Serious eye damage/irritation

Serious eye

damage/irritation

Not irritating.

Alkaryl polyether

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >3000 mg/kg, Dermal, Rabbit

Skin corrosion/irritation

Skin corrosion/irritation Not irritating. Read-across data.

Serious eye damage/irritation

Serious eye

Not irritating. Read-across data.

damage/irritation
Skin sensitisation

Skin sensitisation Guinea pig Not sensitising. Read-across data.

Germ cell mutagenicity

Genotoxicity - in vitroBacterial reverse mutation test: Negative. Read-across data.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)

REACH dossier information.

Acute toxicity - aquatic

EL₅₀, 48 hours: > 1000 mg/l, Daphnia magna

invertebrates

REACH dossier information.

Acute toxicity - aquatic

EL₅₀, 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata

plants

REACH dossier information.

Chronic aquatic toxicity

Chronic toxicity - fish early

NOELR, 28 days: 0.173 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

REACH dossier information.

QSAR

Chronic toxicity - aquatic

NOELR, 21 days: 1.22 mg/l, Daphnia magna

invertebrates

REACH dossier information.

Hydrocarbons, C10, aromatics, >1% naphthalene

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: 2 - 5 mg/l, Oncorhynchus mykiss (Rainbow trout)

REACH dossier information.

Acute toxicity - aquatic

EL₅₀, 48 hours: 10 mg/l, Daphnia magna

invertebrates

REACH dossier information.

Acute toxicity - aquatic

plants

EL₅₀, 72 hours: 1 - 3 mg/l, Pseudokirchneriella subcapitata

REACH dossier information.

Acute toxicity -NOELR, 48 hours: 1.892 mg/l, Tetrahymena pyriformis

REACH dossier information. microorganisms

QSAR

Chronic aquatic toxicity

Chronic toxicity - fish early NOELR, 28 days: 0.487 mg/l, Oncorhynchus mykiss (Rainbow trout)

REACH dossier information.

QSAR

Chronic toxicity - aquatic

invertebrates

life stage

NOELR, 21 days: 0.851 mg/l, Daphnia magna

REACH dossier information.

QSAR

Polyolefin alkyl phenol alkyl amine

Acute aquatic toxicity

Acute toxicity - aquatic

plants

EC₅₀, 96 hours: 5.4 mg/l, Algae

Chronic aquatic toxicity

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 3.38 mg/l, Daphnia magna

STP® Emissions Reducer - Petrol

Alkaryl polyether

Toxicity Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradation Water - Degradation ~ 5%: 3 days

Water - Degradation 69: 28 days REACH dossier information.

Readily biodegradable but failing the 10-day window.

Hydrocarbons, C10, aromatics, >1% naphthalene

Biodegradation Water - Degradation 57.95 %: 28 days

REACH dossier information. Inherently biodegradable.

Polyolefin alkyl phenol alkyl amine

Biodegradation Water - Degradation 4%: 28 days

Not readily biodegradable.

Alkaryl polyether

Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Partition coefficient Scientifically unjustified. REACH dossier information.

Hydrocarbons, C10, aromatics, >1% naphthalene

Bioaccumulative potential No data available on bioaccumulation.

Polyolefin alkyl phenol alkyl amine

Bioaccumulative potential No data available on bioaccumulation.

Alkaryl polyether

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is soluble in water.

STP® Emissions Reducer - Petrol

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Mobility The product has poor water-solubility.

Surface tension 26.4 mN/m @ 25°C

Hydrocarbons, C10, aromatics, >1% naphthalene

Surface tension 30.4 mN/m @ 25°C/77°F REACH dossier information.

Polyolefin alkyl phenol alkyl amine

Mobility No data available.

Alkaryl polyether

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

Polyolefin alkyl phenol alkyl amine

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria. assessment

Alkaryl polyether

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria. assessment

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IMDG: International Maritime Dangerous Goods.

IATA: International Air Transport Association.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

ATE: Acute Toxicity Estimate.

DNEL: Derived No Effect Level.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

BCF: Bioconcentration Factor.

Classification procedures according to Regulation (EC) 1272/2008

Asp. Tox. 1 - H304: Calculation method., On basis of test data. Aquatic Chronic 3 - H412:

Calculation method.

STP® Emissions Reducer – Petrol

Revision comments Section 1: Identification of the substance/mixture and of the company/undertaking // 1.3.

Details of the supplier of the safety data sheet. Section 2: Hazards identification // 2.2. Label elements. Section 3: Composition/information on ingredients // 3.2 Mixtures. Section 8:

Exposure controls/personal protection // 8.1. Control parameters.

Revision date 19/03/2020

Revision 1

Supersedes date 04/04/2016

SDS number 886

Hazard statements in full H226 Flammable liquid and vapour.

H228 Flammable solid. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.