



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ EGR CLEANER

Product code : 887071

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cleaner.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global
Operations
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person : SDS@valvolineglobal.com
responsible for the SDS

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single	H336: May cause drowsiness or dizziness.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

exposure, Category 3, Central nervous system

Specific target organ toxicity - single exposure, Category 3, Respiratory system

Specific target organ toxicity - repeated exposure, Category 2

Long-term (chronic) aquatic hazard, Category 3

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust or mist.
P271 Use only outdoors or in a well-ventilated area.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane

METHYL ETHYL KETONE

ISOPROPANOL

XYLENE

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane	64742-49-0 265-151-9 649-328-00-1 01-2119475514-35-xxxx	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
METHYL ETHYL KETONE	78-93-3 201-159-0 606-002-00-3 01-2119457290-43-xxxx	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 20 - < 25
ISOPROPANOL	67-63-0 200-661-7 603-117-00-0 01-2119457558-25-xxxx	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 20 - < 25
XYLENE	1330-20-7 215-535-7 601-022-00-9	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315	>= 20 - < 25



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

	01-2119488216-32-xxxx	Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Central nervous system, Liver, Kidney) Asp. Tox. 1; H304	
Substances with a workplace exposure limit :			
BUTANE NORMAL	106-97-8 203-448-7 649-196-00-5 01-2119474691-32-xxxx	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | | |
|-------------------------|---|---|
| General advice | : | Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended. |
| If inhaled | : | Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : | If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : | Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Induce vomiting immediately and call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|--|
| Symptoms | : | No symptoms known or expected. |
| Risks | : | Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure. |
| | : | Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|--|
| Treatment | : | No hazards which require special first aid measures. |
| | : | Treat symptomatically. |

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|------------------------------|---|---|
| Suitable extinguishing media | : | Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
|------------------------------|---|---|

- | | | |
|--------------------------------|---|-----------------------|
| Unsuitable extinguishing media | : | High volume water jet |
|--------------------------------|---|-----------------------|

5.2 Special hazards arising from the substance or mixture

- | | | |
|--------------------------------------|---|---|
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | carbon dioxide and carbon monoxide |



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

- Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Container may be opened only under exhaust ventilation hood.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
METHYL ETHYL KETONE	78-93-3	TWA	200 ppm 600 mg/m3	GB EH40



Valvoline™
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	300 ppm 899 mg/m3	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	200 ppm 600 mg/m3	2000/39/EC
		Further information: Indicative		
		STEL	300 ppm 900 mg/m3	2000/39/EC
		Further information: Indicative		
ISOPROPANOL	67-63-0	TWA	400 ppm 999 mg/m3	GB EH40
		STEL	500 ppm 1,250 mg/m3	GB EH40
XYLENE	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	100 ppm 441 mg/m3	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	50 ppm 221 mg/m3	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m3	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
BUTANE NORMAL	106-97-8	TWA	600 ppm 1,450 mg/m3	GB EH40
		Further information: Capable of causing cancer and/or heritable genetic damage.		
		STEL	750 ppm 1,810 mg/m3	GB EH40
		Further information: Capable of causing cancer and/or heritable genetic damage.		



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
METHYL ETHYL KETONE	78-93-3	butan-2-one: 70 micromol per litre (Urine)	After shift	GB EH40 BAT
XYLENE	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Hand protection	:	
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 143
Filter type	:	Particulates type (P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	aerosol
Colour	:	colourless
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: 11.5 %(V)
Lower explosion limit / Lower flammability limit	: 0.6 %(V)
Vapour pressure	: 105 hPa (20 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.73 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: 500 °C
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

9.2 Other information

Self-ignition	: not auto-flammable
---------------	----------------------



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Acids
Aldehydes
alkalis
Amines
Copper
Copper alloys
Ethylene oxide
halogens
isocyanates
strong alkalis
Strong oxidizing agents
Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg
Remarks: The toxicological data has been taken from
products of similar composition.

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2,800 - 3,100 mg/kg
Assessment: The substance or mixture has no acute dermal
toxicity
Remarks: The toxicological data has been taken from
products of similar composition.

METHYL ETHYL KETONE:

Acute oral toxicity : LD50 (Rat): 2,300 - 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

XYLENE:

Acute oral toxicity : LD50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 29 mg/l, 6700 ppm
Exposure time: 4 h



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Rat): > 50000 ppm
Exposure time: 2 h
Test atmosphere: gas

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Result : Irritating to skin.

METHYL ETHYL KETONE:

Result : No skin irritation

ISOPROPANOL:

Result : Slight, transient irritation

XYLENE:

Assessment : Irritating to skin.

Result : Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Result : Slight, transient irritation



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

METHYL ETHYL KETONE:

Result : Irritating to eyes.

ISOPROPANOL:

Result : Irritating to eyes.

XYLENE:

Result : Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Germ cell mutagenicity- : Classified based on benzene content < 0.1% (Regulation (EC)
Assessment 1272/2008, Annex VI, Part 3, Note P)

BUTANE NORMAL:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)
Assessment 1272/2008, Annex VI, Part 3, Note P)



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Product:

Assessment : May cause drowsiness or dizziness., May cause respiratory irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Assessment : May cause drowsiness or dizziness.

METHYL ETHYL KETONE:

Assessment : May cause drowsiness or dizziness.

ISOPROPANOL:

Assessment : May cause drowsiness or dizziness.

XYLENE:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Product:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Components:

XYLENE:

Target Organs : Central nervous system, Liver, Kidney

Assessment : May cause damage to organs through prolonged or repeated exposure.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

May be fatal if swallowed and enters airways.

METHYL ETHYL KETONE:

May be harmful if swallowed and enters airways.

XYLENE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

Components:

METHYL ETHYL KETONE:

Remarks : Central nervous system

ISOPROPANOL:

Remarks : Central nervous system

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 11.4 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia hyalina (water flea)): 3 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 10 - 30 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.17 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 2; Toxic to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 2; Toxic to aquatic life with long lasting effects.

METHYL ETHYL KETONE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 3,130 - 3,320 mg/l
Exposure time: 96 h
Test Type: flow-through test



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,025 - 6,440 mg/l
Exposure time: 48 h
Test Type: static test
Remarks: Intoxication

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

ISOPROPANOL:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5,770 - 7,450 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h
Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

XYLENE:

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 - < 1,000 mg/l
Exposure time: 24 h
Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

BUTANE NORMAL:

Toxicity to fish : Remarks: No toxicity at the limit of solubility
QSAR

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100 mg/l



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Exposure time: 48 h
Remarks: QSAR

Toxicity to algae/aquatic plants : EC50 (green algae): Expected 7.7 mg/l
Exposure time: 96 h
Remarks: QSAR

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 2; Toxic to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.

12.2 Persistence and degradability

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Biodegradability : Inoculum: activated sludge
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

XYLENE:

Physico-chemical removability : Remarks: The product evaporates readily.

BUTANE NORMAL:

Biodegradability : Result: Readily biodegradable.
Remarks: The toxicological data has been taken from products of similar composition.

12.3 Bioaccumulative potential

Components:

METHYL ETHYL KETONE:

Partition coefficient: n-octanol/water : log Pow: 0.29

ISOPROPANOL:

Partition coefficient: n-octanol/water : log Pow: 0.05

XYLENE:

Partition coefficient: n-octanol/water : log Pow: 3.16



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

octanol/water

BUTANE NORMAL:

Partition coefficient: n- : log Pow: 2.89
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

SECTION 14: Transport information

14.1 UN number

ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

ADR	:	2
RID	:	2
IMDG	:	2.1
IATA	:	2.1

14.4 Packing group

ADR		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)

RID		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Hazard Identification Number	:	23
Labels	:	2.1

IMDG		
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U

IATA (Cargo)



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA_P (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:
ISOBTANE (Number on list 29, 28)

UK REACH Candidate list of substances of very high : Not applicable



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) P3a FLAMMABLE AEROSOLS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

18 Liquefied flammable gases (including LPG) and natural gas

according to Detergents Regulation EC 648/2004 : 30 % and more: Aliphatic hydrocarbons
15 % or over but less than 30 %: Aromatic hydrocarbons

Regulation (EC) No. 648/2004, as amended : 30 % and more: Aliphatic hydrocarbons
15 % or over but less than 30 %: Aromatic hydrocarbons

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H220	: Extremely flammable gas.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H280	: Contains gas under pressure; may explode if heated.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Press. Gas	: Gases under pressure



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ EGR CLEANER

Version: 6.0

Revision Date: 18.07.2023

Print Date: 02/10/2025

Further information

Internal information : 000000274851

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Calculation method
Based on product data or assessment
Based on product data or assessment
Based on product data or assessment
Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN