



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 22

TEROSON VR 105 known as Teroson Screen Cleaner 500 ML

SDS No. : 446051  
V007.0

Revision: 15.08.2025

printing date: 27.08.2025

Replaces version from: 17.06.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TEROSON VR 105 known as Teroson Screen Cleaner 500 ML  
UFI: EN9W-QWVD-Y201-PEVA

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:  
Cleaner

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd  
Adhesives  
Wood Lane End  
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website [www.mysds.henkel.com](http://www.mysds.henkel.com) or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Aerosols

Category 1

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

#### 2.2. Label elements

##### Label elements (CLP):

##### Hazard pictogram:



##### Signal word:

Danger

**Hazard statement:** H222 Extremely flammable aerosol.  
H229 Pressurized container: May burst if heated.

**Supplemental information** Contains: Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine  
**May produce an allergic reaction.**

**Precautionary statement:** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
**Prevention** No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.

**Precautionary statement:** P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
**Storage**

### 2.3. Other hazards

The aerosol container is under pressure. Do not expose to high temperatures.

**Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):**

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS No. EC No. REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Propan-2-ol 67-63-0 200-661-7 01-2119457558-25	1- < 5 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
Butane, n- (< 0.1 % butadiene) 106-97-8 203-448-7 01-2119474691-32	1- < 5 %	Press. Gas H280 Flam. Gas 1A, H220		
1-Butoxypropan-2-ol 5131-66-8 225-878-4 01-2119475527-28	1- < 5 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Flam. Liq. 3, H226		
Propane 74-98-6 200-827-9 01-2119486944-21	1- < 3 %	Flam. Gas 1A, H220 Press. Gas H280		
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9 01-2119980932-27	0,1- < 1 %	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Dam. 1, H318		
ammonia, aqueous solution 1336-21-6 215-647-6 01-2119488876-14	0,1- < 1 %	Aquatic Acute 1, H400 Aquatic Chronic 2, H411 Skin Corr. 1B, H314 Acute Tox. 4, Inhalation, H332 STOT SE 3, H335	STOT SE 3; H335; C >= 5 % ===== M acute = 1 ===== inhalation:	EU OEL

**If no ATE values are displayed, please refer to LD/LC50 values in Section 11.  
For full text of the H - statements and other abbreviations see section 16 "Other information".**

The hazard classification of this product is based solely on the mixture present within the aerosol, excluding the propellant gases. The information provided in Section 3 is based on the combination of the mixture and propellant gases.

**Declaration of ingredients according to Detergent Regulation 648/2004/EC**

5 - 15 %	aliphatic hydrocarbons
	non-ionic surfactants
contains	Perfumes
Allergenic fragrance ingredients >=100 ppm:	Limonene, Benzyl Alcohol

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation:**

Move to fresh air, consult doctor if complaint persists.

**Skin contact:**

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:  
not relevant.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

## SECTION 5: Firefighting measures

**5.1. Extinguishing media**

**Suitable extinguishing media:**

All common extinguishing agents are suitable.

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**

In case of fire toxic gases can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus.

Wear protective equipment.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

Avoid open flames and sources of ignition.

Ground/bond container and receiving equipment.

Use explosion proof electric equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

**Hygiene measures:**

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container.

Ensure good ventilation/extraction.

**7.3. Specific end use(s)**  
Cleaner

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Propan-2-ol 67-63-0 [PROPAN-2-OL]	400	999	Time Weighted Average (TWA):		EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	500	1.250	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Butane 106-97-8 [Butane]	600	1.450	Time Weighted Average (TWA):		EH40 WEL
Butane 106-97-8 [Butane]	750	1.810	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Ammonia, aqueous solution 1336-21-6 [Ammonia, anhydrous]	35	25	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Ammonia, aqueous solution 1336-21-6 [Ammonia, anhydrous]	25	18	Time Weighted Average (TWA):		EH40 WEL
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	50	36	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	20	14	Time Weighted Average (TWA):	Indicative	ECTLV

#### Occupational Exposure Limits

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]	200		Time Weighted Average (TWA):		IR_OEL
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]	400		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Butane 106-97-8 [N-BUTANE]	1.000		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	50	36	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	20	14	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	50	36	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	20	14	Time Weighted Average (TWA):	Indicative	ECTLV

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Propan-2-ol 67-63-0	aqua (freshwater)		140,9 mg/l				
Propan-2-ol 67-63-0	aqua (marine water)		140,9 mg/l				
Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	Soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)		140,9 mg/l				
Propan-2-ol 67-63-0	sewage treatment plant (STP)		2251 mg/l				
Propan-2-ol 67-63-0	oral				160 mg/kg		
1-Butoxypropan-2-ol 5131-66-8	aqua (freshwater)		0,525 mg/l				
1-Butoxypropan-2-ol 5131-66-8	aqua (marine water)		0,0525 mg/l				
1-Butoxypropan-2-ol 5131-66-8	aqua (intermittent releases)		5,25 mg/l				
1-Butoxypropan-2-ol 5131-66-8	sewage treatment plant (STP)		10 mg/l				
1-Butoxypropan-2-ol 5131-66-8	sediment (freshwater)				2,36 mg/kg		
1-Butoxypropan-2-ol 5131-66-8	sediment (marine water)				0,236 mg/kg		
1-Butoxypropan-2-ol 5131-66-8	Soil				0,16 mg/kg		
Reaction product of Maleic anhydride, 2- Ethylhexylamine and Triethanolamine 1471311-93-9	aqua (freshwater)		0,1 mg/l				
Reaction product of Maleic anhydride, 2- Ethylhexylamine and Triethanolamine 1471311-93-9	aqua (marine water)		0,01 mg/l				
Reaction product of Maleic anhydride, 2- Ethylhexylamine and Triethanolamine 1471311-93-9	aqua (intermittent releases)		1 mg/l				
Reaction product of Maleic anhydride, 2- Ethylhexylamine and Triethanolamine 1471311-93-9	sewage treatment plant (STP)		100 mg/l				
Reaction product of Maleic anhydride, 2- Ethylhexylamine and Triethanolamine 1471311-93-9	sediment (freshwater)				4,85 mg/kg		
Reaction product of Maleic anhydride, 2- Ethylhexylamine and Triethanolamine 1471311-93-9	sediment (marine water)				0,485 mg/kg		
Reaction product of Maleic anhydride, 2- Ethylhexylamine and Triethanolamine 1471311-93-9	Soil				0,909 mg/kg		
ammonia, aqueous solution 1336-21-6	aqua (freshwater)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (marine water)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (intermittent releases)		0,0068 mg/l				

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Propan-2-ol 67-63-0	Workers	dermal	Long term exposure - systemic effects		888 mg/kg	
Propan-2-ol 67-63-0	Workers	inhalation	Long term exposure - systemic effects		500 mg/m3	
Propan-2-ol 67-63-0	General population	dermal	Long term exposure - systemic effects		319 mg/kg	
Propan-2-ol 67-63-0	General population	inhalation	Long term exposure - systemic effects		89 mg/m3	
Propan-2-ol 67-63-0	General population	oral	Long term exposure - systemic effects		26 mg/kg	
1-Butoxypropan-2-ol 5131-66-8	Workers	dermal	Long term exposure - systemic effects		52 mg/kg	
1-Butoxypropan-2-ol 5131-66-8	Workers	inhalation	Long term exposure - systemic effects		147 mg/m3	
1-Butoxypropan-2-ol 5131-66-8	General population	dermal	Long term exposure - systemic effects		22 mg/kg	
1-Butoxypropan-2-ol 5131-66-8	General population	inhalation	Long term exposure - systemic effects		43 mg/m3	
1-Butoxypropan-2-ol 5131-66-8	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	
1-Butoxypropan-2-ol 5131-66-8	Workers	dermal	Acute/short term exposure - local effects		50 %	
1-Butoxypropan-2-ol 5131-66-8	Workers	dermal	Long term exposure - local effects		50 %	
1-Butoxypropan-2-ol 5131-66-8	General population	dermal	Acute/short term exposure - local effects		50 %	
1-Butoxypropan-2-ol 5131-66-8	General population	dermal	Long term exposure - local effects		50 %	
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	Workers	inhalation	Long term exposure - systemic effects		35,26 mg/m3	
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	Workers	dermal	Long term exposure - systemic effects		10 mg/kg	
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	General population	inhalation	Long term exposure - systemic effects		8,7 mg/m3	
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	General population	dermal	Long term exposure - systemic effects		5 mg/kg	
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	General population	oral	Long term exposure - systemic effects		5 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	inhalation	Long term exposure - systemic effects		47,6 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	inhalation	Acute/short term exposure - systemic effects		47,6 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	inhalation	Long term exposure - local effects		14 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Acute/short term exposure - local		36 mg/m3	

			effects			
ammonia, aqueous solution 1336-21-6	Workers	dermal	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	dermal	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	inhalation	Long term exposure - systemic effects		23,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	inhalation	Acute/short term exposure - systemic effects		23,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	inhalation	Long term exposure - local effects		2,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	inhalation	Acute/short term exposure - local effects		7,2 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	dermal	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	dermal	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	oral	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	oral	Acute/short term exposure - systemic effects		6,8 mg/kg	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

In case of aerosol forming ensure sufficient suction and ventilation.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; ≥ 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; ≥ 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Delivery form	aerosol
Colour	White
Odor	Characteristic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	Not applicable, Not measurable since pressurized gas pack.
Initial boiling point	93 °C (199.4 °F)
Flammability	The product is not flammable.
Explosive limits	
lower	7,7 %(V);
Flash point	42 °C (107.6 °F)
Auto-ignition temperature	> 300 °C (> 572 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	10,8
(23 °C (73 °F); Conc.: 100 % product; Solvent: None)	
Viscosity (kinematic)	1,33 mm <sup>2</sup> /s
(40 °C (104 °F); )	
Solubility (qualitative)	fully miscible
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure	Mixture
(20 °C (68 °F))	54 hPa
Density	0,9882 g/cm <sup>3</sup> no method / method unknown
(20 °C (68 °F))	
Bulk density	Not applicable
Relative vapour density:	Currently under determination
Particle characteristics	Not applicable
	Product is a liquid

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Aerosols:	Classified as Aerosol category 1 because it contains more than 1 % (by mass) flammable components or has a heat of combustion of at least 20 kJ/g and is not submitted to the flammability classification procedures
-----------	--

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None if used for intended purpose.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

**10.4. Conditions to avoid**

Temperatures over appr. 50 °C  
Heat, flames, sparks and other sources of ignition.

**10.5. Incompatible materials**

None if used properly.

**10.6. Hazardous decomposition products**

No decomposition if used according to specifications.

**SECTION 11: Toxicological information**

**General toxicological information:**

An allergic reaction cannot be excluded after repeated skin contact.

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
1-Butoxypropan-2-ol 5131-66-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction product of Maleic anhydride, 2- Ethylhexylamine and Triethanolamine 1471311-93-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	274200 ppm	gas	4 h	rat	not specified
1-Butoxypropan-2-ol 5131-66-8	LC50	> 651 ppm	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Propane 74-98-6	LC50	> 800000 ppm	gas	15 min	rat	not specified
ammonia, aqueous solution 1336-21-6	Acute toxicity estimate (ATE)	6570 ppm	gas	4 h		Expert judgement

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Propan-2-ol 67-63-0	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1-Butoxypropan-2-ol 5131-66-8	moderately irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
ammonia, aqueous solution 1336-21-6	corrosive	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Propan-2-ol 67-63-0	Category 2A (irritating to eyes)		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1-Butoxypropan-2-ol 5131-66-8	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
ammonia, aqueous solution 1336-21-6	corrosive			not specified

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1-Butoxypropan-2-ol 5131-66-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
ammonia, aqueous solution 1336-21-6	not sensitising	not specified	guinea pig	not specified

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Propan-2-ol 67-63-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1-Butoxypropan-2-ol 5131-66-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1-Butoxypropan-2-ol 5131-66-8	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1-Butoxypropan-2-ol 5131-66-8	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propane 74-98-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propane 74-98-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
ammonia, aqueous solution 1336-21-6	negative	bacterial reverse mutation assay (e.g Ames test)	not specified		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Propane 74-98-6	negative			Drosophila melanogaster	not specified
Propane 74-98-6	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
ammonia, aqueous solution 1336-21-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)
ammonia, aqueous solution 1336-21-6	not carcinogenic	oral: feed	104 w daily	rat		OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Propan-2-ol 67-63-0	NOAEL P 853 mg/kg	One generation study	oral: drinking water	rat	equivalent or similar to OECD Guideline 415 (One- Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 500 mg/kg NOAEL F1 1.000 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Butane, n- (< 0.1 % butadiene) 106-97-8	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
1-Butoxypropan-2-ol 5131-66-8	NOAEL P 300 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Propane 74-98-6	NOAEL P 21,6 mg/l NOAEL F1 21,6 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
ammonia, aqueous solution 1336-21-6	NOAEL P 408 mg/kg	screening	oral: unspecified	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

**STOT-single exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Propan-2-ol 67-63-0	May cause drowsiness or dizziness.			

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)
Butane, n- (< 0.1 % butadiene) 106-97-8		inhalation: gas	28 d 6 h/d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
1-Butoxypropan-2-ol 5131-66-8	NOAEL 350 mg/kg	oral: drinking water	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
1-Butoxypropan-2-ol 5131-66-8	NOAEL 600 ppm	inhalation	11 d 6h/d	rat	equivalent or similar to OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
1-Butoxypropan-2-ol 5131-66-8	NOAEL 880 mg/kg		13 w 5 d/w	rat	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Propane 74-98-6		inhalation: gas	28 d 6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

**Aspiration hazard:**

The mixture is classified based on Viscosity data.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Propan-2-ol 67-63-0	1,8 mm <sup>2</sup> /s	40 °C	ASTM Standard D7042	

**11.2 Information on other hazards**

not applicable

**SECTION 12: Ecological information****General ecological information:**

Do not empty into drains, soil or bodies of water.

**12.1. Toxicity****Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Propan-2-ol 67-63-0	LC50	> 9.640 - 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	27,98 mg/l	96 h		QSAR (Quantitative Structure Activity Relationship)
1-Butoxypropan-2-ol 5131-66-8	LC50	1.732 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	not specified
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	LC50	> 150 - 220 mg/l	96 h	Leuciscus idus	DIN 38412-15
ammonia, aqueous solution 1336-21-6	LC50	0,16 - 1,1 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
ammonia, aqueous solution 1336-21-6	NOEC	0,013 mg/l	73 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)

**Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	14,22 mg/l	48 h		QSAR (Quantitative Structure Activity Relationship)
1-Butoxypropan-2-ol 5131-66-8	EC50	> 700 mg/l	24 h	Daphnia magna	not specified
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
ammonia, aqueous solution 1336-21-6	EC50	25,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**Chronic toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Propan-2-ol 67-63-0	NOEC	30 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
ammonia, aqueous solution 1336-21-6	NOEC	0,79 mg/l	96 h	Daphnia magna	EPA OPPTS 850.1300 (Daphnid Chronic Toxicity Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	7,71 mg/l	96 h		QSAR (Quantitative Structure Activity Relationship)
1-Butoxypropan-2-ol 5131-66-8	EC50	1.466 mg/l		Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	EC50	197,27 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	EC10	111,84 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
ammonia, aqueous solution 1336-21-6	EC50	> 1.000 mg/l	72 h	Skeletonema costatum	ISO 10253 (Water quality)
ammonia, aqueous solution 1336-21-6	NOEC	1.000 mg/l	72 h	Skeletonema costatum	ISO 10253 (Water quality)

**Toxicity (microorganisms):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1-Butoxypropan-2-ol 5131-66-8	EC0	10.000 mg/l	30 min		not specified
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	EC20	> 1.000 mg/l	30 min	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

**12.2. Persistence and degradability**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
1-Butoxypropan-2-ol 5131-66-8	readily biodegradable	aerobic	80 - 90 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Propane 74-98-6	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
Reaction product of Maleic anhydride, 2-Ethylhexylamine and Triethanolamine 1471311-93-9	readily biodegradable	aerobic	89 - 90 %	28 d	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Propan-2-ol 67-63-0	0,05		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Butane, n- (< 0.1 % butadiene) 106-97-8	2,31	20 °C	other (measured)
ammonia, aqueous solution 1336-21-6	-1,14		EU Method A.8 (Partition Coefficient)

### 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
ammonia, aqueous solution 1336-21-6	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.

### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:  
In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

**SECTION 14: Transport information**

**14.1. UN number or ID number**

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

**14.2. UN proper shipping name**

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

**14.3. Transport hazard class(es)**

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

**14.4. Packing group**

ADR  
RID  
ADN  
IMDG  
IATA

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable
-----	----------------

	Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

VOC content 13,5 %  
(2010/75/EU)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADG(-Code): Australian Dangerous Goods (Code)  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
ASTM: American Society for Testing and Materials  
ATE: acute toxicity estimate  
AS: Australian Standard  
AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water  
CAS: Chemical Abstract Service  
CLP: Regulation (EC) No 1272/2008  
CMR: cancerogenic, mutagenic or reprotoxic  
DIN: German Institute for Standardization  
ECx: Effective concentration (x% effective level)  
ECHA: European Chemicals Agency  
EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS  
ECTLV: European community threshold limit value  
ED: Substance identified as having endocrine disrupting properties  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
EN : European Standard  
ENCS: Japanese chemical inventory  
EPA: US Environmental Protection Agency  
EU: European Union  
EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148  
EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148  
EWC: European Waste Catalogue  
GHS: Globally Harmonised System for Classification and Labelling of Chemicals  
GLP: Good Laboratory Practice  
HSNO: Hazardous Substances and New Organisms  
IARC: International Agency for Research of Cancer  
IATA: International Air Transport Association  
IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
IC50: half maximal inhibitory concentration  
ICAO: International Civil Aviation Organization  
IMDG-Code: International Maritime Code for Dangerous Goods  
IMO: International Maritime Organization  
ISO: International Standardization Organisation  
LC50: Median lethal concentration  
LD50: Median lethal dose  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
n.o.s.: not otherwise specified  
NO(A)EC: No (adverse) effect concentration  
NO(A)EL: No (adverse) effect level  
NZS: New Zealand Standard  
OECD: Organisation for Economic Co-operation and Development

OEL: Occupational Exposure Limit  
OPPT: US EPA Office of Pollution Prevention and Toxics  
OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances  
PBT: Persistent, bioaccumulative, toxic  
(Q)SAR: (Quantitative) structure–activity relationship  
REACH: Regulation (EC) No. 1907/2006  
RID: Regulations concerning the International Transport of Dangerous Goods by Rail  
SADT: Self Accelerating Decomposition Temperature  
SDS: Safety Data Sheet  
STOT: Specific Target Organ Toxicity  
STOT SE: Specific Target Organ Toxicity - single exposure  
STOT RE: Specific Target Organ Toxicity - repeated exposure  
SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons  
SVHC: Substance of very high concern (REACH Candidate List)  
TRGS: German Technical Rules for hazardous substances  
UN: United Nations  
VOC: Volatile Organic Compound  
814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds  
vPvB: Very persistent, very bioaccumulative  
VwVwS: Administrative Regulation on Substances Hazardous to Waters  
WGK: Water hazard class

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**