

SAFETY DATA SHEET

BIZOL Gasoline Intake Clean+ c36**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1. Product identifier**

▼ *Trade name:* BIZOL Gasoline Intake Clean+ c36

Product no.: 80016

Unique formula identifier (UFI): 9RK4-57TJ-U002-GMJQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Cleaning product

Use descriptors (UK REACH):

Product category	Description
PC 0	Other products

Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **EUROLUB GmbH**
Freisingerstraße 25-27
85386 Eching
Germany
Tel.: +49 8165 9591-0
www.eurolub.com

Contact person: Laboratory

E-mail: info@eurolub.com

Revision: 25/10/2024

SDS Version: 2.0

Date of previous version: 24/10/2024 (1.0)

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

Acute Tox. 4; H332, Harmful if inhaled.

STOT SE 3; H335, May cause respiratory irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)
 Causes skin irritation. (H315)
 Causes serious eye irritation. (H319)
 Harmful if inhaled. (H332)
 May cause respiratory irritation. (H335)
 May cause drowsiness or dizziness. (H336)

May cause damage to organs through prolonged or repeated exposure. (H373)

Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s):

General: If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not pierce or burn, even after use. (P251)

Do not breathe spray. (P260)

Use only outdoors or in a well-ventilated area. (P271)

Response: Call a POISON CENTER/doctor if you feel unwell. (P312)

Get medical advice/attention if you feel unwell. (P314)

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal: Dispose of contents/container in accordance with local regulations (P501)

Hazardous substances: reaction mass of ethylbenzene and xylene
butanone;ethyl methyl ketone
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve

Additional labelling:

UFI: 9RK4-57TJ-U002-GMJQ

2.3. Other hazards

Additional warnings: In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
reaction mass of ethylbenzene and xylene	CAS No.: EC No.: 905-588-0 UK-REACH: Index No.:	25-50%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	
butanone;ethyl methyl ketone	CAS No.: 78-93-3 EC No.: 201-159-0 UK-REACH: Index No.: 606-002-00-3	15-25%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	CAS No.: EC No.: 920-750-0 UK-REACH: Index No.:	15-25%	EUH066 Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411	
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: Index No.: 603-117-00-0	15-25%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
propane	CAS No.: 74-98-6 EC No.: 200-827-9 UK-REACH: Index No.: 601-003-00-5	15-25%	Flam. Gas 1A, H220	
butane	CAS No.: 106-97-8 EC No.: 203-448-7 UK-REACH: Index No.: 601-004-01-8	1-3%	Flam. Gas 1A, H220	

2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve	CAS No.: 111-76-2 EC No.: 203-905-0 UK-REACH: Index No.: 603-014-00-0	1-3%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]
---	--	------	---	-----

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

<i>General information:</i>	In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
<i>Inhalation:</i>	Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.
<i>Skin contact:</i>	Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.
<i>Eye contact:</i>	If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation

stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion:

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns:

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER/doctor if you feel unwell.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: None

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth,

vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid static electricity.

Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Avoid direct contact with the product.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material: Always store in containers of the same material as the original container.

Storage conditions: Dry, cool and well ventilated

Incompatible materials: Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

butanone;ethyl methyl ketone

Long term exposure limit (8 hours) (ppm): 200

Long term exposure limit (8 hours) (mg/m³): 600

Short term exposure limit (15 minutes) (ppm): 300

Short term exposure limit (15 minutes) (mg/m³): 899

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

propan-2-ol;isopropyl alcohol;isopropanol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 1250

2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve

Long term exposure limit (8 hours) (ppm): 25

Long term exposure limit (8 hours) (mg/m³): 123

Short term exposure limit (15 minutes) (ppm): 50

Short term exposure limit (15 minutes) (mg/m³): 246

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m ³
Long term – Systemic effects - Workers	Inhalation	98 mg/m ³
Short term – Local effects - General population	Inhalation	147 mg/m ³
Short term – Local effects - Workers	Inhalation	246 mg/m ³
Short term – Systemic effects - General population	Inhalation	426 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1091 mg/m ³
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

butanone;ethyl methyl ketone

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	412 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	1161 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	106 mg/m ³
Long term – Systemic effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - General population	Inhalation	450 mg/m ³
Short term – Systemic effects - Workers	Inhalation	900 mg/m ³
Long term – Systemic effects - General population	Oral	31 mg/kg bw/day

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m ³
Long term – Systemic effects - Workers	Inhalation	500 mg/m ³
Short term – Systemic effects - General population	Inhalation	178 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1000 mg/m ³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

PNEC

2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg

Intermittent release (freshwater)		26.4 mg/L
Marine water		880 µg/L
Marine water sediment		3.46 mg/kg
Predators		20 mg/kg
Sewage treatment plant		463 mg/L
Soil		2.33 mg/kg

butanone;ethyl methyl ketone

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		55.8 mg/L
Freshwater sediment		284.74 mg/kg
Intermittent release (freshwater)		55.8 mg/L
Marine water		55.8 mg/L
Marine water sediment		284.7 mg/kg
Predators		1 g/kg
Sewage treatment plant		709 mg/L
Soil		22.5 mg/kg

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release (freshwater)		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Predators		160 mg/kg
Sewage treatment plant		2.251 g/L
Soil		28 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations: Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios implemented for this product.

Exposure limits: Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures: Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures: Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure: Provide adequate general and local exhaust ventilation.


Individual protection measures, such as personal protective equipment

Generally: Use only UKCA marked protective equipment.


Respiratory Equipment:

Type	Class	Colour	Standards	
Respiratory protection is not needed in the event of adequate ventilation.				


Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388	

Eye protection:

Type	Standards	
In the likelihood of direct or incidental exposure, use face protection.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Aerosol
<i>Colour:</i>	Transparent
<i>Odour / Odour threshold:</i>	Aromatic
<i>pH:</i>	No relevant or available data due to the nature of the product.
<i>Density (g/cm³):</i>	0.745
<i>Kinematic viscosity:</i>	No relevant or available data due to the nature of the product.
<i>Particle characteristics:</i>	No relevant or available data due to the nature of the product.

Phase changes

<i>Melting point/Freezing point (°C):</i>	No relevant or available data due to the nature of the product.
<i>Softening point/range (°C):</i>	Does not apply to aerosols.
<i>Boiling point (°C):</i>	-44.5
<i>Vapour pressure:</i>	3300 hPa (20 °C)
<i>Relative vapour density:</i>	No relevant or available data due to the nature of the product.
<i>Decomposition temperature (°C):</i>	No relevant or available data due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C): -97

Flammability (°C): 200

Auto-ignition temperature (°C): No relevant or available data due to the nature of the product.

Lower and upper explosion limit (% v/v): No relevant or available data due to the nature of the product.

Solubility

Solubility in water: No relevant or available data due to the nature of the product.

n-octanol/water coefficient (LogKow): No relevant or available data due to the nature of the product.

Solubility in fat (g/L): No relevant or available data due to the nature of the product.

9.2. Other information

VOC (g/l): 745

Oxidizing properties: No relevant or available data due to the nature of the product.

Other physical and chemical parameters: No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.
Extremes of temperature

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Harmful if inhaled.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.
2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code




07 01 04* Other organic solvents, washing liquids and mother liquors

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
ADR	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

-

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or

warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: None

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application: People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education: No specific requirements.

Control of Major Accident Hazards (COMAH) - P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

Categories / dangerous substances:

Regulation on drug precursors: butanone;ethyl methyl ketone is included (Category 3)

UK-REACH, Annex XVII: reaction mass of ethylbenzene and xylene is subject to UK-REACH restrictions (entry 40).

butanone;ethyl methyl ketone is subject to UK-REACH restrictions

(entry 40).

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics is subject to UK-REACH restrictions (entry 40).

propan-2-ol;isopropyl alcohol;isopropanol is subject to UK-REACH restrictions (entry 40).

propane is subject to UK-REACH restrictions (entry 40).

butane is subject to UK-REACH restrictions (entry 40).

Additional information: Tactile warning.

Sources: The Management of Health and Safety at Work Regulations 1999.
The Health and Safety at Work etc. Act 1974 Regulations 2013.
The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).
Regulation (EC) No 648/2004 on detergents as retained and amended in UK law.
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
The Controlled Drugs (Drug Precursors) Regulations 2008.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H220, Extremely flammable gas.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.

H312, Harmful in contact with skin.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

H373, May cause damage to organs through prolonged or repeated exposure.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

PC 0 = Other products

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental

data.

The safety data sheet is validated by

MSDS

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en