



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SynPower™ XL III C3 0W30
Synthetic Blend Motor Oil

Product code : 882240

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.
EUH210 Safety data sheet available on request.



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 25,00 - < 40,00
DECENE-1 HOMOPOLYMER HYDROGENATED	68037-01-4 01-2119486452-34-xxxx	Asp. Tox.1; H304	>= 15,00 - < 25,00
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 5,00 - < 10,00
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based	72623-86-0 276-737-9	Asp. Tox.1; H304	>= 5,00 - < 10,00
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 0,10 - < 0,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Nitrogen oxides (NO_x)
carbon dioxide and carbon monoxide



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

- Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : General industrial hygiene practice.



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

7.2 Conditions for safe storage, including any incompatibilities

Advice on common storage : No materials to be especially mentioned.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes

Respiratory protection : No personal respiratory protective equipment normally required.

No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

Odour	: oily
Odour Threshold	: No data available
pH	: Not applicable
Pour point	: < -45 °C
Boiling point/boiling range	: No data available
Flash point	: 230 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0,844 g/cm ³ (15 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: < 6.200 mPa.s (-35 °C)
Viscosity, kinematic	: 65 mm ² /s (40 °C)
Oxidizing properties	: No data available



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 15 g/kg



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: No mortality observed at this dose.

Components:

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

Components:

C14-16-18 Alkyl phenol:

Acute oral toxicity	: LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by ingestion under GHS.
Acute dermal toxicity	: LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

DECENE-1 HOMOPOLYMER HYDROGENATED:

Species: Rabbit

Result: No skin irritation

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit

Result: No skin irritation

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: No skin irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Mild skin irritation

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Method: OECD Test Guideline 431

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HEAVY PARAFFINIC DISTILLATE:



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

Result: No eye irritation

DECENE-1 HOMOPOLYMER HYDROGENATED:

Species: Rabbit

Result: Slight, transient irritation

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit

Result: No eye irritation

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: No eye irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Test Type: Local lymph node assay

Species: Mouse



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

Assessment: The product is a skin sensitiser, sub-category 1B.
Method: OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

C14-16-18 Alkyl phenol:

Target Organs: **Liver**

Assessment: **The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.**

Aspiration toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

DECENE-1 HOMOPOLYMER HYDROGENATED:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity to fish : **LL50 (Fish): > 100 mg/l**
Exposure time: **96 h**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Aquatic invertebrates): > 10.000 mg/l**
Exposure time: **48 h**

Toxicity to algae : **EL50 (Algae, algal mat (Algae)): > 100 mg/l**
Exposure time: **72 h**

Toxicity to fish (Chronic toxicity) : **NOEC: 10 mg/l**
Species: **Fish**

Toxicity to daphnia and other aquatic invertebrates : **NOEC: 10 mg/l**
Species: **Aquatic invertebrates**



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

(Chronic toxicity)

DECENE-1 HOMOPOLYMER HYDROGENATED

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)) : > 1.000 mg/l Exposure time: 96 h Test Type: semi-static test Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)) : > 1.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: EL50 (Scenedesmus capricornutum (fresh water algae)) : > 1.000 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR : 125 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)) : > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)) : > 10.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)) : >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

	Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1.000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211

bis(nonylphenyl)amine

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

C14-16-18 Alkyl phenol

Toxicity to fish	: LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

12.2 Persistence and degradability

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED

Biodegradability : Result: **Inherently biodegradable**

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **2 - 4 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

bis(nonylphenyl)amine

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **0 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

C14-16-18 Alkyl phenol

Biodegradability : Result: **Readily biodegradable.**
Remarks: **Expert judgement**

12.3 Bioaccumulative potential

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED

Partition coefficient: n-octanol/water : log Pow: **> 6,5**

bis(nonylphenyl)amine

Partition coefficient: n-octanol/water : log Pow: **> 7,5**

C14-16-18 Alkyl phenol

Partition coefficient: n-octanol/water : log Pow: **> 7,2**

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging : Empty remaining contents.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : 000000272542

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-phrases : Risk phrases



SAFETY DATA SHEET

SynPower™ XL III C3 0W30 Synthetic Blend
Motor Oil

Version: 2.0

Revision Date: 21.07.2020

Print Date: 16/09/2022

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-phrase: Safety phrase
WGK : German Water Hazard Class