



18000TR

Gear Oil 75W-140 Premium Synthetic Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 2-5-2019 Revision date: 26-10-2020 Supersedes: 2-5-2019 version: 5.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Gear Oil 75W-140 Premium Synthetic Truck
Product code : 18000TR

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Automotive care products
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
Cyclotronweg 1
2629 HN Delft Delft - Nederland
T +31 (0)15 2514030 - F +31 (0)15 2514031
msds@mpmoil.nl - www.mpmoil.nl

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Polysulfides, di-tert-Bu, Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polysulfides, di-tert-Bu	(CAS-No.) 68937-96-2 (EC-No.) 273-103-3 (REACH-no) 01-2119540515-43	2,5 – 5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Gear Oil 75W-140 Premium Synthetic Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), hydrotreated light paraffinic, Baseoil - unspecified.	(CAS-No.) 64742-55-8 (EC-No.) 265-158-7 (EC Index-No.) 649-468-00-3 (REACH-no) 01-2119487077-29	1 – 5	Asp. Tox. 1, H304
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	1 – 2,5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Solvent refined mineral oil	(CAS-No.) 64741-88-4, 67741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-65-0, 64742-71-8, 72623-83-7, 76623-85-9, 72623-86-0, 72623-87-1, 74869-22-0	1 – 2,5	Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation	: No special protection required.
After skin contact	: Gently wash with plenty of soap and water.
After eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes.
After ingestion	: If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: water spray, powder, foam and CO ₂ .
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Exercise caution when fighting any chemical fire. Use a water spray to cool exposed surfaces and to protect fire-fighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Clean with the help of detergents. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
Other information	: If spilled, may cause the floor to be slippery.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
-------------------------------	---

Gear Oil 75W-140 Premium Synthetic Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Handling temperature : < 40 °C
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage temperature : < 40 °C
Storage area : Keep in a cool, well-ventilated place. Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m3 oilspray (TWA, 8 hour workday) is recommended.

8.2. Exposure controls

Personal protective equipment:

Gloves. Protective goggles.

Materials for protective clothing:

Wear suitable protective clothing, gloves and eye/face protection

Hand protection:

Wear suitable gloves resistant to chemical penetration

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	5 (> 240 minutes)	>0.35mm		EN 374-3

Eye protection:

Safety goggles

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Oily.
Colour : light brown.
Odour : characteristic.
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : > 110 °C ASTM D 92
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available

Gear Oil 75W-140 Premium Synthetic Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Density	: 873 g/l @ 15°C
Solubility	: Slightly soluble, the product remains on the water surface.
Log Pow	: No data available
Viscosity, kinematic	: 188 mm²/s @ 100°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

acids and bases. Oxidizing agent.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated light paraffinic, Baseoil - unspecified. (64742-55-8)

LD50 oral rat	> 5000 kilogram
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5,53 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day @28d
----------------------------	-------------------------------

Aspiration hazard	: Not classified
-------------------	------------------

Gear Oil 75W-140 Premium Synthetic Truck

Viscosity, kinematic	188 mm²/s @ 100°C
Other information	: This product is formulated with highly refined mineral oils which are considered under IARC as not carcinogenic. It was the IP 346 test showed that all oils in this product contains less than 3% extractable substances.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
--	------------------

Gear Oil 75W-140 Premium Synthetic Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Polysulfides, di-tert-Bu (68937-96-2)

LC50 fish 1	> 0,088 mg/l Danio rerio
EC50 Daphnia 1	63 mg/l @2d
EC50 other aquatic organisms 1	> 100 mg/l @3d
EC50 72h algae (1)	≈ 63 mg/l @2d Waterflea
EC50 72h algae (2)	> 100 mg/l @3d
EC50 96h algae (1)	> 10000 mg/l @0.1d sediment

Distillates (petroleum), hydrotreated light paraffinic, Baseoil - unspecified. (64742-55-8)

LC50 fish 1	> 100 mg/l 96h
LC50 other aquatic organisms 1	> 100 mg/l
ErC50 (algae)	> 100 mg/l 48h
NOEC chronic fish	100 mg/l

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

LC50 fish 1	24 mg/l @4d Oncorhynchus mykiss
LC50 fish 2	8,5 mg/l @4d Pimephales promelas
EC50 Daphnia 1	91,4 mg/l @2d
EC50 Daphnia 2	0,66 mg/l @21 d
EC50 other aquatic organisms 1	6,4 mg/l @4d selenastrum capricornutum
EC50 72h algae (1)	91,4 mg/l @2d waterflea
EC50 72h algae (2)	0,66 mg/l @21d waterflea
EC50 96h algae (1)	2433 mg/l @0.1d slib
NOEC chronic crustacea	0,12 mg/l @21 d waterflea
NOEC chronic algae	1,7 mg/l @4d selenastrum capricornutum

12.2. Persistence and degradability

Gear Oil 75W-140 Premium Synthetic Truck

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

Polysulfides, di-tert-Bu (68937-96-2)

Biodegradation	13 % @28 d OECD TG
----------------	--------------------

Distillates (petroleum), hydrotreated light paraffinic, Baseoil - unspecified. (64742-55-8)

Persistence and degradability	Not established.
-------------------------------	------------------

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

BOD (% of ThOD)	3,6 % ThOD @28d inherent sediment
Biodegradation	7,4 % Sturm (28d)

12.3. Bioaccumulative potential

Polysulfides, di-tert-Bu (68937-96-2)

Log Pow	-
Log Kow	6

Gear Oil 75W-140 Premium Synthetic Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), hydrotreated light paraffinic, Baseoil - unspecified. (64742-55-8)

Log Pow	> 3
Bioaccumulative potential	No data available.

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Log Pow	< 0,3 40C OECD 117 methode
---------	----------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects	: Danger of drinking-water pollution (ground water).
Additional information	: Do not empty into drains or the aquatic environment. Do not allow material to contaminate ground water system

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Do not dispose of with domestic waste.
Waste disposal recommendations	: Remove to an authorized waste treatment plant.
European List of Waste (LoW) code	: 13 02 06* - synthetic engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG
14.1. UN number	
Not applicable	Not applicable
14.2. UN proper shipping name	
Not applicable	Not applicable
14.3. Transport hazard class(es)	
Not applicable	Not applicable
14.4. Packing group	
Not applicable	Not applicable
14.5. Environmental hazards	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

Gear Oil 75W-140 Premium Synthetic Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Polysulfides, di-tert-Bu, Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.