



# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878  
Issue date: 13-8-2014 Revision date: 15-7-2022 Supersedes: 13-7-2022 version: 2.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : MPM Diesel Detox Professional  
UFI : RN7U-NS9H-K10H-XR18  
Product code : AD08000  
Type of product : Additives  
Product group : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use  
Function or use category : Fuel additives

##### 1.2.2. Uses advised against

No additional information available.

#### 1.3. Details of the supplier of the safety data sheet

MPM International Oil Company  
Cyclotronweg 1  
2629 HN Delft Delft - Nederland  
T +31 (0)15 2514030  
[info@mpmoil.nl](mailto:info@mpmoil.nl) - [www.mpmoil.com](http://www.mpmoil.com)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category 1 H304  
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412  
Full text of H-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

CLP Signal word : Danger.  
Hazardous ingredients : Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics.  
Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways.  
H412 - Harmful to aquatic life with long lasting effects.

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Precautionary statements (CLP)	: P102 - Keep out of reach of children. P273 - Avoid release to the environment. P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER. P331 - Do NOT induce vomiting. P501 - Dispose of Contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

No additional information available.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Comments : Mixture of substances listed below, possibly with non-hazardous additions.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics.	(EC-No.) 918-481-9 (REACH-no) 01-2119457273-39	≥ 80 – ≤ 95	Asp. Tox. 1, H304
2-Ethylhexyl, Nitrate	(CAS-No.) 27247-96-7 (EC-No.) 248-363-6 (REACH-no) 01-2119539586-27	≥ 5 – ≤ 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Aquatic Chronic 2, H411
2-Ethylhexanol	(CAS-No.) 104-76-7 (EC-No.) 203-234-3 (REACH-no) 01-2119487289-20	< 1	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
2-ethylhexanoic acid	(CAS-No.) 149-57-5 (EC-No.) 205-743-6 (EC Index-No.) 607-230-00-6 (REACH-no) 01-2119488942-23	< 1	Repr. 2, H361d
Naphthalene	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2	< 0,01	Flam. Sol. 2, H228 Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General	: First aider: Pay attention to self-protection!. Remove to fresh air and keep at rest in a position comfortable for breathing. Cough, difficult breathing or other symptoms of poisoning may occur within some hours. Keep under medical supervision for at least 48 hours.
After inhalation	: Remove person to fresh air and keep comfortable for breathing. If unconscious, place in the recovery position and seek medical advice. Get medical advice/attention if you feel unwell.
After skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Do not use solvents or thinners.
After eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes. If eye irritation persists: Get medical advice/attention.
After ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Symptoms of respiratory complications (lung oedema) may occur several hours after.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray, powder, foam and CO2.
Unsuitable extinguishing media	: Do not use a heavy water stream.

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 5.2. Special hazards arising from the substance or mixture

No additional information available.

### 5.3. Advice for firefighters

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing and gloves.

Emergency procedures : Avoid contact with skin and eyes. Do not breathe vapours.

#### 6.1.2. For emergency responders

Protective equipment : Wear respiratory protection.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Other information : Provide adequate ventilation.

### 6.4. Reference to other sections

Information on safe handling - see Section 7. Information on personal protective equipment - see Chapter 8. Information on disposal - see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : This product is not to be used under conditions of poor ventilation. Avoid aerosol formation.

Precautions for safe handling : Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.

Hygiene measures : Avoid all unnecessary exposure. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a well-ventilated place. Keep container tightly closed. Keep in a cool, well-ventilated place away from heat. Keep only in the original container at a temperature not exceeding the flash point.

Storage conditions : Keep container tightly closed. Store in a dry place. Store in a well-ventilated place. Keep cool.

Heat and ignition sources : Protect from heat and direct sunlight.

Storage area : Store according to local legislation.

Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 2-Ethylhexyl, Nitrate (27247-96-7)

EU	IOELV TWA (mg/m <sup>3</sup> )	5,4 mg/m <sup>3</sup> long term value
EU	IOELV TWA (ppm)	1 ppm long term value
Germany	Notes	
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	5,4 mg/m <sup>3</sup> long term value
United Kingdom	WEL TWA (ppm)	1 ppm long term value

#### 2-Ethylhexanol (104-76-7)

EU	Local name	2-ethylhexan-1-ol
EU	IOELV TWA (mg/m <sup>3</sup> )	5,4 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	1 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Germany	Notes	

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2-Ethylhexanol (104-76-7)		
Ireland	Local name	2-Ethylhexan-1-ol
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	5,4 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	1 ppm
Ireland	Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom	Local name	2-ethylhexan-1-ol
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	5,4 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	1 ppm
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Naphthalene (91-20-3)		
EU	Local name	Naphthalene
EU	IOELV TWA (mg/m <sup>3</sup> )	30 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	10 ppm
EU	Notes	(Year of adoption 2010)
Germany	Notes	
Ireland	Local name	Naphthalene
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	10 ppm
Ireland	Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>

Additional information : Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40) 1200mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Personal protective equipment:

At high vapor/gas concentration: gas mask with filter type AX. Gloves. Safety glasses.

#### Materials for protective clothing:

Wear suitable protective clothing, gloves and eye/face protection

#### Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Fluoroelastomer (FKM)	6 (> 480 minutes)	> 0,71		EN ISO 374-1

#### Eye protection:

Wear tight fitting safety glasses or facial screen

Type	Field of application	Characteristics	Standard
Safety glasses	Use splash goggles when eye contact due to splashing is possible	With side shields	EN 166

#### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

#### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: Tests not relevant or not possible due to the nature of the product.
Relative evaporation rate (butylacetate=1)	: 0,04 (n-butylacetaat = 100)
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 160 – 245 °C
Flash point	: > 62 °C
Auto-ignition temperature	: > 200
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0,1 kPa at 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 805 kg/m <sup>3</sup>
Solubility	: Insoluble in water. Organic solvent:90,9 %
Log Pow	: No data available
Viscosity, kinematic	: 7 mm <sup>2</sup> /s @ 40°C
Viscosity, dynamic	: No data available
Explosive properties	: Flammable or explosive vapour/air mixtures may be formed. Product is not explosive.
Oxidising properties	: No data available
Explosive limits	: 0,6 – 7 vol %

### 9.2. Other information

VOC content	: 739,8 g/l EU, 1993/13/EC
Other properties	: No oxidising properties.
Additional information	: No additional information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts violently with oxidizing agents, strong acids and strong bases.

### 10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Overheating. Direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Strong oxidizing agent.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### MPM Diesel Detox Professional

LD50 oral rat	14002 mg/kg
---------------	-------------

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics.

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 4951 mg/m <sup>3</sup> @ 4h

### 2-Ethylhexyl, Nitrate (27247-96-7)

LD50 oral rat	> 960 ml/kg
LD50 dermal rabbit	4820 µg/kg

### 2-Ethylhexanol (104-76-7)

LD50 oral rat	2049 mg/kg
LD50 dermal rabbit	1970 mg/kg
LC50 Inhalation - Rat	2,5 mg/l/4h

### Naphthalene (91-20-3)

LD50 oral rat	490 mg/kg
LD50 dermal rat	5000 mg/kg
LC50 Inhalation - Rat	> 100 mg/l/4h

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)  
pH: Tests not relevant or not possible due to the nature of the product.

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)  
pH: Tests not relevant or not possible due to the nature of the product.

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

### 2-Ethylhexanol (104-76-7)

NOAEL (chronic, oral, animal/male, 2 years)	750 mg/kg bodyweight
---	----------------------

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

### 2-Ethylhexyl, Nitrate (27247-96-7)

NOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight EPA OPP 82-2 (21/28 D)
-------------------------------------	---

### 2-Ethylhexanol (104-76-7)

NOAEC (inhalation, rat, gas, 90 days)	120 ppm OECD Guideline 413
---------------------------------------	----------------------------

Aspiration hazard : May be fatal if swallowed and enters airways.

### MPM Diesel Detox Professional

Viscosity, kinematic	7 mm <sup>2</sup> /s @ 40°C
----------------------	-----------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

General : Harmful to fishes. Do not allow material to contaminate ground water system. Danger of drinking-water pollution (ground water).

Ecology - water : This product is not water soluble. It floats on the water and forms a film on the surface. The damage to aquatic organisms is of a mechanical nature (immobilization and containment).

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics.

LC50 fish 1	> 100 mg/l @96h Oncorhynchus mykiss
EC50 Daphnia 1	> 100 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	> 100 mg/l @72h Pseudokirchneriella subcapitata

### 2-Ethylhexyl, Nitrate (27247-96-7)

LC50 fish 1	2 mg/l @96h fish
EC50 Daphnia 1	> 12,6 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	> 12,6 mg/l @72h Algae
EC50 72h - Algae [1]	3,22 mg/l pseudokirchneriella subcapitata
EC50 72h - Algae [2]	1,57 mg/l Pseudokirchneriella subcapitata

### 2-Ethylhexanol (104-76-7)

LC50 fish 1	17,1 mg/l @96h Leuciscus idus
LC50 fish 2	17,1 mg/l leuciscus idus melanotus
EC50 Daphnia 1	39 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	11,5 mg/l @72h Algae Scenedesmus subspicatus
EC50 72h - Algae [1]	28,2 mg/l pimephales promelas
EC50 72h - Algae [2]	16,6 mg/l Desmodesmus subspicatus

### Naphthalene (91-20-3)

LC50 fish 1	0,5 mg/l
-------------	----------

### 12.2. Persistence and degradability

#### MPM Diesel Detox Professional

Persistence and degradability	No relevant information available.
-------------------------------	------------------------------------

### 2-Ethylhexyl, Nitrate (27247-96-7)

Persistence and degradability	Poorly biodegradable.
Biodegradation	0 % @28d

### 2-Ethylhexanol (104-76-7)

Persistence and degradability	Readily biodegradable.
Biodegradation	> 95 % @5d

### 12.3. Bioaccumulative potential

#### MPM Diesel Detox Professional

Bioaccumulative potential	No relevant information available.
---------------------------	------------------------------------

### 2-Ethylhexyl, Nitrate (27247-96-7)

Bioconcentration factor (BCF REACH)	1332
Log Pow	4,5 – 5,26

### 2-Ethylhexanol (104-76-7)

Bioconcentration factor (BCF REACH)	25,33
Log Kow	2,9

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.4. Mobility in soil

#### MPM Diesel Detox Professional

Soil	No additional information available.
------	--------------------------------------

### 2-Ethylhexyl, Nitrate (27247-96-7)

Log Koc	3,8
---------	-----

### 12.5. Results of PBT and vPvB assessment

No additional information available.

### 12.6. Other adverse effects

No additional information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Hand over to officially registered waste disposal company. Recycle the material as far as possible. Waste suitable for incineration.
Waste materials	: Dispose of contents/container in accordance with licensed collector's sorting instructions and in accordance to local and regional legislation.

## SECTION 14: Transport information

In accordance with ADR / IMDG

ADR	IMDG
<b>14.1. UN number</b>	
Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>	
Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>	
Not applicable	Not applicable
<b>14.4. Packing group</b>	
Not applicable	Not applicable
<b>14.5. Environmental hazards</b>	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

### 14.6. Special precautions for user

#### Overland transport

No data available

#### Transport by sea

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

VOC content

: 739,8 g/l EU, 1993/13/EC

### 15.1.2. National regulations

No additional information available.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out by the registrant

## SECTION 16: Other information

### Indication of changes:

Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Precautionary statements (CLP)	Modified	
2.2	Hazard statements (CLP)	Modified	
3	Composition/information on ingredients	Modified	
9.1	Relative evaporation rate (butylacetate=1)	Added	
9.1	Vapour pressure	Modified	
9.1	Boiling point	Modified	
9.1	pH	Added	
9.1	Density	Modified	

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Sol. 2	Flammable solids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

# MPM Diesel Detox Professional

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### SDS MPM REACH

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*