

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 17/01/2023 Revision date: 08/06/2021 Version: 07.01

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1. Product identifier**

Product name	: Diesel Clean-Up
Product code	: W25241
Product group	: Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture Function or use category

: Internal cleaning of diesel fuel systems and engines. : Fuel additives

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

ITW ADDITIVES INTL B.V. Industriepark-West 46 9100 Sint-Niklaas Belgium T +32 3 766 60 20 - F +32 3 778 16 56 msds@wynns.eu - www.wynns.com

#### 1.4. Emergency telephone number

Emergency number

: BIG: +32(0)14 58 45 45 (NL FR EN DE)

SECTION 2: Hazards identification	on
2.1. Classification of the substance of	or mixture
Classification according to Regulation (E Aspiration hazard, Category 1 Hazardous to the aquatic environment – Chr Full text of H- and EUH-statements: see sec Adverse physicochemical, human health	H304 ronic Hazard, Category 3 H412 tion 16
No additional information available	
2.2. Label elements	
Labelling according to Regulation (EC) Not Hazard pictograms (CLP)	o. 1272/2008 [CLP]
	GHS08
Signal word (CLP) Contains	: Danger
Hazard statements (CLP)	<ul> <li>C8-C26 branched and linear hydrocarbons – Distillates</li> <li>H304 - May be fatal if swallowed and enters airways.</li> <li>H412 - Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements (CLP)	<ul> <li>P102 - Keep out of reach of children.</li> <li>P405 - Store locked up.</li> <li>P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.</li> <li>P331 - Do NOT induce vomiting.</li> <li>P273 - Avoid release to the environment.</li> </ul>
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
2-ethylhexan-1-ol (104-76-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

### Not applicable

## 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
C8-C26 branched and linear hydrocarbons – Distillates	CAS-No.: 848301-67-7 EC-No.: 481-740-5 REACH-no: 01-0000020119- 75	≥ 50	Asp. Tox. 1, H304 EUH066
Hydrocarbons, C10, aromatics, <1% naphthalene	EC-No.: 918-811-1 REACH-no: 01-2119463583- 34	10 – 25	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
2-butoxyethanol substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108- 36	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
2-ethylhexan-1-ol substance with a Community workplace exposure limit	CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289- 20	0,1 – 1	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Naphthalene substance with a Community workplace exposure limit	CAS-No.: 91-20-3 EC-No.: 202-049-5 EC Index-No.: 601-052-00-2 REACH-no: 01-2119561346- 37	0,1 – 1	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid.
First-aid measures after inhalation	<ul><li>Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.</li><li>If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.</li></ul>

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Ingestion of large quantities: immediately to hospital.
4.2. Most important symptoms and effects,	both acute and delayed
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Water spray. AFFF foam. ABC-powder.	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard	<ul><li>Combustible liquid. Agitation can cause build up of electrostatic charge.</li><li>Product is not explosive.</li></ul>	
5.3. Advice for firefighters		
Firefighting instructions Protection during firefighting	<ul><li>Prevent fire fighting water from entering the environment.</li><li>Do not enter fire area without proper protective equipment, including respiratory protection.</li></ul>	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protect	ive equipment and emergency procedures	
General measures	: Use special care to avoid static electric charges. No open flames. No smoking.	
6.1.1. For non-emergency personnel		
Protective equipment	: Wear suitable gloves and eye/face protection. protective clothing.	
Emergency procedures	: Mark the danger area. Keep upwind. Prevent flow to low areas. In confined space use self- contained breathing apparatus. Take off contaminated clothing and wash it before reuse.	
6.1.2. For emergency responders		
Protective equipment	: Equip cleanup crew with proper protection.	
6.2. Environmental precautions		

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up	
For containment Methods for cleaning up	<ul> <li>Collect spillage. Contain leaking substance, pump over in suitable containers.</li> <li>Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.</li> </ul>

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautions for safe handling Hygiene measures	<ul> <li>Meet the legal requirements. Repeated exposure may cause skin dryness or cracking. Presents no particular risk when handled in accordance with good occupational hygiene practice.</li> <li>Use good personal hygiene practices. IF ON SKIN: Gently wash with plenty of soap and water. Wash contaminated clothing before reuse.</li> </ul>		
7.2. Conditions for safe storage, including any incompatibilities			
Technical measures Storage conditions Storage area Special rules on packaging	<ul> <li>Does not require any specific or particular technical measures.</li> <li>Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.</li> <li>Meet the legal requirements. Store in a well-ventilated place. Ventilation along the floor.</li> <li>Meet the legal requirements. Store in a closed container. Labelling according to.</li> </ul>		

7.3. Specific end use(s)

Read label before use. Observe the label precautions. See product bulletin for detailed information.

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Hydrocarbons, C10, aromatics, <1% naphthalene		
Belgium - Occupational Exposure Limits		
OEL TWA	200 mg/m <sup>3</sup>	
2-butoxyethanol (111-76-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	2-Butoxyethanol	
IOEL TWA	98 mg/m³	
IOEL TWA [ppm]	20 ppm	
IOEL STEL	246 mg/m³	
IOEL STEL [ppm]	50 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	2-Butoxyéthanol # 2-Butoxy-ethanol	
OEL TWA	98 mg/m³	
OEL TWA [ppm]	20 ppm	
OEL STEL	246 mg/m <sup>3</sup>	
OEL STEL [ppm]	50 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002	
France - Occupational Exposure Limits		
VME (OEL TWA)	49 mg/m³	
VME (OEL TWA) [ppm]	10 ppm	
VLE (OEL C/STEL)	246 mg/m³	
VLE (OEL C/STEL) [ppm]	50 ppm	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethanol (111-76-2)		
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	98 mg/m³	
CK (OEL STEL)	246 mg/m <sup>3</sup>	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	100 mg/m³	
TGG-8u (OEL TWA) [ppm]	20 ppm	
TGG-15min (OEL STEL)	246 mg/m <sup>3</sup>	
TGG-15min (OEL STEL) [ppm]	50 ppm	
2-ethylhexan-1-ol (104-76-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5,4 mg/m³	
IOEL TWA [ppm]	1 ppm	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA) [1]	110 mg/m³	
AGW (OEL TWA) [2]	20 ppm	
Naphthalene (91-20-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	50 mg/m³	
IOEL TWA [ppm]	10 ppm	
Belgium - Occupational Exposure Limits		
OEL TWA	53 mg/m³	
OEL TWA [ppm]	10 ppm	
OEL STEL	80 mg/m³	
OEL STEL [ppm]	15 ppm	
Remark	D	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	50 mg/m³	
8.1.2. Recommended monitoring procedures         No additional information available         8.1.3. Air contaminants formed         No additional information available		
8.1.4. DNEL and PNEC		
C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)		
PNEC (Sediment)		
PNEC sediment (freshwater)	2,06 mg/kg dwt	
PNEC (Soil)		
PNEC soil	1,68 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	10 mg/l	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C10, aromatics, <1% naphthal	Hydrocarbons, C10, aromatics, <1% naphthalene		
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	12,5 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	151 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	7,5 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	32 mg/m <sup>3</sup>		
Long-term - systemic effects, dermal	7,5 mg/kg bodyweight/day		
2-butoxyethanol (111-76-2)			
DNEL/DMEL (Workers)			
Acute - systemic effects, dermal	89 mg/kg bodyweight/day		
Acute - systemic effects, inhalation	1091 mg/m <sup>3</sup>		
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	98 mg/m³		
Long-term - local effects, inhalation	246 mg/m³		
DNEL/DMEL (General population)			
Acute - systemic effects, dermal	89 mg/kg bodyweight		
Acute - systemic effects, inhalation	426 mg/m <sup>3</sup>		
Acute - systemic effects, oral	26,7 mg/kg bodyweight		
Long-term - systemic effects,oral	6,3 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	59 mg/m³		
Long-term - systemic effects, dermal	75 mg/kg bodyweight/day		
Long-term - local effects, inhalation	147 mg/m³		
PNEC (Water)			
PNEC aqua (freshwater)	8,8 mg/l		
PNEC aqua (marine water)	0,88 mg/l		
PNEC aqua (intermittent, freshwater)	9,1 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	34,6 mg/kg dwt		
PNEC sediment (marine water)	3,46 mg/kg dwt		
PNEC (Soil)	PNEC (Soil)		
PNEC soil	2,33 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	463 mg/l		
2-ethylhexan-1-ol (104-76-7)			
DNEL/DMEL (Workers)			
Acute - local effects, inhalation	53,2 mg/m <sup>3</sup>		
Long-term - systemic effects, dermal	23 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	12,8 mg/m <sup>3</sup>		

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethylhexan-1-ol (104-76-7)		
Long-term - local effects, inhalation	53,2 mg/m <sup>3</sup>	
DNEL/DMEL (General population)		
Acute - local effects, inhalation	26,6 mg/m <sup>3</sup>	
Long-term - systemic effects,oral	1,1 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,3 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	11,4 mg/kg bodyweight/day	
Long-term - local effects, inhalation	26,6 mg/m <sup>3</sup>	
PNEC (Water)		
PNEC aqua (freshwater)	0,017 mg/l	
PNEC aqua (marine water)	0,0017 mg/l	
PNEC aqua (intermittent, freshwater)	0,17 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0,284 mg/kg dwt	
PNEC sediment (marine water)	0,0284 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,047 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	10 mg/l	
Naphthalene (91-20-3)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	3,57 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	25 mg/m <sup>3</sup>	
Long-term - local effects, inhalation	25 mg/m <sup>3</sup>	
PNEC (STP)		
PNEC sewage treatment plant	2,9 mg/l	

#### 8.1.5. Control banding

No additional information available

8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide good ventilation in process area to prevent formation of vapour. Does not require any specific or particular technical measures.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Safety glasses.

Personal protective equipment symbol(s):



## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2.2.1. Eye and face protection

#### No additional information available

#### 8.2.2.2. Skin protection

#### Hand protection:

Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer

#### 8.2.2.3. Respiratory protection

No additional information available

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Appearance	: clear.
Odour	: petroleum-like odour.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 64 °C (ASTM D93)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 2 mm²/s @ 40°C (ASTM D445)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 800 kg/m³ @ 20°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

#### No additional information available

#### 9.2.2. Other safety characteristics

Additional information

: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity	
10.1. Reactivity	
No additional information available	
10.2. Chemical stability	
Stable under normal conditions.	

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

**10.6. Hazardous decomposition products** 

Under normal conditions of storage and use, hazardous decomposition products should not be produced. On burning: release of harmful/irritant gases/vapours. Carbon monoxide. Carbon dioxide.

### **SECTION 11: Toxicological information**

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (dermal)	Not classified Not classified Not classified	
C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)		
LD50 oral rat	> 5000 mg/kg bodyweight Sprague-Dawley	
LD50 dermal rat	> 2000 mg/kg bodyweight Sprague-Dawley	
Hydrocarbons, C10, aromatics, <1% naphthalene		
LD50 oral rat	6318 mg/kg bodyweight Crl:CDBR	
LD50 dermal rabbit	> 2000 mg/kg bodyweight New Zealand White	
LC50 Inhalation - Rat	> 4,688 mg/l/4h Sprague-Dawley	
2-butoxyethanol (111-76-2)		
LD50 oral rat	1200 mg/kg bodyweight Rat	
LD50 dermal rat	> 2000 mg/kg bodyweight Sprague-Dawley	
LD50 dermal rabbit	24h 435 mg/kg New Zealand White	
2-ethylhexan-1-ol (104-76-7)		
LD50 oral rat	2047 mg/kg	
LD50 dermal rabbit	> 3000 mg/kg	
LC50 Inhalation - Rat	1,1 mg/l/4h	
Naphthalene (91-20-3)		
LD50 oral rat	> 2000 mg/kg bodyweight Sprague-Dawley	
LD50 dermal rat	> 2500 mg/kg bodyweight Sherman	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Not classified	
Respiratory or skin sensitisation	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
Hydrocarbons, C10, aromatics, <1% naphthalene		
STOT-single exposure	May cause drowsiness or dizziness.	
2-ethylhexan-1-ol (104-76-7)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure	Not classified	
Aspiration hazard	: May be fatal if swallowed and enters airways.	
Diesel Clean-Up		
Viscosity, kinematic	2 mm²/s @ 40°C (ASTM D445)	
C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)		
Viscosity, kinematic	2 – 4,5 mm²/s	
Hydrocarbons, C10, aromatics, <1% naphthalene		
Viscosity, kinematic	< 2 mm²/s	
Aliphatic, alicyclic or aromatic hydrocarbon	Yes	
2-butoxyethanol (111-76-2)		
Viscosity, kinematic	< 3,7 mm²/s	
11.2. Information on other hazards		

No additional information available

## **SECTION 12: Ecological information**

12.1. Toxicity

Ecology - water : Hazardous to the aquatic environment, short-term : (acute)	This product contains hazardous components for the aquatic environment. Harmful to aquatic life with long lasting effects. Not classified Harmful to aquatic life with long lasting effects.	
C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)		
LC50 - Fish [1]	> 1000 mg/l @96h Pimephales promelas	
EC50 - Crustacea [1]	> 1000 mg/l @48h Daphnia magna	
EC50 - Other aquatic organisms [1]	> 1000 mg/l @72h Pseudokirchneriella subcapitata	
NOEC (acute)	> 1000 mg/l @48h Daphnia magna	
Hydrocarbons, C10, aromatics, <1% naphthalene		
LC50 - Fish [1]	96h 2 (≤ 5) mg/l Oncorhynchus mykiss	
EC50 - Crustacea [1]	48h 3 (≤ 10) mg/l Daphnia magna	
EC50 - Other aquatic organisms [1]	72h 1 (≤ 3) mg/l Pseudokirchneriella subcapitata	
NOEC chronic fish	0,441 mg/l	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C10, aromatics, <1% naphthalene		
NOEC chronic crustacea	0,771 mg/l	
NOEC chronic algae	1 mg/l	
2-butoxyethanol (111-76-2)		
LC50 - Fish [1]	96h 1464 mg/l Oncorhynchus mykiss	
EC50 - Crustacea [1]	48h 1800 mg/l Daphnia magna	
EC50 - Other aquatic organisms [1]	72h 911 mg/l Pseudokirchneriella subcapitata	
NOEC (acute)	72h 88 mg/l Pseudokirchneriella subcapitata	
2-ethylhexan-1-ol (104-76-7)		
LC50 - Fish [1]	96h 28,2 mg/l pimephales promelas	
EC50 - Crustacea [1]	48h 39 mg/l daphnia magna	
EC50 - Other aquatic organisms [1]	72h 11,5 mg/l algae (desmodesmus subspicatus)	
Naphthalene (91-20-3)		
LC50 - Fish [1]	96h 1,6 mg/l Oncorhynchus mykiss	
EC50 - Crustacea [1]	48h 2,16 mg/l Daphnia magna	

## 12.2. Persistence and degradability

C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)		
Persistence and degradability	Readily biodegradable.	
Hydrocarbons, C10, aromatics, <1% naphthalene		
Persistence and degradability	Readily biodegradable.	
Biodegradation	50 %	
2-butoxyethanol (111-76-2)		
Persistence and degradability	Readily biodegradable.	
2-ethylhexan-1-ol (104-76-7)		
Persistence and degradability	Readily biodegradable.	
12.3. Bioaccumulative potential		
C8-C26 branched and linear hydrocarbons – E	Distillates (848301-67-7)	
Partition coefficient n-octanol/water (Log Pow)	> 6,5 @40°C	
2-butoxyethanol (111-76-2)		
Bioaccumulative potential	Slightly bioaccumulative.	
2-ethylhexan-1-ol (104-76-7)		
Bioaccumulative potential	No bioaccumulation.	
12.4. Mobility in soil		
2-butoxyethanol (111-76-2)		
Ecology - soil	Small adsorption.	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment	
Component	
2-ethylhexan-1-ol (104-76-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
12.6. Endocrine disrupting properties	

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal consideration	s
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.
European List of Waste (LoW) code	: 14 06 03* - other solvents and solvent mixtures 15 01 10* - packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

ADR	IMDG	ΙΑΤΑ	ADN	RID
I4.1. UN number or ID	number			
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
4.2. UN proper shippi	ng name	1		
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard	class(es)	· · · · · · · · · · · · · · · · · · ·		
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental ha	zards			
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

14.6. Special precautions for user

Overland transport Not regulated

Transport by sea Not regulated

Air transport Not regulated

**Inland waterway transport** Not regulated

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

**Explosives Precursors Regulation (2019/1148)** 

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

#### France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) Hazardous Incident Ordinance (12. BImSchV)	<ul> <li>WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).</li> <li>Is not subject of the Hazardous Incident Ordinance (12. BImSchV)</li> </ul>
Netherlands	
SZW-lijst van kankerverwekkende stoffen SZW-lijst van mutagene stoffen SZW-lijst van reprotoxische stoffen – Borstvoedin SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkelin Denmark Class for fire hazard	g : None of the components are listed : Class III-1

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Store unit Classification remarks	<ul> <li>50 liter</li> <li>Flammable according to the Danish Ministry of Justice; Emergency management guidelines</li> </ul>
Danish National Regulations	<ul> <li>for the storage of flammable liquids must be followed</li> <li>Young people below the age of 18 years are not allowed to use the product</li> <li>The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal</li> </ul>

### 15.2. Chemical safety assessment

No additional information available

### **SECTION 16: Other information**

Full text of H- and EUH	Full text of H- and EUH-statements:		
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Asp. Tox. 1	Aspiration hazard, Category 1		
Carc. 2	Carcinogenicity, Category 2		
EUH066	Repeated exposure may cause skin dryness or cracking.		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H351	Suspected of causing cancer.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.