

Safety Data Sheet

according to Commission Regulation (EU) 2020/878 as amended

DIESEL INJECTOR CLEANER

TEC-2000 LTD.

P. O. BOX 285, Hitchin, HERTS., SG4 9WQ, U.K.

info@TEC-2000.co.uk

PH: 01462-433 660 FAX: 01462-674 468 MOB: 07831-105 386

Revision Dated: 21-November-2023

Version Number: 21

SECTION 1: Identification of the substance	/mixture and of the company/undertaking
1.1 Product Identifier	TEC-2000 DIESEL INJECTOR CLEANER
Substance / mixture	mixture
UFI:	1500-C029-G007-DEHS
1.2 Relevant identified uses of the substan	ce or mixture and uses advised against
Mixture's intended use	
Cleaning Diesel Powered Combustion Eng	gine Fuel Injectors In Situ.
Main intended use	
PC-CLN-OTH	Other cleaning, care and maintenance products (excludes biocidal products)
Mixture uses advised against	
The product should not be used in ways o	
1.3 Details of the supplier of the safety data	a sheet
Manufacturer	
Name or trade name	TEC-2000 LIMITED
Address	PO Box 285, Hitchin, Hertfordshire, SG4 9WQ, United Kingdom
VAT Reg No	GB626640834
Phone	+44 (0) 1462 433 660
E-mail	mike@tec-2000.co.uk
Web address	www.tec-2000.co.uk
Competent person responsible for the	
Name	TEC-2000 LIMITED
E-mail	mike@tec-2000.co.uk
1.4 Emergency telephone number	
0044 (Ø) 7831 105386 (24hrs)	
NHS Direct: 111	
	(NPIS): 0344 892 0111 (healthcare professionals only).
ireiand - National Poisons information Cer	ntre (NPIC): (01) 809 2566 (healthcare professionals only).
SECTION 2: Hazards identification	

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 The mixture is classified as dangerous.

Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

Most serious adverse effects on human health and the environment

Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging the unborn child. May cause an allergic skin reaction. Harmful if inhaled. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.





Registered office: Second Floor, 2 Walsworth Road, Hitchin, Hertfordshire, SG4 9SP Registered in England No. 460 8392

2.2 Label elements Hazard pictograms:



Signal word:	
Danger	
Hazardous substance	es
Acetone	
propan-2-ol	
Distillates (petroleum),	hydro- treated light
toluene	
permethrin (ISO)	
2-ethylhexyl nitrate	
, ,	pxocyclopent-2-enyl(1R,3R)-2,2-dimethyl-3-(2-methylprop-1-enyl) cyclopropanecarboxylate
Hazard statements	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statem	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
5040	Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501 Supplemental inform	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental inform	iation: acarbans 5 <15 % aromatic hydrocarbans <5 % anionic surfactants

>=30 % aliphatic hydrocarbons, 5-<15 % aromatic hydrocarbons, <5 % anionic surfactants

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3 Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment					
Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note	
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49-XXXX	acetone	20-25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	2	

Version Number: 21	TEC-2000 Diesel In	jector Clea	ner	Revision Date: 21-No	vember-2023
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25-XXXX	propan-2-ol	20-25	Flam. Liq. 2, H2 Eye Irrit. 2, H31 STOT SE 3, H3	9	
Index: 649-422-00-2 CAS: 64742-47-8 EC: 265-149-8 Registration number: 01-2119484819-18-XXXX	Distillates (petroleum), hydro- treated light	10-25	Flam. Liq. 3, H2 Asp. Tox. 1, H3(Acute Tox. 3, H3	04	
Index: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 Registration number: 01-2119471310-51-XXXX	toluene	10-<20	Flam. Liq. 2, H2 Asp. Tox. 1, H30 STOT SE 3, H33 Repr. 2, H361d STOT RE 2, H3 Aquatic Chronic	04 36 73	2, 3
Index: 613-058-00-2 CAS: 52645-53-1 EC: 258-067-9	permethrin (ISO)	2,5-10			
CAS: 51-03-6 EC: 200-076-7 Registration number: 01-2119537431-46-XXXX	1,3-Benzodioxole, 5-[[2-(2-butoxyethoxy) ethoxy]methyl]-6-propyl-	2,5-10	Acute Tox. 3, H Aquatic Chronic	311	
CAS: 27247-96-7 EC: 248-363-6 Registration number: 01-2119539586-27-XXXX	2-ethylhexyl nitrate	0,25-<2,5	Acute Tox. 4, H3 Aquatic Chronic	302+H312+H332 2, H411	
Index: 006-025-00-3 CAS: 28434-00-6 EC: 249-013-5	(S)-3-allyl-2-methyl-4-oxocyclopent-2-enyl (1R,3R)-2,2-dimethyl-3-(2-methylprop-1- enyl)cyclopropanecarboxylate	0,25-<1	Acute Tox. 4, H Aquatic Acute 1 Aquatic Chronic	, H400 (M=1) 1, H410 (M=1)	1
Index: 649-424-00-3 CAS: 64742-94-5 EC: 265-198-5 Registration number: 01-2119510128-50-XXXX	Solvent naphtha (petroleum), heavy arom.	0,1-<1	Asp. Tox. 1, H3(Resp. Sens. 1, H		
Index: 601-052-00-2 CAS: 91-20-3 EC: 202-049-5 Registration number: 01-2119561346-37-XXXX	naphthalene	0,1-<0,25	Acute Tox. 4, H Carc. 2, H351 Aquatic Acute 1 Aquatic Chronic		2

Notes

1. Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

2. Substance with a Union workplace exposure limit.

3. The use of the substance is restricted by Annex XVII of REACH Regulation.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately. If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2 Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause drowsiness or dizziness. If on skin May cause an allergic skin reaction. If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting Measures

5.1 Extinguishing media

Suitable extinguishing agents:

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3 Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2 Environmental precautions

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

6.3 Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4 Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling:

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Wash hands and exposed parts of the body thoroughly after handling. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2 Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3 Specific end use(s):

not available

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union			Commission Directive 2000/39/EC
Substance name (component)	Туре	Value	Note
anotono (CAS: 67 64 1)	OEL 8 hours	1210 mg/m ³	
acetone (CAS: 67-64-1)	OEL 8 hours	500 ppm	
European Union			Commission Directive 2006/15/EC
Substance name (component)	Туре	Value	Note
	OEL 8 hours	192 mg/m ³	
toluene (CAS: 108-88-3)	OEL 8 hours	50 ppm	Skin
	OEL 15 minutes	384 mg/m ³	SKIII
	OEL 15 minutes	100 ppm	
European Union		•	Commission Directive 91/322/EC
Substance name (component)	Туре	Value	Note
naphthalene (CAS: 91-20-3)	OEL 8 hours	50 mg/m³	
European Union		-	Commission Directive 91/322/EEC
Substance name (component)	Туре	Value	Note
naphthalene (CAS: 91-20-3)	OEL 8 hours	10 ppm	
DNEL			

2-ethylhexyl nitrate

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Dermal	1 mg/kg bw/day	Systemic chronic effects		
Workers	Inhalation	0.35 mg/m ³	Systemic chronic effects		
Workers	Dermal	0.044 mg/cm ²	Local acute effects		

PNEC

2-ethylhexyl nitrate

Route of exposure	Value	Value determination	Source
Drinking water	0.8 µg/l		
Seawater	0.08 µg/l		
Freshwater sediment	0.74 µg/l		

8.2 Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest. **Eye/face protection**

Protective goggles. Skin protection

Skin protection

Hand protection: Protective gloves resistant to the product. (np. Butyl rubber, BR) EN ISO 374-1. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Contaminated skin should be washed thoroughly.

/ersion Number: 21	TEC-2	000 Diesel Injector Cleaner	Revision Date: 21-November-2023
Respiratory protection			
Mask with a filter against or	ganic vapours in a poor	ly ventilated environment.	
Thermal hazard			
Data not available.	<i>.</i> .		
Environmental exposure			
Observe usual measures for	or protection of the envir	onment, see Section 6.2. Collect spillage.	
SECTION 9: Physical and Ch	emical Properties		
.1 Physical and chemical pr	operties		
Physical state		liquid	
Colour		orange	
Odour		data not available	
Melting point/freezing point		data not available	
Boiling point or initial boiling	point and boiling range	e 56 °C	
Flammability		data not available	
Lower and upper explosion	limit	data not available	
Flash point		0°C	
Auto-ignition temperature		data not available	
Decomposition temperature)	data not available	
pH		non-soluble (in water)	
Kinematic viscosity		data not available	
Solubility in water		data not available	
Partition coefficient n-octan	ol/water (log value)	data not available	

Vapour pressure Density and/or relative density 9.2 Other information

not available

SECTION 10: Stability and Reactivity

10.1 Reactivity:

Not available.

10.2 Chemical stability

The product is stable under normal conditions.

10.3 Possibility of hazardous reactions: Unknown

10.4 Conditions to avoid:

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. **10.5 Incompatible materials:**

data not available

data not available

Protect against strong acids, bases and oxidizing agents.

10.6 Hazardous decomposition products:

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide and nitrogen oxides are formed at high temperature and in fire.

SECTION 11: Toxicological Information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Harmful if inhaled

1,3-Benzodioxole, 5-[[2-(2-butoxyethoxy)ethoxy]methyl]-6-propyl-

Route of exposure	Parameter	Value	Exposure tim	ie Species	Sex
Oral	LD ₅₀	7181 mg/kg		Rat	
Dermal	LD_{50}	>2000 mg/kg		Rabbit	
Inhalation	LC ₅₀	>5.9 mg/l	4 hour	Rat	
2-ethylhexyl nitrate	•	•	•	•	•

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Dermal	LD ₅₀	>4820 mg/kg		Rabbit	
Oral	LD ₅₀	>9640 mg/kg		Rat	

Version Number: 21	Version	Number:	21
--------------------	---------	---------	----

TEC-2000 Diesel Injector Cleaner

acetone

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5800 mg/kg		Rat	
Dermal	LD ₅₀	20000 mg/kg		Rabbit	
Distillates (petroleum), hydro- t	treated light	•		•	
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Inhalation	LC ₅₀	5 mg/l	4 hour	Rat	
naphthalene				-	
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	490 mg/kg		Rat	
Dermal	LD ₅₀	5000 mg/kg		Rabbit	
propan-2-ol					•
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5840 mg/kg		Rat	
Dermal	LD ₅₀	12800 mg/kg		Rabbit	
Inhalation	LC ₅₀	30 mg/l	4 hour	Rat	
toluene				-	
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5000 mg/kg		Rat	
Dermal	LD ₅₀	12124 mg/kg		Rabbit	
Inhalation	LC ₅₀	5320 mg/l	4 hour	Rat	

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity:

Suspected of damaging the unborn child.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Very toxic to aquatic life with long lasting effects.

propan-2-ol

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	9640 mg/l	96 hour	Fishes	
LC ₅₀	>10000 mg/l	24 hour	Daphnia	

Chronic toxicity

propan-2-oi					
Parameter	Value	Exposure time	Species	Environment	
NOEC	1050 mg/l	Microorganisms			

12.2 Persistence and degradability:

The mixture is biodegradable.

12.3 Bioaccumulative potential:

Data not available.

12.4 Mobility in soil:

Data not available.

12.5 Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6 Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7 Other adverse effects:

Data not available.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport Information

- 14.1 UN Number or ID number
- UN1993
- 14.2 UN proper shipping name
 - FLAMMABLE LIQUID, N.O.S. (ACETONE, ISOPROPANOL (ISOPROPYL ALCOHOL))
- 14.3 Transport hazard class(es)
- 3 Flammable liquids
- 14.4 Packing group
 - II substances presenting medium danger
- 14.5 Environmental hazards: not relevant
- 14.6 Special precautions for user
- Reference in the Sections 4 to 8. 14.7 Maritime transport in bulk according to IMO instruments

not relevant Additional information

Hazard identification No. UN number Classification code Safety signs

33 1993 F1



Marine transport - IMDG EmS (emergency plan) MFAG

F-E, S-E 310

SECTION 15: Regulatory Information.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9.

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

toluene

Restriction	Conditions of restriction
48	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other Information.				
A list of standard risk phrases used in the safety data sheet				
H225	Highly flammable liquid and vapour.			
H226	Flammable liquid and vapour.			
H302	Harmful if swallowed.			
H304	May be fatal if swallowed and enters airways.			
H311	Toxic in contact with skin.			
H317	May cause an allergic skin reaction.			
H319	Causes serious eye irritation.			
H331	Toxic if inhaled.			
H332	Harmful if inhaled.			
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.			
H336	May cause drowsiness or dizziness.			
H351	Suspected of causing cancer.			
H361d	Suspected of damaging the unborn child.			
H373	May cause damage to organs through prolonged or repeated exposure.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
H411	Toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			
H302+H332	Harmful if swallowed or if inhaled.			
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.			
	handling used in the safety data sheet			
P101	If medical advice is needed, have product container or label at hand.			
P102	Keep out of reach of children.			
P271	Use only outdoors or in a well-ventilated area.			
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.			
P331	Do NOT induce vomiting.			
P405	Store locked up.			
P501	Dispose of contents/container to in accordance with local/regional/national/international regulations.			
P103	Read label before use.			
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.			
P337+P313	If eye irritation persists: Get medical advice/attention.			
P362+P364	Take off contaminated clothing and wash it before reuse.			
P312	Call a POISON CENTER/doctor if you feel unwell.			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
P280	Wear protective gloves/protective clothing/eye protection/face protection. P304+P340 IF INHALED: Remove person to			
0204.0240	fresh air and keep comfortable for breathing.			
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue			
P321	rinsing.			
A list of additional standard phrases used in the safety data sheet EUH066 Repeated exposure may cause skin dryness or cracking.				
	cepeared exposure may cause skill dryness of Gacking.			

Version Number: 21	TEC-	2000 Diesel Injector Cleaner	Revision Date: 21-November-2023		
Other important information about human health protection					
		ed by the manufacturer/importer - used for purposes	other than as per the Section 1. The		
	for adherence to all related health				
Key to abbreviat	ns and acronyms used in the s	afety data sheet			
ADR		the international carriage of dangerous goods by roa	d		
BCF	Bioconcentration Factor				
CAS	Chemical Abstracts Service				
CLP	Regulation (EC) No 1272/2008 or	n classification, labelling and packaging of substance	and mixtures		
DNEL	Derived no-effect level				
EINECS	European Inventory of Existing C	ommercial Chemical Substances			
EmS	Emergency plan				
ES	Identification code for each subst	ance listed in EINECS			
EU	European Union				
EuPCS	European Product Categorisation	i System			
IATA	International Air Transport Associ	iation			
IBC	International Code For The Const	truction And Equipment of Ships Carrying Dangerous	Chemicals		
ICAO	International Civil Aviation Organi	ization			
IMDG	International Maritime Dangerous	Goods			
INCI	International Nomenclature of Co	smetic Ingredients			
ISO	International Organization for Sta	ndardization			
IUPAC	International Union of Pure and A	pplied Chemistry			
LC_{50}	Lethal concentration of a substan	ce in which it can be expected death of 50% of the p	opulation		
LD_{50}	Lethal dose of a substance in whi	ich it can be expected death of 50% of the population			
log Kow	Octanol-water partition coefficient	t			
MARPOL	International Convention for the F	Prevention of Pollution from Ships			
NOEC	No observed effect concentration				
OEL	Occupational Exposure Limits				
PBT	Persistent, Bioaccumulative and				
PNEC	Predicted no-effect concentration				
ppm	Parts per million				
REACH		ation and Restriction of Chemicals			
RID	Agreement on the transport of da				
UN		of the substance or article taken from the UN Model I			
UVCB		le composition, complex reaction products or biologic	cal materials		
VOC	Volatile organic compounds				
vPvB	Very Persistent and very Bioaccu	mulative			
Acute Tox.	Acute toxicity				
Aquatic Acute	Hazardous to the aquatic environ				
Aquatic Chronic	Hazardous to the aquatic environment (chronic)				
Asp. Tox.	Aspiration hazard				
Carc.	Carcinogenicity				
Eye Irrit. Flam. Liq.	Eye irritation Flammable liquid				
Repr. Resp. Sens.	Reproductive toxicity Respiratory sensitization				
Skin Sens.	Skin sensitization				
STOT RE	Specific target organ toxicity - repeated exposure				
STOT SE	Specific target organ toxicity - rep Specific target organ toxicity - sin				

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product. Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 2.0 replaces the SDS version from 10.08.2021. Change of product composition.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.