

Safety Data Sheet

according to Commission Regulation (EU) 2020/878 as amended

FUEL SYSTEM CLEANER

(Tank Additive)

TEC-2000

P. O. BOX 285. litchin HERTS.. SG4 9WQ U.K

info@TEC-2000.co.uk

01462-433 660 01462-674 468 FAX: MOB: 07831-105 386

PH:

Version Number: 18

Revision Date: 21-November-2023 SECTION 1: Identification of the substance/mixture and of the company/undertaking **1.1 Product Identifier TEC-2000 FUEL SYSTEM CLEANER TANK ADDITIVE** Substance / mixture mixture UFI: VA00-C0F3-3007-Q3PW 1.2 Relevant identified uses of the substance or mixture and uses advised against Mixture's intended use Petrol Tank Addditive To Promote Cleaner Exhaust Emissions. Main intended use PC-FUE-5 Fuel additives and fuel components Mixture uses advised against The product should not be used in ways other then those referred in Section 1. 1.3 Details of the supplier of the safety data sheet Manufacturer **TEC-2000 LIMITED** Name or trade name Address PO Box 285, Hitchin, Hertfordshire, SG4 9WQ United Kingdom VAT Reg No GB626640834 Phone +44 (0) 1462 433 660 Email: mike@tec-2000.co.uk Website: www.tec-2000.co.uk Competent person responsible for the safety data sheet Name **TEC-2000 LIMITED** E-mail mike@tec-2000.co.uk 1.4 Emergency telephone number 0044 (Ø) 7831 105386 (24hrs) NHS Direct: 111 UK-National Poisons Information Service (NPIS): 0344 892 0111 (healthcare professionals only). Ireland - National Poisons Information Centre (NPIC): (01) 809 2566 (healthcare professionals only). **SECTION 2: Hazards identification** 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The mixture is classified as dangerous. Flam. Lig. 2, H225 Asp. Tox. 1, H304 Eye Dam. 1, H318 STOT SE 3, H335-H336 Aquatic Chronic 2, H411 Full text of all classifications and hazard statements is given in the section 16. Most serious adverse physico-chemical effects Highly flammable liquid and vapour. Most serious adverse effects on human health and the environment May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Causes serious eye damage. Suspected of causing cancer. Toxic to aquatic life with long lasting effects. 2.2 Label elements Hazard pictograms: Signal word: Danger





Registered office: Second Floor, 2 Walsworth Road, Hitchin, Hertfordshire, SG4 9SP Registered in England No. 460 8392

Version Number: 18	TEC-2000 Fuel System Cleaner (Tank Additive)	Revision Date: 21-November-2023
Hazardous substan	ces	
acetone		
propan-2-ol		
Petroleum Light aron	natic C9	
Poly(oxy-1,2-ethaned	tiyl), .alphatridecylomegahydroxy-	
Hazard statements:		
H225	Highly flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H318	Causes serious eye damage.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
Precautionary state	ments:	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.	No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.	-
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P301+P310	IF SWALLOWED: Immediately call a doctor.	
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse	e skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lense	s, if present and easy to do.
	Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor.	
P331	Do NOT induce vomiting.	
P405	Store locked up.	
P501	Dispose of contents/container to according to local/by regional/according to national	/by international regulations.
Supplemental inform		, ,
EUH066	Repeated exposure may cause skin dryness or cracking.	
>30% aromatic hydro	ocarbons, <5% non-ionic surfactants	
	hild-resistant fastenings and tactile warning of danger	
	a tactile warning of danger. Container must be fitted with child-resistant fastening.	
2.3 Other hazards		

2.3 Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
 - Chemical characterization

Mixture.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49- XXXX	acetone	25-50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	1
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25- XXXX	propan-2-ol	25-50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
CAS: 64742-95-6 EC: 918-668-5 Registration number: 01-2119455851-35- XXXX	Petroleum Light aromatic C9	25-50	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411	
CAS: 24938-91-8	Poly(oxy-1,2-ethanediyl), .alphatridecylomegahydroxy-	3-<5	Acute Tox. 4, H302 Eye Dam. 1, H318	

TEC-2000 Fuel System Cleaner (Tank Additive)

Revision Date: 21-November-2023

Identification numbers	Substance name	Content in % weight	· · · · · · · · · · · · · · · · · · ·	Note
Index: 601-052-00-2 CAS: 91-20-3 EC: 202-049-5 Registration number: 01-2119561346-37- XXXX	naphthalene		Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	1

Notes

Substance with a Union workplace exposure limit.

SECTION 4: First aid measures

4.1 Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately. If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eves

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2 Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system. Cough, headache. May cause respiratory irritation. May cause drowsiness or dizziness.

If on skin Not expected. If in eyes Causes serious eye damage. If swallowed

Corrosion of the digestion system can occur.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full iet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3 Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2 Environmental precautions

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

6.3 Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4 Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2 Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3 Specific end use(s):

not available

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union	Commission Directive 2000/39/E	
Substance name (component)	Туре	Value
acetone (CAS: 67-64-1)	OEL 8 hours	1210 mg/m ³
	OEL 8 hours	500 ppm

European Union	Commission Directive 91/322/EEC		
Substance name (component)	Туре	Value	
nanhthalana (CAS: 01 20 2)	OEL 8 hours	50 mg/m³	
naphthalene (CAS: 91-20-3)	OEL 8 hours	10 ppm	

8.2 Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Contaminated skin should be washed thoroughly.

Respiratory protection

Mask with a filter in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical propert	ies
Physical state	liquid
Colour	red
Odour	data not available
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	56 °C
Flammability	data not available
Lower and upper explosion limit	
bottom	0,8 %
upper	13,3 %

	1EC-200	D Fuel System Clea	ner (Tank Additive)	Revision Date:	21-November-202
Flash point		0 °C			
Auto-ignition temperatur	e	data not available	ġ		
Decomposition temperat		data not available			
pH		non-polar/aprotic			
Kinematic viscosity		<7 mm²/s at 40 °			
Solubility in water		miscible			
Partition coefficient n-oc	tanol/water (log value)	data not available	9		
Vapour pressure		data not available)		
Density and/or relative d	ensity	data not available	9		
Relative vapour density		data not available			
Particle characteristics		data not available	9		
.2 Other information:					
not available					
ECTION 10: Stability and	Reactivity				
0.1 Reactivity					
not available					
0.2 Chemical stability					
The product is stable u		S.			
0.3 Possibility of hazardo Unknown.	ous reactions				
0.4 Conditions to avoid					
	and no degradation oc	curs under normal use. Prote	rt against flames, sparks, ov	arheating and agai	net fraet
0.5 Incompatible materia			a against harnes, sparks, ow	enteating and again	131 11031.
Protect against strong		izing agents			
0.6 Hazardous decompos					
		us outcomes such as carbon	monoxide and carbon dioxide	e are formed at hig	h temperature an
in fire.					
ECTION 11: Toxicologica					
		in Regulation (EC) No 1272			
		exceeding exposure limits fo			nalation noisoning
depending on the leve Acute toxicity	I of concentration and	expositive time. No toxicologic	al data is available for the m		
				ixture.	
	ta the classification crit			ixture.	
Based on available da	ta the classification crit			ixture.	
Based on available da	ta the classification crit Parameter		Exposure time	species	Sex
Based on available da cetone	<u> </u>	teria are not met.			
Based on available da cetone Route of exposure	Parameter LD ₅₀	teria are not met. Value 5800 mg/kg		Species	
Based on available da cetone Route of exposure Oral Dermal	Parameter	teria are not met. Value		Species Rat	
Based on available da etone Route of exposure Oral Dermal aphthalene Route of exposure	Parameter LD ₅₀ LD ₅₀ Parameter	teria are not met. Value 5800 mg/kg 20000 mg/kg Value		Species Rat Rabbit Species	
Based on available da etone Route of exposure Oral Dermal aphthalene Route of exposure Oral	Parameter LD ₅₀ LD ₅₀ Parameter LD ₅₀	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg	Exposure time	Species Rat Rabbit Species Rat	Sex
Based on available da etone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal Dermal	Parameter LD ₅₀ LD ₅₀ Parameter	teria are not met. Value 5800 mg/kg 20000 mg/kg Value	Exposure time	Species Rat Rabbit Species	Sex
Based on available da etone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal Dermal opan-2-ol	Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50}	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg	Exposure time	Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal	Parameter LD ₅₀ LD ₅₀ Parameter LD ₅₀ LD ₅₀ Parameter	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value Value Value Value Value Value Value Value Value Source Value	Exposure time	Species Rat Rabbit Species Rat	Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure Oral	Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} Parameter LD_{50}	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure	Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50}Parameter LD_{50} LD_{50}	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure Oral Dermal Dermal Inhalation	Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50}	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure Oral Dermal Dermal Inhalation Skin corrosion/irritat	Parameter LD_{50} LD_{50} Parameter LD_{50} LO_{50}	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da	Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} Parameter LD_{50} Interval 1000000000000000000000000000000000000	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/	Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} Parameter LD_{50} Parameter LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LC_{50} ion ta the classification crit /irritation	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/ Causes serious eye da	Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} LO_{50} amage.	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/ Causes serious eye da	Parameter LD_{50} LD_{50} Parameter LD_{50} LC_{50} ion ta the classification crit amage. sensitization	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l teria are not met.	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/ Causes serious eye da Respiratory or skin s Based on available da	Parameter LD_{50} LD_{50} Parameter LD_{50} LC_{50} ion ta the classification crit amage. sensitization ta the classification crit	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l teria are not met.	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/ Causes serious eye da Respiratory or skin s Based on available da Germ cell mutagenic	Parameter LD_{50} LD_{50} $Parameter$ LD_{50} LC_{50} ion ta the classification critication amage. exensitization ta the classification critication crit	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l teria are not met. teria are not met.	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/ Causes serious eye da Respiratory or skin s Based on available da Germ cell mutagenic Based on available da	Parameter LD_{50} LD_{50} $Parameter$ LD_{50} LC_{50} ion ta the classification critication amage. exensitization ta the classification critication crit	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l teria are not met. teria are not met.	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/ Causes serious eye da Respiratory or skin s Based on available da Germ cell mutagenic Based on available da Carcinogenicity	Parameter LD_{50} LD_{50} $Parameter$ LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LC_{50} ion ta the classification crit /irritation amage. sensitization ta the classification crit ity ta the classification crit	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l teria are not met. teria are not met.	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da cetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal ropan-2-ol Route of exposure Oral Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/ Causes serious eye da Respiratory or skin s Based on available da Germ cell mutagenic Based on available da Carcinogenicity Suspected of causing	Parameter LD_{50} LD_{50} Parameter LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LD_{50} LC_{50} ion ta the classification crit /irritation amage. sensitization ta the classification crit ity ta the classification crit ity ta the classification crit cancer.	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l teria are not met. teria are not met.	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex
Based on available da acetone Route of exposure Oral Dermal aphthalene Route of exposure Oral Dermal Dermal Dermal Inhalation Skin corrosion/irritat Based on available da Serious eye damage/ Causes serious eye da Respiratory or skin s Based on available da Germ cell mutagenic Based on available da Carcinogenicity	Parameter LD ₅₀ LD ₅₀ Parameter LD ₅₀ LD ₅₀ LD ₅₀ LD ₅₀ LD ₅₀ ion ta the classification crit /irritation amage. sensitization ta the classification crit ity ta the classification crit cancer.	teria are not met. Value 5800 mg/kg 20000 mg/kg Value 490 mg/kg 5000 mg/kg Value 5840 mg/kg 12800 mg/kg 30 mg/l teria are not met. teria are not met. teria are not met.	Exposure time	Species Rat Rabbit Species Rat Rabbit Species Rat Rabbit	Sex Sex

Based on available data the classification criteria are not met. **Toxicity for specific target organ - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Toxic to aquatic life with long lasting effects.

Petroleum Light aromatic C9

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	3.2 mg/l	48 hour	Daphnia	
propan-2-ol				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	9640 mg/l	96 hour	Fishes	
LC_{50}	>10000 mg/l	24 hour	Daphnia	

Chronic toxicity

propan-2-ol

Parameter	Value	Exposure time	Species	Environment
NOEC	1050 mg/l		Microorganisms	

12.2 Persistence and degradability

Petroleum Light aromatic C9

>60 % 28 day Biodegrada	Result	Environment	Exposure time	Value	Parameter
Diodograda	Biodegradable		28 day	>60 %	

The mixture is biodegradable.

12.3 Bioaccumulative potential

Data not available.

12.4 Mobility in soil

Data not available. 12.5 Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6 Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7 Other adverse effects

Data not available.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport Information

14.1 UN Number or ID number

- UN 1993
- 14.2 UN proper shipping name
 - PETROLEUM DISTILLATES, N.O.S. (Solvent naphtha (petroleum) light aromatic C9)
- 14.3 Transport hazard class(es) 3 Flammable liquids

14.4 Packing group

- II substances presenting medium danger
- 14.5 Environmental hazards: not relevant

Version Number: 18	TEC-2	OOO Fuel Syste	em Cleaner	(Tank Additive)	Revision Date: 21-November-2023
14.6 Special precaution	is for user				
not available	in hulk according	to IMO instrumente	Not relevant.		
14.7 Maritime transport Additional informa	•		NULTEIEValli.		
Hazard identification		33			
UN number		1993			
Classification code		F1			
Safety signs		3+hazardous for the	environment		
			¥		
Air transport - ICA		•	\checkmark		
Packaging instruction		355			
Cargo packaging in		366			
Marine transport - EmS (emergency p		F-E, S-E			
MFAG		310			
		010			

SECTION 15: Regulatory Information.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9.

15.2 Chemical safety assessment

not available

SECTION 16: Other	Information.
A list of standard ri	sk phrases used in the safety data sheet
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
	handling used in the safety data sheet
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P301+P310	IF SWALLOWED: Immediately call a doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container to according to local/by regional/according to national/by international regulations.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 Immediately call a POISON
D205 . D254 . D220	CENTER/doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing.

Version Number: 18	TEC-2000 Fuel System Cleaner (Tank Additive) Revision Date: 21-November-202	3	
A list of additional standard phrases used in the safety data sheet EUH066 Repeated exposure may cause skin dryness or cracking. Other important information about human health protection			
The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.			
Key to abbreviations and acronyms used in the safety data sheet			
ADR	uropean agreement concerning the international carriage of dangerous goods by road		
BCF CAS	ioconcentration Factor Chemical Abstracts Service		
CLP	legulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures		
EC ₅₀	Concentration of a substance when it is affected 50% of the population		
EINECS	European Inventory of Existing Commercial Chemical Substances		
EmS	mergency plan		
ES	dentification code for each substance listed in EINECS		
EU	uropean Union		
EuPCS	uropean Product Categorisation System		
IATA	nternational Air Transport Association		
IBC	nternational Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals		
ICAO	nternational Civil Aviation Organization		
IMDG	nternational Maritime Dangerous Goods		
INCI	nternational Nomenclature of Cosmetic Ingredients		
ISO IUPAC	nternational Organization for Standardization nternational Union of Pure and Applied Chemistry		
LC_{50}	ethal concentration of a substance in which it can be expected death of 50% of the population		
LD ₅₀	ethal dose of a substance in which it can be expected death of 50% of the population		
log Kow	Octanol-water partition coefficient		
MARPOL	iternational Convention for the Prevention of Pollution from Ships		
NOEC	lo observed effect concentration		
OEL	Occupational Exposure Limits		
PBT	Persistent, Bioaccumulative and Toxic		
ppm	Parts per million		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals		
RID	greement on the transport of dangerous goods by rail		
UN	our-figure identification number of the substance or article taken from the UN Model Regulations		
UVCB	ubstances of unknown or variable composition, complex reaction products or biological materials		
VOC vPvB	olatile organic compounds /ery Persistent and very Bioaccumulative		
Acute Tox.	cute toxicity		
Aquatic Acute	lazardous to the aquatic environment		
Aquatic Chronic	lazardous to the aquatic environment (chronic)		
Asp. Tox.	spiration hazard		
Carc.	arcinogenicity		
Eye Dam.	erious eye damage		
Eye Irrit.	ye irritation		
Flam. Liq.	lammable liquid		
STOT SE	pecific target organ toxicity - single exposure		
Training quidalines			

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product. Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 2.0 replaces the SDS version from 11.08.2021. Change of product composition.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.