SAFETY DATA SHEET


5in1 LPG valve saver

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier ▼ Trade name 5in1 LPG valve saver Product no. 687253 Unique formula identifier (UFI) TRAD-FYK5-610K-GVXF 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture Additive Use descriptors (REACH) **Product category** Description Additives to petrol or diesel fuel Uses advised against None known. 1.3. Details of the supplier of the safety data sheet Company and address **Maumo International BV** P.O. Box 441 2990 AK Barendrecht Nederland +31 (0)180 699234 +31 (0)180 699235 www.maumo.nl Contact person **Product Safety Department** E-mail info@maumo.nl Revision 25/01/2023 SDS Version 3.0 Date of previous version 24/01/2023 (2.0) 1.4. Emergency telephone number Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures". SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Asp. Tox. 1; H304, May be fatal if swallowed and enters airways. Skin Irrit. 2; H315, Causes skin irritation.

Eye Dam. 1; H318, Causes serious eye damage.

2.2. Label elements

Hazard pictogram(s)



3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, <2% aromatics	CAS No.: EC No.: 918-481-9 UK-REACH: Index No.:	40-60%	EUH066 Asp. Tox. 1, H304	
Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified	CAS No.: 64742-53-6 EC No.: 265-156-6 UK-REACH: Index No.: 649-466-00-2	25-40%	Asp. Tox. 1, H304	[12], [19]
Potassium 1,2-bis(2- ethylhexyloxycarbonyl)ethane sulphonate	CAS No.: 7491-09-0 EC No.: 231-308-5 UK-REACH: Index No.:	10-15%	Skin Irrit. 2, H315 Eye Dam. 1, H318	
Distillates (petroleum), hydrotreated light;Kerosine - unspecified	CAS No.: 64742-47-8 EC No.: 265-149-8 UK-REACH:	5-10%	Asp. Tox. 1, H304	

Index No.: 649-422-00-2

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[12] The classification as a carcinogen will not be taken into account as the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method' (CLP, Annex VI, note L).
[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides

Carbon oxides (CO / CO2)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures Avoid direct contact with spilled substances.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material Keep only in original packaging.

Storage temperature

Dry, cool and well ventilated

Store out of direct sunlight.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Long term exposure limit (8 hours) (ppm): 184 Long term exposure limit (8 hours) (mg/m³): 1200

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified

Duration	Route of exposure	DNEL
Long term – Local effects - Workers	Inhalation	5,58 mg/m³
Potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate		

Duration	Route of exposure	DNEL
	Dermal	13,4 mg/kgbw/day
	Inhalation	46,6 mg/m³

No data available.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

8.3. Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

	Туре	Class	Colour		Standards	
	No special when used as intended.					
Sk	in protection					
	Recommended	Type/Category		Standards		
	Dedicated work clothing should be worn.	-		-		R
Ha	and protection					
	Material	Glove thickness (mm)	Breakthrou (min.)	ıgh time	Standards	
	Nitrile	0,38	> 240		EN374-2, EN374-3, EN388	

Eye protection

Туре	Standards
Safety glasses with side shields.	EN166

SECTION 9: Physical and chemical properties

```
9.1. Information on basic physical and chemical properties
Physical state

Liquid
Colour
Colourless

Odour / Odour threshold

Characteristic
pH
Testing not relevant or not possible due to nature of the product.

Density (g/cm<sup>3</sup>)
```

0.841 (20 °C) **Kinematic viscosity** No data available Particle characteristics Not applicable - product is a liquid Phase changes Melting point/Freezing point (°C) No data available Softening point/range (waxes and pastes) (°C) Does not apply to liquids. Boiling point (°C) 180 Vapour pressure No data available Relative vapour density No data available Decomposition temperature (°C) No data available Data on fire and explosion hazards Flash point (°C) >61 Auto-Ignition (°C) No data available Flammability (°C) No data available Lower and upper explosion limit (% v/v) No data available Solubility Solubility in water Insoluble n-octanol/water coefficient No data available Solubility in fat (q/L) No data available 9.2. Other information Evaporation rate (n-butylacetate = 100) No data available Other physical and chemical parameters No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product/substance Test method Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Test method OECD 401 Species Rat Route of exposure UDS0 Result >5000 mg/kg Other information Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Product/substance Test method Species Route of exposure Test Result	OECD 403 Rat Inhalation LC50 (4 hours)
Test method OECD 402 Species Rabbit Route of exposure Dermal Test LD50 Result >5000 mg/kg Other information Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Fest method Est method Species Rat Route of exposure Inhalation Test LC50 (dust) Result >5,53 mg/L Other information Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Test ESO (dust) Result >5,53 mg/L Other information Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Test ELD50 Result >5000 mg/kg Other information Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Test LD50 Result >5000 mg/kg Other information Species Species Rat Route of exposure Oral Test LD50 Result >5000 mg/kg Other information Cause	Test method Species Route of exposure Test Result	OECD 401 Rat Oral LD50
Test method Rat Species Rat Route of exposure Inhalation Test LC50 (dust) Result >5,53 mg/L Other information Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Test method Route of exposure Species Rabbit Route of exposure Dermal Test LD50 Result >5000 mg/kg Other information Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Product/substance Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Test method Species Species Rat Route of exposure Oral Test LD50 Result >5000 mg/kg Other information Social Skin corrosion/irritation. Secioas serious eye damage/irritation. Serious eye damage/irritation Causes serious eye damage. Respiratory sensitisation Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met.	Test method Species Route of exposure Test Result	OECD 402 Rabbit Dermal LD50
Test method Rabbit Route of exposure Dermal Test LD50 Result >5000 mg/kg Other information	Test method Species Route of exposure Test Result	Rat Inhalation LC50 (dust)
Test method Species Rat Route of exposure Oral Test LD50 Result >5000 mg/kg Other information Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation Causes serious eye damage. Respiratory sensitisation Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Germ cell mutagenicity	Test method Species Route of exposure Test Result	Rabbit Dermal LD50
Causes skin irritation. Serious eye damage/irritation Causes serious eye damage. Respiratory sensitisation Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met.	Test method Species Route of exposure Test Result	Rat Oral LD50
Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met.	Causes skin irritation. Serious eye damage/irrita	
	Based on available data Skin sensitisation Based on available data Germ cell mutagenicity	a, the classification criteria are not met.
Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure	Carcinogenicity Based on available data Reproductive toxicity Based on available data	a, the classification criteria are not met.

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Endocrine disrupting properties

None known.

Other information

None known.

SECTION 12: Ecological information

12.1. ▼Toxicity Product/substance Test method Species Compartment Duration Test Result Other information	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Daphnia, Daphnia magna 48 hours EL0 1000 mg/L
Product/substance Test method Species Compartment Duration Test Result Other information	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Fish, Oncorhynchus mykiss 96 hours LL0 1000 mg/L
Product/substance Test method Species Compartment Duration Test Result Other information	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Algae, Pseudokirchneriella subcapitata 72 hours EL0 1000 mg/L
Product/substance Test method Species Compartment Duration Test Result Other information	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Daphnia, Daphnia magna 48 hours EL50 >10000 mg/L
Product/substance Test method Species Compartment Duration Test Result Other information	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Fish 96 hours LL50 >100 mg/L
Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified

Test method	
Species	Algae
Compartment	
Duration	72 hours
Test	NOELR
Result	>100 mg/L
Other information	
Product/substance Test method	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified
Species	Daphnia, Daphnia magna
Compartment	Freshwater
Duration	21 days
Test	NOELR
Result	10 mg/L
Other information	i o mgr 2
12.2. ▼ Persistence and deg	gradability
Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Biodegradable	Yes
Test method	OECD 301 F
Result	>60%
Product/substance Biodegradable Test method Result	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified Yes
Product/substance Biodegradable Test method Result	Potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate Yes
Product/substance Biodegradable Test method Result	Distillates (petroleum), hydrotreated light;Kerosine - unspecified Yes OECD 301 F 61%, 28 days
12.3. ▼Bioaccumulative po Product/substance	otential Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified
Test method	
Potential bioaccumulation	Yes
LogPow	No data available.
BCF	<500
Other information	
 12.4. Mobility in soil No data available. 12.5. Results of PBT and vP This mixture/product do vPvB. 	VB assessment bes not contain any substances considered to meet the criteria classifying them as PBT and/or
12.6. Endocrine disrupting	properties
None known.	
12.7. Other adverse effects	
None known.	
NOTIE KTOWT.	
SECTION 13: Disposal cons	siderations
HP 4 - Irritant (skin irrita Regulation (EU) No 1357 EWC code	e regulations on hazardous waste. ition and eye damage) 7/2014 of 18 December 2014 on waste as retained and amended in UK law. els (including mixtures)

13 07 03* Other fuels (including mixtures)

Specific labelling Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatior
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
ΙΑΤΑ	-	-	-	-	-	-
** Env Addi N 14.6. N 14.7.	Special preco	nation s goods according to AD cautions for user ansport in bulk accordin				
SEC	TION 15: Reg	gulatory information				
R(D) S(S(15.2. N	estrictions fo Restricted t emands for s No specific EVESO - Categ Not applica dditional info Not applica ources The Manag Regulation Regulation retained an Regulation (REACH) as Chemical sa	ermation ible. ement of Health and Sa (EU) No 1357/2014 of 18 (EC) No 1272/2008 on cl ad amended in UK law. (EC) No 1907/2006 conc retained and amended ifety assessment	fety at Work Regula 3 December 2014 o assification, labellin erning the Registra	ations 1999. n waste as retained ng and packaging o	and amended in f substances and	ı UK law.
SEC	TION 16: Oth	ner information				
El H H H The f	JH066, Repe 304, May be 315, Causes 318, Causes full text of ide	ases as mentioned in sec ated exposure may caus fatal if swallowed and er skin irritation. serious eye damage. entified uses as mention petrol or diesel fuel d acronyms	se skin dryness or c nters airways. ned in section 1	racking.		

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CE = Conformité Européenne CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario EUH statement = CLP-specific Hazard statement EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer (IARC) IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SCL = A specific concentration limit SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVBC = Unknown or variable composition, complex reaction products or of biological materials VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Additional information The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law. ▼ The safety data sheet is validated by Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en