

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date	28th November 2022	Version	3.0
Revision date	10th June 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture MA PROFESSIONAL RUST CONVERTER + EPOXY
Number mixture
UFI M-10062025
XA60-84WA-EN4H-0FEU
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Corrosion inhibitor.
Main intended use
PC-PNT-1 Aerosol paints and coatings
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name AMTRA Sp. z o. o.
Address Schonów 3, Sosnowiec, 41-200
Poland
VAT Reg No PL6250009241
Phone +48 32 294 41 00
E-mail amtra@amtra.pl
Competent person responsible for the safety data sheet
Name AMTRA Sp. z o. o.
E-mail amtra@amtra.pl
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Asp. Tox. 1, H304
Skin Irrit. 2, H315
Skin Sens. 1, H317
Eye Irrit. 2, H319
STOT SE 3, H335, H336
STOT RE 2, H373

Most serious adverse physico-chemical effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

- 2.2. Label elements**
Hazard pictogram



Signal word

Danger

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date 28th November 2022

Revision date 10th June 2025

Version

3.0

Hazardous substances

acetone
propan-2-ol
reaction mass of ethylbenzene and xylene
Poly(Bisphenol A-co-epichlorohydrin) glycidyl end-capped

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P403 Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 Dispose of contents/container to according to applicable regulations.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8	dimethyl ether	25-<50	Press. Gas, Flam. Gas 1A, H220	2, 3
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2	acetone	10-<25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	3, 4, 5
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7	propan-2-ol	10-<25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date 28th November 2022

Revision date 10th June 2025

Version

3.0

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
EC: 905-588-0	reaction mass of ethylbenzene and xylene	10-<25	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412	
Index: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1	1-methoxy-2-propanol	2.5-<10	Flam. Liq. 3, H226 STOT SE 3, H336	3
CAS: 1401-55-4 EC: 215-753-2	Tannin	2.5-<10	Eye Irrit. 2, H319	
CAS: 25036-25-3 EC: 607-500-3	Poly(Bisphenol A-co-epichlorohydrin) glycidyl end-capped	1-<2.5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	
Index: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6	butan-1-ol	0.1-<1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	
Index: 603-108-00-1 CAS: 78-83-1 EC: 201-148-0	2-methylpropan-1-ol	0.1-<1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7	xylene	0.1-<1	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373	1, 3

Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)
Press. Gas (Liq.)
Press. Gas (Ref. Liq.)
Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

- A substance for which exposure limits are set.
- Explosive precursor
- Drug precursor

Full text of all classifications and hazard statements is given in the section 16.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date	28th November 2022	Version	3.0
Revision date	10th June 2025		

SECTION 4: First aid measures

4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Provide medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause respiratory irritation. May cause drowsiness or dizziness.

If on skin

May cause an allergic skin reaction.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Pressurised container: May burst if heated. Extremely flammable aerosol. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date 28th November 2022

Revision date 10th June 2025

Version

3.0

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not eat, drink or smoke when using this product. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Recommended storage temperature is from +5 °C to +30 °C. Protect against frost. Protect from sunlight. Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value
dimethyl ether (CAS: 115–10–6)	OEL 8 hours	1920 mg/m ³
	OEL 8 hours	1000 ppm
acetone (CAS: 67–64–1)	OEL 8 hours	1210 mg/m ³
	OEL 8 hours	500 ppm

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value
1-methoxy-2-propanol (CAS: 107–98–2)	OEL 8 hours	375 mg/m ³
	OEL 8 hours	100 ppm
	OEL 15 minutes	568 mg/m ³
	OEL 15 minutes	150 ppm
xylene (CAS: 1330–20–7)	OEL 8 hours	221 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	442 mg/m ³
	OEL 15 minutes	100 ppm

Notes

Skin.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date 28th November 2022

Revision date 10th June 2025

Version

3.0

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection



Protective goggles.

Skin protection



Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: Protective antistatic clothing made of natural fibres (cotton) or synthetic fibres resistant to elevated temperatures. Antistatic footwear. Contaminated skin should be washed thoroughly.

Glove material	Thickness	Breakthrough time	Class
Butyl rubber (IIR)	0.3 mm	>480 min	6

Respiratory protection



Respirator.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	brown
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not determined
Flammability	flammable
Lower and upper explosion limit	
bottom	1.1 %
upper	20 %
Flash point	not determined
Auto-ignition temperature	235 °C
Decomposition temperature	not determined
pH	2.5 (undiluted)
Kinematic viscosity	>20 mm ² /s at 40 °C
Solubility in water	soluble

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date	28th November 2022	Version	3.0
Revision date	10th June 2025		

Partition coefficient n-octanol/water (log value)	not determined
Vapour pressure	3300 hPa
Density and/or relative density	
Density	0.794 g/cm ³
Relative vapour density	not determined
Particle characteristics	not determined

9.2. Other information

not available

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met. Data for the components of the mixture are not available.

MA PROFESSIONAL RUST CONVERTER + EPOXY						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	Value determination
Dermal	ATE	4400 mg/kg				Calculation of value
Inhalation (dust/mist)	ATE	>6 mg/l				Calculation of value

Skin corrosion/irritation

Causes skin irritation. Data for the components of the mixture are not available.

Serious eye damage/irritation

Causes serious eye irritation. Data for the components of the mixture are not available.

Respiratory or skin sensitisation

May cause an allergic skin reaction. Data for the components of the mixture are not available.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date 28th November 2022

Revision date 10th June 2025

Version

3.0

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness. Data for the components of the mixture are not available.

Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure. Data for the components of the mixture are not available.

Aspiration hazard

May be fatal if swallowed and enters airways. Data for the components of the mixture are not available.

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date	28th November 2022		
Revision date	10th June 2025	Version	3.0

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended.
Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1



Road transport - ADR

Special provisions

190, 327, 344, 625

Limited quantities

1 L

Excepted quantities

E0

Packaging

Packing instructions

P207, LP200

Special packing provisions

PP87, RR6, L2

Mixed packing provisions

MP9

Transport category

2

Tunnel restriction code

(D)

Special provision for

packages

V14

loading, unloading and handling

CV9, CV12

operation

S2

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date	28th November 2022	Version	3.0
Revision date	10th June 2025		

Railway transport - RID

Special provisions	190, 327, 344, 625
Excepted quantities	E0

Packaging

Packing instructions	P207, LP200
Special packing provisions	PP87, RR6, L2
Mixed packing provisions	MP9
Transport category	0

Special provision for

packages	W14
loading, unloading and handling	CW9, CW12

Air transport - ICAO/IATA

Packaging instructions for limited amount	Y203
Packaging instructions passenger	203
Cargo packaging instructions	203

Marine transport - IMDG

EmS (emergency plan)	F-D, S-U
MFAG	620

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P102	Keep out of reach of children.
------	--------------------------------

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date	28th November 2022	Version	3.0
Revision date	10th June 2025		

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403	Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501	Dispose of contents/container to according to applicable regulations.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aerosol	Aerosol
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
log Kow	Octanol-water partition coefficient
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
Press. Gas (Comp.)	Gas under pressure: compressed gas
Press. Gas (Diss.)	Gas under pressure: dissolved gas
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.)	Gas under pressure: refrigerated liquefied gas
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL RUST CONVERTER + EPOXY

Creation date	28th November 2022	Version	3.0
Revision date	10th June 2025		

RID	Agreement on the transport of dangerous goods by rail
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from Wednesday, 8 January 2025. Changes were made in sections 1, 2, 3 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.