



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Product code : 892410

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global
Operations
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person : SDS@valvolineglobal.com
responsible for the SDS

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Long-term (chronic) aquatic hazard,
Category 3

H412: Harmful to aquatic life with long lasting
effects.



SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
 Valvoline™ HYBRID VEHICLE C5 0W20
 Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
 P273 Avoid release to the environment.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 70 - < 80
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- xxxx	Asp. Tox. 1; H304	>= 2.5 - < 5
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8 265-158-7 649-468-00-3	Asp. Tox. 1; H304	>= 1 - < 2.5



ValvolineTM
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
ValvolineTM HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

	01-2119487077-29-xxxx		
PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8 283-392-8 01-2119493626-26-xxxx	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 6.25 % Eye Dam. 1; H318 >= 12.5 % Eye Irrit. 2; H319 >= 10.0 %	>= 1 - < 2.5
Branched alkylphenol and Calcium branched alkylphenol	74499-35-7 604-092-00-9	Skin Corr. 1C; H314 Eye Dam. 1; H318 Repr. 1B; H360F Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 0.025 - < 0.1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

- If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : carbon dioxide and carbon monoxide
Nitrogen oxides (NOx)

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : neoprene, nitrile rubber
Break through time : ≥ 240 min
Glove thickness : ≥ 0.35 mm
Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: oily
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: ca. 204 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0.8438 g/cm ³ (15.6 °C)
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 44.4 mm²/s (40 °C)
Method: ASTM D 445

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents
strong reducing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: The toxicological data has been taken from products of similar composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit
Result : Mild skin irritation
Remarks : The toxicological data has been taken from products of similar composition.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit
Result : Irritating to skin.

Branched alkylphenol and Calcium branched alkylphenol:

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : May cause irreversible eye damage.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation
Result : No eye irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species	:	Rabbit
Result	:	Slight, transient irritation
Remarks	:	The toxicological data has been taken from products of similar composition.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment	:	Slight, transient irritation
Result	:	Slight, transient irritation

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species	:	Rabbit
Result	:	Corrosive

Branched alkylphenol and Calcium branched alkylphenol:

Result	:	Irritating to eyes.
--------	---	---------------------

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Remarks	:	The toxicological data has been taken from products of similar composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: **Ames test**
Test system: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Genotoxicity in vitro : Test Type: **Ames test**
Test system: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

Reproductive toxicity

Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Components:

Branched alkylphenol and Calcium branched alkylphenol:

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

|| May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

|| May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

|| May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Chronic aquatic toxicity : Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 10 mg/l Species: Aquatic invertebrates

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Toxicity to algae/aquatic plants : **EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l**
End point: **Growth inhibition**
Exposure time: **72 h**
Test Type: **static test**

Ecotoxicology Assessment

Acute aquatic toxicity : **Not classified based on available information.**
Chronic aquatic toxicity : **Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.**

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment

Acute aquatic toxicity : **Not classified based on available information.**
Chronic aquatic toxicity : **Not classified based on available information.**

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : **NOEC: 0.4 mg/l**
End point: **Reproduction Test**
Exposure time: **28 d**
Species: **Daphnia magna (Water flea)**
Test substance: **WAF**
Method: **OECD Test Guideline 211**

Ecotoxicology Assessment

Acute aquatic toxicity : **Not classified based on available information.**
Chronic aquatic toxicity : **Not classified based on available information.**

Branched alkylphenol and Calcium branched alkylphenol:

M-Factor (Acute aquatic toxicity) : **10**
M-Factor (Chronic aquatic toxicity) : **10**

Ecotoxicology Assessment

Acute aquatic toxicity : **Very toxic to aquatic life.**
Acute aquatic toxicity Category 1; Very toxic to aquatic life.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Chronic aquatic toxicity : **Very toxic to aquatic life with long lasting effects.**
Chronic aquatic toxicity Category 1; Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **0 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **1.5 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n-octanol/water : log Pow: **> 7.5**

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Partition coefficient: n-octanol/water : log Pow: **0.56**

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

Components:

Branched alkylphenol and Calcium branched alkylphenol:

Endocrine disrupting potential : The substance is considered to have endocrine disrupting properties according to REACH Article 57(f) for the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:



ValvolineTM
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
ValvolineTM HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable	Number on list 3
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable	
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable	
UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable	
Control of Major Accident Hazards Regulations 2015 (COMAH)	Not applicable	

The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AiIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AiIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.



ValvolineTM
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ValvolineTM HYBRID VEHICLE C5 0W20

Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H360F	:	May damage fertility.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic



ValvolineTM
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
ValvolineTM HYBRID VEHICLE C5 0W20
Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 28/05/2025

Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000277161

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN