



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

TECPO Motoröl 5W-30 LONGLIFE Plus 504/507_EN

Article No.

300200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Engine oil.

PC24 - Lubricants, greases, release products.

Not suitable for use in

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

SDS created by

Gefahrgutberatung Florian Herber, Erbigsweg 12, 36137 Großenlütder

Telefon: 0163 / 8408334

E-Mail: kontakt@gefahrgut-herber.de

www.gefahrgut-herber.de



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

Supplier

TECPO GmbH

Address

Dreherstraße 16-20

42899 Remscheid

Germany

Telephone

+49 2191 951 3305

Email

info@tecpo.de

Fax

+49 2191 951 33044

Web site

www.tecpo.de

Contact person

Baris Ünsal

1.4. Emergency telephone number

Poison center/Additional emergency number

+49 (0) 89 19240 - Poison Emergency Call Munich

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Description

This mixture is not classified as dangerous according to Regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Supplemental hazard statements

EUH210 Safety data sheet available on request.

2.3. Other hazards

Do not handle until all safety precautions have been read and understood.

Release into the environment must be avoided.



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0
Issued: 2025-06-10

Other

This product does not contain any PBT or vPvB substances.

The product does not contain any substances with endocrine-disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Specific concentration limits	Note
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25 649-467-00-8	55 - <60%	Asp. Tox. 1	H304 - -	-	inhalative: LC50 = >5,53 mg/l; dermal: LD50 = >5000 mg/kg; oral: LD50 =>5000 mg/kg
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0 274-263-7 01-2119492616-28-XXXX -	0 - <0,25%	Skin Sens. 1B	H317 - -	Skin Sens. 1B, H317: 10% ≤ C ≤ 100%	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg
Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts	148520-84-7 800-941-4 - -	0 - <0,25%	Skin Sens. 1B	H317 - -	Skin Sens. 1B, H317: 10% ≤ C ≤ 100%	-
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	68784-26-9 701-251-5 01-2119524004-56 -	0 - <0,25%	Repr. 1B, Aquatic Chronic 4	H360, H413 - -	-	inhalative: LC50 = >1,67 mg/l; dermal: LD50 = >4000 mg/kg; oral: LD50 = >5000 mg/kg

Substance additional information

Contains:

Base oil , Additive

The mineral oils in this product contain < 3 % DMSO extract (IP 346).

For the complete text of H- / EUH-statements mentioned in this section, see section 16.



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

SECTION 4: First aid measures

4.1. Description of first aid measures

First aiders should pay attention to self-protection. Remove the affected person from the danger zone and lay them down. Remove soiled, soaked clothing immediately. In case of accident or if you feel unwell, seek medical advice immediately. Show safety data sheet if possible.

Inhalation

Avoid the formation of oil mist. Take the affected person out into the fresh air and keep them warm and calm. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Skin contact

Take off immediately all contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur or persist, consult an ophthalmologist.

Ingestion

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or if convulsions occur. Consult a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

There is no information available. If symptoms occur or in case of doubt, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Sand , Water spray jet, carbon dioxide (CO₂), foam, extinguishing powder.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Carbon dioxide (CO₂). Phosporoxides Sulphur oxides Carbon monoxide (CO).



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Do not inhale explosion and combustion gases. If safe to do so, remove undamaged containers from the danger zone. In case of fire: Use self-contained breathing apparatus.

Other

Measures in case of fire

Cool endangered containers with water spray. Collect contaminated extinguishing water separately and do not allow it to enter the sewage system. Do not allow to enter drains or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Respiratory protection is required for: Aerosol or mist formation. (See section 8.) Avoid contact with eyes and skin. Use suitable personal protective equipment (see SECTION 8). Keep ignition sources away. In case of gas leakage or ingress into water, soil or sewage system, inform the responsible authorities.

6.2. Environmental precautions

Do not allow to enter drains or waterways.
Do not allow to enter the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Prevent the spill from spreading (e.g. by containing it with oil booms).
Pick up mechanically and dispose of in suitable containers.
Remove from the water surface (e.g. vacuum).
In case of spills, beware of slippery floors and surfaces.
Absorb with liquid-binding material (sand, diatomaceous earth, acid binder, universal binder).
Dispose of the collected material in accordance with the regulations (Section 13).

6.4. Reference to other sections

See SECTIONS 7+8+13



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions

Instructions for safe handling:

Do not inhale vapors/aerosols. Ensure adequate ventilation.

Avoid contact with eyes and skin.

Remove soiled, soaked clothing immediately.

For industrial use only.

Notes on fire and explosion protection:

No specific precautions.

Avoid the formation of oil mist. Hot product develops flammable vapors.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Fire class B (DIN EN 2).

General hygiene

Do not eat, drink, smoke or take snuff at the workplace.

Avoid contact with skin, eyes and clothing.

Preventive skin protection with skin protection ointment.

Remove soiled, soaked clothing immediately.

Wash contaminated clothing before reuse.

Wash hands before breaks and at the end of work.

Use oily skin care products after cleansing.

Do not carry product-soaked cleaning cloths in your trouser pockets.

7.2. Conditions for safe storage, including any incompatibilities

Store container in a cool, well-ventilated place.

Only use containers that are specifically approved for the product.

Always close the container tightly after removing the product.

Recommended storage temperature: 5 - 30 °C

Do not store at temperatures above: 40 °C

Protect against: Heat, light, moisture. Protect against direct sunlight.

Storage instructions:

Do not store together with oxidizing agents.

Do not store together with self-igniting substances.

Keep away from food, drink and animal feeding stuffs.

Storage class according to TRGS 510: 10 - Flammable liquids that cannot be assigned to any of the aforementioned LGKs

7.3. Specific end use(s)

Engine oil.



TECPO Motoröl 5W-30 LONGLIFE Plus

504/507_EN

Version number: 1.0
Issued: 2025-06-10

Other

Observe the technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

Air limit values: Mineral oil mist

Limit value type (country of origin): US-OSHA PEL value: 5 mg/m³

Limit value type (country of origin): ACGIH STEL value: 10 mg/m³

DNEL/DMEL

Product/Substance name (CAS No./EC No.)	Type	Exposure	Value	Population	Effects
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7/265-157-1)	DNEL	Chronic (long term) Dermal	0,97 mg/kg bw/day	Workers	Systemic
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7/265-157-1)	DNEL	Chronic (long term) Inhalation	2,73 mg/m ³	Workers	Systemic
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7/265-157-1)	DNEL	Chronic (long term) Inhalation	5,58 mg/m ³	Workers	Local
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0/274-263-7)	DNEL	Chronic (long term) Inhalation	11,75 mg/m ³	Workers	Systemic
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0/274-263-7)	DNEL	Chronic (long term) Dermal	3,33 mg/kg bw/day	Workers	Systemic

PNEC/PEC

Product/Substance name (CAS No./EC No.)	Type	Environmental compartment	Value
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7/265-157-1)	PNEC	Oral (Secondary Poisoning)	9,33 mg/kg food
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	PNEC	Freshwater	1 mg/l



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0
Issued: 2025-06-10

Product/Substance name (CAS No./EC No.)	Type	Environmental compartment	Value
(70024-69-0/274-263-7)			
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0/274-263-7)	PNEC	Intermittent releases (freshwater)	10 mg/l
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0/274-263-7)	PNEC	Marine water	1 mg/l
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0/274-263-7)	PNEC	Oral (Secondary Poisoning)	16,667 mg/l
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0/274-263-7)	PNEC	Sewage Treatment Plant	1000 mg/l

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Personal Protective Equipment Symbols



Eye / face protection

Tightly sealed safety goggles. (EN 166)

Hand protection

Handling large quantities: Tested protective gloves must be worn: DIN/EN standards: DIN EN 420, EN ISO 374.

Suitable material: NBR (nitrile rubber), PVC (polyvinyl chloride), CR (polychloroprene, chloroprene rubber).

Required properties: liquid tight.

Penetration time of the glove material: > 240 min

Glove material thickness: 0.4 mm EN ISO 374

Check for leaks / impermeability before use.

Other skin protection

Wear suitable protective clothing when working.



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

Respiratory protection

When used properly and under normal conditions, respiratory protection is not required.

Respiratory protection is required if: Exceeding limit values, insufficient ventilation. Aerosol or mist formation.

Suitable breathing apparatus: A2/P2 combination filter device (DIN EN 141).

Filter types: A, B, E, K. Do not use small filters (filter class 1)! Class 2: Maximum permissible

Pollutant concentration in the breathing air = 5000 ml/m³ (0.5% by volume); Class 3 = 10000 ml/m³ (1.0% by volume).

Environmental exposure controls

Ensure that leaks can be collected (e.g. collecting trays or collecting surfaces).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Yellow.

Odour

Characteristic.

Melting point / freezing point

No data available.

Boiling point or initial boiling point and boiling range

No data available.

Flammability

No data available

Lower and upper explosion limit

No data available.

Flash point

242 °C

Method

DIN ISO 2592

Auto-ignition temperature

No data available.



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

Decomposition temperature

No data available.

pH

Not applicable.

Kinematic viscosity

70 mm²/s

Method

DIN 51562

Viscosity, dynamic

No data available.

Solubility

No data available

Water solubility

insoluble

Partition coefficient n-octanol/water

No data available.

Vapour pressure

< 0,1 hPa

Method

@ 20 °C

Density and/or relative density

0,84 - 0,85 g/cm³

Method

DIN 51757

Relative vapour density

No data available.

Explosive properties

Based on available data, the classification criteria are not met.

Oxidising properties

Based on available data, the classification criteria are not met.

VOC %

0 %

Particle characteristics

No data available



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

9.2. Other information

Pourpoint: <-30 °C DIN ISO 3016

SECTION 10: Stability and reactivity

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

Do not mix with: Strong oxidising agents.

10.4. Conditions to avoid

Do not store at temperatures above: 40 °C

This material is combustible but not highly flammable.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous decomposition products

Thermal decomposition may lead to release of irritating gases and vapors.

In the event of fire, the following may occur: Carbon dioxide (CO₂). Phosphoroxides Sulphur oxides

Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapor) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Acute toxicity

Based on available data, the classification criteria are not met.



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0
Issued: 2025-06-10

Product / Sub- stance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline
Distillates (petro- leum), hydro- treated heavy paraffinic 64742-54-7 / 265-157-1	LD50	> 5000 mg/kg	Oral	-	Rat	OECD 401
Distillates (petro- leum), hydro- treated heavy paraffinic 64742-54-7 / 265-157-1	LD50	> 5000 mg/kg	Dermal	-	Rabbit	OECD 402
Distillates (petro- leum), hydro- treated heavy paraffinic 64742-54-7 / 265-157-1	LC50	>5,53 mg/l	Inhalative	4 hours	Rat	OECD 403
Benzenesulfonic acid, mono-C16- 24-alkyl derivs., calcium salts 70024-69-0 / 274-263-7	LD50	>2000 mg/kg	Dermal	-	Rat	OECD 402
Benzenesulfonic acid, mono-C16- 24-alkyl derivs., calcium salts 70024-69-0 / 274-263-7	LD50	>5000 mg/kg	Oral	-	Rat	OECD 401
Phenol, dodecyl- , sulfurized, car- bonates, calcium salts, overbased 68784-26-9 / 701-251-5	LD50	>5000 mg/kg	Oral	-	Rat	OECD 401
Phenol, dodecyl- , sulfurized, car- bonates, calcium salts, overbased 68784-26-9 / 701-251-5	LD50	>4000 mg/kg	Dermal	-	Rabbit	OECD 402
Phenol, dodecyl-	LC50	>1,67 mg/l	Inhalative	1 hour	Rat	OECD 403



**TECPO Motoröl 5W-
30 LONGLIFE Plus
504/507_EN**

Version number: 1.0
Issued: 2025-06-10

Product / Sub- stance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline
, sulfurized, car- bonates, calcium salts, overbased 68784-26-9 / 701-251-5						

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.
The mineral oils in this product contain < 3 % DMSO extract (IP 346).

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Prolonged or repeated skin contact can have a degreasing effect and lead to dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain any substance that exhibits endocrine disrupting properties towards humans, as no ingredient meets the criteria.



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0
Issued: 2025-06-10

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Based on available data, the classification criteria are not met.

Acute fish toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
Distillates (petro- leum), hydrotreated heavy paraffinic 64742-54-7 / 265- 157-1	LL50	>100 mg/l	96 hours	Pimephales pro- melas (Fat-head Minnow)	OECD 203
Distillates (petro- leum), hydrotreated heavy paraffinic 64742-54-7 / 265- 157-1	NOEC	>100 mg/l	4 days	Pimephales pro- melas (Fat-head Minnow)	OECD 203
Benzenesulfonic acid, mono-C16-24- alkyl derivs., cal- cium salts 70024-69-0 / 274- 263-7	LL50	>10000 mg/l	96 hours	Cyprinodon varie- gatus (Sheepshead minnow)	OECD 203
Phenol, dodecyl-, sulfurized, carbon- ates, calcium salts, overbased 68784-26-9 / 701- 251-5	LL50	>1000 mg/l	96 hours	Pimephales pro- melas (Fat-head Minnow)	OECD 203

Acute algae toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
Benzenesulfonic acid, mono-C16-24- alkyl derivs., cal- cium salts 70024-69-0 / 274-	ErC50	1000 mg/l	72 hours	algae	-



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0
Issued: 2025-06-10

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
263-7					
Distillates (petro- leum), hydrotreated heavy paraffinic 64742-54-7 / 265- 157-1	ErC50	>100 mg/l	72 hours	Pseudokirchneriella subcapitata	OECD 201
Distillates (petro- leum), hydrotreated heavy paraffinic 64742-54-7 / 265- 157-1	NOEC	>100 mg/l	72 hours	Pseudokirchneriella subcapitata	OECD 201

Acute crustacean toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
Benzenesulfonic acid, mono-C16-24- alkyl derivs., cal- cium salts 70024-69-0 / 274- 263-7	EL50	>10000 mg/l	48 hours	Daphnia magna	EPA OTS 797.1300
Phenol, dodecyl-, sulfurized, carbon- ates, calcium salts, overbased 68784-26-9 / 701- 251-5	EC50	>1000 mg/l	48 hours	Daphnia magna	OECD 202
Distillates (petro- leum), hydrotreated heavy paraffinic 64742-54-7 / 265- 157-1	NOEC	1000 mg/l	4 days	Daphnia magna	OECD 202
Distillates (petro- leum), hydrotreated heavy paraffinic 64742-54-7 / 265- 157-1	EC50	>1000 mg/l	48 hours	Daphnia magna	OECD 202

12.2. Persistence and degradability

Not readily biodegradable



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

Product / Substance name CAS / EC no.	Duration	Result	Method / Guideline
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts 70024-69-0 / 274-263-7	28 days	8 % Not readily biodegradable	OECD 301D
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased 68784-26-9 / 701-251-5	28 days	13,4 % Not readily biodegradable	OECD 301B

12.3. Bioaccumulative potential

There is no information available.

Product / Substance name CAS / EC no.	LogKow / LogPow
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts 70024-69-0 / 274-263-7	22,12

12.4. Mobility in soil

Mobility

Physical state: liquid at room temperature.

If the product penetrates the soil, it is mobile and can contaminate the groundwater.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not fulfill the PBT/vPvB criteria according to REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain any substance that exhibits endocrine disrupting properties towards non-target organisms, as no ingredient fulfills the criteria.

12.7. Other adverse effects

There is no information available.

Other

Avoid release to the environment.

Do not allow to enter drains or waterways.

Do not allow to enter the subsoil/soil.

German Water Class

WGK1 - slightly water endangering



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0
Issued: 2025-06-10

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal considerations

Do not discharge into drains, water courses or onto the ground. Disposal in accordance with official regulations. The mentioned waste codes are recommendations based on the expected use of the product. Contact the responsible authorized waste disposal company for waste disposal. Observe mixing prohibitions according to the Waste Oil Ordinance.

Packaging

Contaminated packaging must be emptied without dripping and can then be recycled after appropriate cleaning. Packaging that cannot be cleaned must be disposed of.

Waste code	Waste description
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Please note - an asterisk (*) next to a code denotes that it is HAZARDOUS WASTE.

SECTION 14: Transport information

14.1. UN number

No dangerous goods in the sense of these transport regulations.

14.2. UN proper shipping name

ADR / RID / ADN proper shipping name

No dangerous goods in the sense of these transport regulations.

14.3. Transport hazard class(es)

Label

No dangerous goods in the sense of these transport regulations.

ADR / RID Class

No dangerous goods in the sense of these transport regulations.

ADR / RID Classification code

No dangerous goods in the sense of these transport regulations.

ADR / RID hazard identification number

No dangerous goods in the sense of these transport regulations.

IMDG Class

No dangerous goods in the sense of these transport regulations.



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

14.4. Packing group

No dangerous goods in the sense of these transport regulations.

14.5. Environmental hazards

No.

IMDG Marine Pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

There is no information available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Information on the SEVESO III Directive 2012/18/EU: Not subject to the SEVESO III Directive

Additional information:

For professional users only.

The recipient of our products is responsible for observing existing laws and regulations.

The national legal regulations must also be observed!

This oil should be taken to a waste oil collection point after use! Improper disposal of waste oil endangers the environment!

Any admixture of foreign substances such as solvents, brake fluids and coolants is prohibited.

National regulations

Water hazard class (WGK): 1, slightly hazardous to water.

Storage class: 10 - Flammable liquids that cannot be assigned to any of the aforementioned LGKs

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.



TECPO Motoröl 5W- 30 LONGLIFE Plus 504/507_EN

Version number: 1.0

Issued: 2025-06-10

SECTION 16: Other information

Phrase meaning

Asp. Tox. 1 - Aspiration hazard, hazard category 1

Skin Sens. 1B - Skin sensitisation, hazard category 1, sub-category 1B

Repr. 1B - Reproductive toxicity, hazard category 1B

Aquatic Chronic 4 - Hazardous to the aquatic environment — Chronic hazard category 4

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H413 May cause long lasting harmful effects to aquatic life.

EUH210 Safety data sheet available on request.

Other

Additional information

The information is based on our current state of knowledge, but does not constitute a guarantee of product properties and does not establish a contractual legal relationship. The recipient of our products is responsible for observing existing laws and regulations. The information in this safety data sheet corresponds to the best of our knowledge at the time of printing. The information is intended to provide you with guidelines for the safe handling of the product mentioned in this safety data sheet during storage, processing, transportation and disposal. The information is not transferable to other products. If the product is mixed, blended or processed with other materials processed or subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise.

Manufacturer's notes

The data of the relevant components were taken from the latest safety data sheet of the upstream supplier.