



TECPO Weisses Fettspray_EN

Version number: 1.0
Issued: 2024-10-24

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

TECPO Weisses Fettspray_EN

Article No.

300563

UFI code

JPDU-0UVX-V00K-RNNM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Lubricant.

Not suitable for use in

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Supplier

TECPO GmbH

Address

Dreherstraße 16-20

42899 Remscheid

Germany

Telephone

+49 2191 951 3305

Email

info@tecpo.de

Fax

+49 2191 951 33044

Web site

www.tecpo.de

1.4. Emergency telephone number

Poison center/Additional emergency number

+49 (0) 89 19240 - Poison Emergency Call Munich

TECPO Weisses Fettspray_EN

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Classification

Aerosol, Hazard category 1

Aspiration hazard, hazard category 1

Skin irritation, hazard category 2

Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis

Hazardous to the aquatic environment — Chronic hazard category 2

Hazard statements

H222, H229, H304, H315, H336, H411

Description

The product is classified and labeled according to the CLP regulation.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Supplemental hazard statements

EUH208 Contains Napthenic acids, zinc salts. May produce an allergic reaction.

TECPO Weisses Fettspray_EN

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing aerosol.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of water/.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P304 + P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container to dispose of in accordance with local / regional / national / international regulations.

More information

Hazard-determining components of labeling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane

2.3. Other hazards

In case of insufficient ventilation and/or due to use, formation of explosive/highly flammable mixtures possible. mixtures possible.

Other

This product does not contain any PBT or vPvB substances.

The product does not contain any substances with endocrine-disrupting properties.

TECPO Weisses Fettspray_EN

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Note
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane	64742-49-0 921-024-6 01-2119475514-35 -	25 - <50%	Flam. Liq. 2, Asp. Tox. 1, Skin Irrit. 2, STOT SE 3 - narcosis, Aquatic Chronic 2	H225, H304, H315, H336, H411 - -	inhalative: LC50 = > 25,2 mg/l; dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = >5000 mg/kg
isobutane	75-28-5 200-857-2 01-2119485395-27 601-004-00-0	25 - <50%	Flam. Gas 1, Press. Gas - Liquefied gas	H220, H280 - -	-
propane	74-98-6 200-827-9 01-2119486944-21 601-003-00-5	5 - <10%	Flam. Gas 1, Press. Gas - Liquefied gas	H220, H280 - -	-
butane	106-97-8 203-448-7 01-2119474691-32 601-004-00-0	1 - <3%	Flam. Gas 1, Press. Gas - Liquefied gas	H220, H280 - -	inhalative: LC50 = 658 ppm (gas)
Naphthenic acids, zinc salts	12001-85-3 234-409-2 01-2120783834-41 -	0 - <0,1%	Skin Sens. 1B, Eye Irrit. 2, Aquatic Chronic 2	H317, H319, H411 - -	oral: LD50 = > 2000 mg/kg

Substance additional information

For the complete text of H- / EUH-statements mentioned in this section, see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

First aiders should pay attention to self-protection. Bring people to safety. Never give anything by mouth to an unconscious person or if convulsions occur.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If symptoms occur or in case of doubt, seek medical advice.

TECPO Weisses Fettspray_EN

Skin contact

Wash off immediately with soap and water and rinse thoroughly. Take off immediately all contaminated clothing and wash it before reuse. If symptoms occur or in case of doubt, seek medical advice.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur or persist, consult an ophthalmologist.

Ingestion

Do NOT induce vomiting. In case of vomiting, note the risk of aspiration. Always consult a doctor!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment. Call a POISON CENTER. Symptoms may not appear until many hours after exposure.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Do not inhale explosion and combustion gases. If safe to do so, remove undamaged containers from the danger zone. In case of fire: Use self-contained breathing apparatus.

Other

Risk of the container bursting.

TECPO Weisses Fettspray_EN

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Respiratory protection must be used when exposed to vapors, dusts and aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment.

Staff not trained for emergencies:
First aiders should pay attention to self-protection.

Emergency services:
Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter drains/surface water/ground water. Prevent the spill from spreading (e.g. by containing it with oil booms). Ensure that all wastewater is collected and treated in a wastewater treatment plant.

6.3. Methods and material for containment and cleaning up

Prevent the spill from spreading (e.g. by containing it with oil booms).
Thoroughly clean soiled objects and floors in compliance with environmental regulations.
Absorb with liquid-binding material (sand, diatomaceous earth, acid binder, universal binder). Thoroughly clean soiled objects and floors in compliance with environmental regulations.

6.4. Reference to other sections

See SECTIONS 7+8+13

TECPO Weisses Fettspray_EN

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions

Follow the instructions for use. Dust must be safely extracted directly at the point of origin. Vapors/aerosols must be safely extracted directly at the point of origin. If local extraction is not possible or insufficient, good ventilation of the work area should be ensured wherever possible. Do not eat, drink, smoke or sniff at the workplace. Wear personal protective equipment (see section 8). Formation of explosive/highly flammable mixtures possible with insufficient ventilation and/or through use.

Notes on fire and explosion protection:

Keep away from sources of ignition - No smoking. Heating leads to an increase in pressure and risk of bursting.

Information on general hygiene measures at the workplace:

Avoid exposure. Wear suitable protective clothing when working. Draw up and observe a skin protection plan!

Further information on handling:

Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and containers:

Keep containers tightly closed. Observe legal rules and regulations.

Storage instructions:

Do not store together with: Oxidizing agents. Pyrophoric or self-heating hazardous substances. Food and animal feed.

Further information on storage conditions:

Protect from frost. Protect from direct sunlight. Store in a cool and dry place. Observe legal rules and regulations.

Storage class according to TRGS 510: 2B Compressed gas packs (aerosol dispensers)

7.3. Specific end use(s)

Lubricant.



TECPO Weisses Fettspray_EN

Version number: 1.0
Issued: 2024-10-24

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure limits

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³	Source	Remark	Year
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane	64742-49-0 921-024-6	- 700	TRGS 900	2(II)	-
isobutane	75-28-5 200-857-2	1000 2400	TRGS 900	4(II)	-
propane	74-98-6 200-827-9	1000 1800	TRGS 900	4 (II)	-
butane	106-97-8 203-448-7	1000 2400	TRGS 900	4(II)	-

DNEL/DMEL

Product/Substance name (CAS No./EC No.)	Type	Exposure	Value	Population	Effects
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane (64742-49-0/921-024-6)	DNEL	Chronic (long term) Oral	699 mg/kg bw/day	Consumers	Systemic
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane (64742-49-0/921-024-6)	DNEL	Chronic (long term) Dermal	773 mg/kg bw/day	Workers	Systemic
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane (64742-49-0/921-024-6)	DNEL	Chronic (long term) Dermal	699 mg/kg bw/day	Consumers	Systemic
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane (64742-49-0/921-024-6)	DNEL	Chronic (long term) Inhalation	2035 mg/m ³	Workers	Systemic
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane (64742-49-0/921-024-6)	DNEL	Chronic (long term) Inhalation	608 mg/m ³	Consumers	Systemic
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	DNEL	Chronic (long term) Inhalation	1,18 mg/m ³	Workers	Systemic
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	DNEL	Chronic (long term) Dermal	3,3 mg/kg bw/day	Workers	Systemic
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	DNEL	Chronic (long term) Inhalation	0,29 mg/m ³	Consumers	Systemic
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	DNEL	Chronic (long term) Dermal	1,7 mg/kg bw/day	Consumers	Systemic

TECPO Weisses Fettspray_EN

PNEC/PEC

Product/Substance name (CAS No./EC No.)	Type	Environmental compartment	Value
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	PNEC	Freshwater	0,004 mg/l
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	PNEC	Intermittent releases (freshwater)	0,04 mg/l
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	PNEC	Marine water	0 mg/l
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	PNEC	Sediment (freshwater)	0,015 mg/kg
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	PNEC	Sediment (marine water)	0,002 mg/kg
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	PNEC	Sewage Treatment Plant	0,6897 mg/l
Naphthenic acids, zinc salts (12001-85-3/234-409-2)	PNEC	Soil	0,001 mg/kg

8.2. Exposure controls

Appropriate engineering controls

For open handling, use devices with local exhaust ventilation.

Personal Protective Equipment Symbols



Eye / face protection

Tightly sealed safety goggles DIN EN 166

Hand protection

Preventive skin protection with skin protection ointment. When handling chemical substances, only chemical protective gloves with a CE mark including a four-digit test number may be worn. The design of chemical protective gloves must be selected specifically for the workplace depending on the concentration and quantity of hazardous substances.

Suitable material: NBR (nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0.45 mm

EN ISO 374

Other skin protection

Wear suitable protective clothing when working. Take off immediately all contaminated clothing and wash it before reuse.

TECPO Weisses Fettspray_EN

Respiratory protection

Respiratory protection must be used when exposed to vapors, dusts and aerosols. If the relevant occupational exposure limit values are exceeded, the following must be observed: Suitable breathing apparatus: Combination filter apparatus (DIN EN 141).

Filter unit with filter or blower filter unit type: AX

The wearing time limits specified by the manufacturer must be observed.

Observe legal rules and regulations.

Environmental exposure controls

Observe legal rules and regulations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

Beige.

Odour

Characteristic.

Odour threshold

Not determined.

Melting point / freezing point

Not determined.

Boiling point or initial boiling point and boiling range

-42 °C

Flammability

Not determined.

Lower and upper explosion limit

Untere: 1 Vol-%; Obere: 9,4 Vol-%

Flash point

-80 °C

Auto-ignition temperature

Not determined.

Decomposition temperature

Not determined.

TECPO Weisses Fettspray_EN

pH

No data available

Kinematic viscosity

Not determined.

Solubility

Not determined.

Water solubility

Slightly soluble in water.

Partition coefficient n-octanol/water

Not determined.

Vapour pressure

Not determined.

Density and/or relative density

0,72 g/cm³

Method

@ 20 °C

Relative vapour density

Not determined.

Particle characteristics

Not applicable.

9.2. Other information

Heating may cause an explosion.

The product is not: Oxidizing.

Other

The data refer to the technical active substance: relative density, color, odor, viscosity, pH value.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating leads to an increase in pressure and risk of bursting.

TECPO Weisses

Fettspray_EN

10.4. Conditions to avoid

Keep away from heat, sparks and open flame. Vapors can form an explosive mixture with air. Take measures against electrostatic charging.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating hazardous substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Other

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ATEmix calculated
ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapor) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Acute toxicity

Based on available data, the classification criteria are not met.

Product / Substance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline	Remarks
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane 64742-49-0 / 921-024-6	LD50	>5000 mg/kg	Oral	-	Rat	-	-
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane 64742-49-0 / 921-024-6	LD50	>2800 - 3100 mg/kg	Dermal	-	Rat	-	-
Hydrocarbons	LC50	>25,2 mg/l	Inhalative	4 hours	Rat	-	-



TECPO Weisses Fettspray_EN

Version number: 1.0
Issued: 2024-10-24

Product / Substance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline	Remarks
C6-C7, n- alkanes, isoalkanes, cyclenes, <5% n-hexane 64742-49-0 / 921-024-6							
butane 106-97-8 / 203-448-7	LC50	658 ppm	Inhalative	4 hours	Rat	-	GESTIS
Naphthenic acids, zinc salts 12001-85-3 / 234-409-2	LD50	>2000 mg/kg	Oral	-	Rat	OECD 423	-

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.
Contains naphthenic acids, zinc salts. May produce an allergic reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

TECPO Weisses

Fettspray_EN

Routes of exposure

Ingestion. Inhalation. skin contact. eye contact.
See sections: 2.1, 4.2.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain any substance that exhibits endocrine disrupting properties towards humans, as no ingredient meets the criteria.

Other information

The mixture is classified as hazardous according to Regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Toxic to aquatic life with long lasting effects.

Acute fish toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
Hydrocarbons C6- C7, n-alkanes, isoalkanes, cyclenes, <5% n- hexane 64742-49-0 / 921- 024-6	LC50	> 1 - 10 mg/l	96 hours	Pimephales pro- melas (Fat-head Minnow)	-
Hydrocarbons C6- C7, n-alkanes, isoalkanes, cyclenes, <5% n- hexane 64742-49-0 / 921- 024-6	NOEC	2,045 mg/l	28 days	Onchorhynchus mykiss (Rainbow trout)	-
isobutane 75-28-5 / 200-857-2	LC50	91,42 mg/l	96 hours	fish	-
propane 74-98-6 / 200-827-9	LC50	49,9 mg/l	96 hours	fish	-
butane 106-97-8 / 203-448- 7	LC50	49,9 mg/l	96 hours	fish	-
Naphthenic acids,	LL50	> 100 mg/l	96 hours	Cyprinus carpio	OECD 203

TECPO Weisses Fettspray_EN

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
zinc salts 12001-85-3 / 234-409-2				(Common carp)	

Acute algae toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane 64742-49-0 / 921-024-6	ErC50	10 - 30 mg/l	72 hours	Pseudokirchneriella subcapitata	-
isobutane 75-28-5 / 200-857-2	ErC50	19,37 mg/l	96 hours	algae	-
propane 74-98-6 / 200-827-9	ErC50	19,37 mg/l	96 hours	algae	-
butane 106-97-8 / 203-448-7	ErC50	19,37 mg/l	96 hours	algae	-
Naphthenic acids, zinc salts 12001-85-3 / 234-409-2	ErC50	4 mg/l	72 hours	Pseudokirchneriella subcapitata	OECD 201

Acute crustacean toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane 64742-49-0 / 921-024-6	EC50	> 1 - 10 mg/l	48 hours	Daphnia magna	-
Hydrocarbons C6-C7, n-alkanes,	NOEC	1 mg/l	21 days	Daphnia magna	OECD 211

TECPO Weisses Fettspray_EN

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
isoalkanes, cyclenes, <5% n- hexane 64742-49-0 / 921- 024-6					
isobutane 75-28-5 / 200-857-2	EC50	69,43 mg/l	48 hours	Daphnia magna	-
propane 74-98-6 / 200-827-9	EC50	69,43 mg/l	48 hours	Daphnia magna	-
butane 106-97-8 / 203-448- 7	EC50	69,43 mg/l	48 hours	Daphnia magna	-
Naphthenic acids, zinc salts 12001-85-3 / 234- 409-2	EL50	35 mg/l	48 hours	Daphnia magna	OECD 202

Micro-/macro organism toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
Naphthenic acids, zinc salts 12001-85-3 / 234- 409-2	EC50	5,2 mg/l	3 hours	activated sludge of a predominantly domestic sewage	OECD 209

12.2. Persistence and degradability

Persistence and degradability

The product has not been tested.

Product / Substance name CAS / EC no.	Duration	Result	Method / Guideline	Remark
Hydrocarbons C6-C7, n- alkanes, isoalkanes, cyclenes, <5% n-hexane 64742-49-0 / 921-024-6	28 days	98 %	OECD 301 F	Readily biodegradable according to OECD cri- teria

12.3. Bioaccumulative potential

Bioaccumulative potential

The product has not been tested.

TECPO Weisses Fettspray_EN

Product / Substance name CAS / EC no.	LogKow / LogPow	Bioconcentration factor (BCF)	Species	Method / Guideline
Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes, <5% n-hexane 64742-49-0 / 921-024-6	3,4 - 5,2	-	-	-
isobutane 75-28-5 / 200-857-2	1,09	-	-	-
propane 74-98-6 / 200-827-9	1,09	-	-	-
butane 106-97-8 / 203-448-7	1,09	-	-	-
Naphthenic acids, zinc salts 12001-85-3 / 234-409-2	0,8	69,48	Capoeta fusca	Water Qual Expo Heal

12.4. Mobility in soil

Mobility

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment

The substances in the mixture do not fulfill the PBT/vPvB criteria according to REACH, Annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain any substance that exhibits endocrine disrupting properties towards non-target organisms, as no ingredient fulfills the criteria.

12.7. Other adverse effects

Other adverse effects

There is no information available.

Other

Do not allow to enter drains or waterways.

Do not allow to enter the subsoil/soil.

German Water Class

WGK2 - significantly water endangering

TECPO Weisses

Fettspray_EN

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal considerations

Do not allow to enter drains or waterways.
 Disposal in accordance with official regulations.

Packaging

Uncleaned packaging: Disposal in accordance with official regulations.

Waste code	Waste description
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 01 04	metallic packaging

Please note - an asterisk (*) next to a code denotes that it is HAZARDOUS WASTE.

SECTION 14: Transport information

14.1. UN number

1950

14.2. UN proper shipping name

ADR / RID / ADN proper shipping name

AEROSOLS, flammable

IMDG proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

Label

ADR/RID/ADN



2.1

IMDG



2.1



TECPO Weisses Fettspray_EN

Version number: 1.0
Issued: 2024-10-24

ADR / RID Class

2

Tunnel restriction code: D

Transportation category: 2

ADR / RID Classification code

5F

IMDG Class

2

14.4. Packing group

ADR: -

IMDG: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS

IMDG Marine Pollutant

ENVIRONMENTALLY HAZARDOUS

14.6. Special precautions for user

There is no information available.

IMDG EmS

F-D, S-U

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

Other

Additional information ADR-RID

Limited quantity: 1 L

Additional information IMDG

Limited quantity: 1 L

TECPO Weisses Fettspray_EN

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Annex XVII (REACH): The product is subject to the following restrictions according to Annex XVII, Regulation (EC) 1907/2006 (REACH): 3 , 28 , 29 , 40 , 75

Information on the SEVESO III Directive 2012/18/EU:

P3a FLAMMABLE AEROSOLE

Additional information: E2

Directive 2010/75/EU on industrial emissions: There is no information available.

Directive 2004/42/EC on VOCs from paints and varnishes: There is no information available.

National regulations

Employment restrictions: Observe employment restrictions for young people (§ 22 JArbSchG)

Water hazard class (WGK): 2, significantly hazardous to water.

Classification of mixtures according to Annex 1, No. 5 AwSV

Storage class: 2B Compressed gas packs (aerosol dispensers)

Substances of Very High Concern (SVHC) according to REACH, Article 57:

None of the ingredients are included.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

TECPO Weisses Fettspray_EN

SECTION 16: Other information

Abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
AGW - Occupational Exposure Limit (Arbeitsplatzgrenzwert)
ATE - Acute Toxicity Estimate
AwSV - Ordinance on Installations for Handling Substances Hazardous to Water
C&L - Einstufung und Kennzeichnung
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSR - Chemical Safety Report
DNEL - Derived No Effect Level
ECHA - European Chemicals Agency
GefStoffV - Hazardous Substances Ordinance (Gefahrstoffverordnung)
GHS - Globally Harmonized System
IMDG - International Maritime Dangerous Goods
International Air Transport Association
IUCLID - International Uniform Chemical Information Database
Kow - octanol-water partition coefficient
LC50 - Lethal Concentration to 50 % of a test population
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
LGK - Storage Class (Lagerklasse)
OEL - Occupational Exposure Lim
PBT - Persistent, Bioaccumulative and Toxic substance
PNEC - Predicted No Effect Concentration(s)
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SCBA - Self-Contained Breathing Apparatus
STOT - Specific Target Organ Toxicity
SVHC - Substances of Very High Concern
TRGS - Technische Regeln für Gefahrstoffe
UFI - Unique Formula Identifier
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class (Wassergefährdungsklasse)

TECPO Weisses Fettspray_EN

Phrase meaning

Aerosol 1 - Aerosol, Hazard category 1

Asp. Tox. 1 - Aspiration hazard, hazard category 1

Skin Irrit. 2 - Skin irritation, hazard category 2

STOT SE 3 - narcosis - Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis

Aquatic Chronic 2 - Hazardous to the aquatic environment — Chronic hazard category 2

Flam. Liq. 2 - Flammable liquids, hazard category 2

Flam. Gas 1 - Flammable gases, hazard category 1

Press. Gas - Liquefied gas - Gases under pressure, Liquefied gas

Skin Sens. 1B - Skin sensitisation, hazard category 1, sub-category 1B

Eye Irrit. 2 - Eye irritation, hazard category 2

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH208 Contains Napthenic acids, zinc salts. May produce an allergic reaction.

Other

Additional information

The information is based on our current state of knowledge, but does not constitute a guarantee of product properties and does not establish a contractual legal relationship. The recipient of our products is responsible for observing existing laws and regulations. The information in this safety data sheet corresponds to the best of our knowledge at the time of printing. The information is intended to provide you with guidelines for the safe handling of the product mentioned in this safety data sheet during storage, processing, transportation and disposal. The information is not transferable to other products. If the product is mixed, blended or processed with other materials processed or subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise.

Manufacturer's notes

The data of the relevant components were taken from the latest safety data sheet of the upstream supplier.