



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific
information for OEL

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BERAL UNI-SEAL HIGH TEMP GASKET BLACK

Form This substance/ mixture contains nanoforms

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant Building and construction work

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik GmbH
Niederlassung Schwepnitz
Industriestraße 1-7
D-01936 Schwepnitz
Germany
Tel. +49 (0)35797 646 0
Fax +49 (0)35797 646 190

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosols	Category 3 - (H229)
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

2.2. Label elements

Signal word

Warning

Hazard statements

H229 - Pressurised container: May burst if heated.

H412 - Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P251 - Do not pierce or burn, even after use
P273 - Avoid release to the environment
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Triacetoxyp(ropyl)silane 17865-07-5	1 - <3	01-2119966899-07-XXXX	241-816-9	Skin Corr. 1B (H314) (EUH071)	-	-	-	-
Silanetriol, methyl-, triacetate 4253-34-3	1 - <2.5	01-2119962266-32-XXXX	224-221-9	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)	-	-	-	-
Octamethylcyclotetra siloxane [D4] 556-67-2	0.05 - <0.1	# 01-2119529238-36-XXXX	209-136-7 (014-018-00-1)	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) PBT vPBT	-	-	10	-

The substance does not require registration according to REACH

#: Exempt, Hazardous impurities

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Triacetoxyp(ropyl)silane	241-816-9	17865-07-5	-	-	-	-	-
Silanetriol, methyl-, triacetate	224-221-9	4253-34-3	1600	-	-	-	-
Octamethylcyclotetrasiloxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.
Self-protection of the first aider	Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours. Containers may explode when heated.
---	--

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

Hazardous combustion products Carbon oxides. Carbon dioxide (CO₂). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Pick up and transfer to properly labelled containers. Use clean non-sparking tools to collect absorbed material.

Prevention of secondary hazards Equipment cleaned with organic solvent, washings are collected and disposed of as solvent waste. Eliminate all ignition sources if safe to do so. Residues which cannot be recycled are disposed of as chemical waste. Collect water from cleaning tools and reuse it or dispose it in local sewage systems. Do not spill water or dispose cleaning water into the environment.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Avoid breathing dust/fume/gas/mist/vapours/spray. Use personal protective equipment. Ensure adequate ventilation. Do not puncture or incinerate cans. Contents under pressure.

General hygiene considerations Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture. Keep from freezing. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep/store only in original container. Store in a dry place. Store in a closed container. Store in accordance with the particular national regulations.

Recommended storage temperature Keep at temperatures between 10 and 35 °C. Do not freeze.

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

7.3. Specific end use(s)

Specific use(s)

Building and construction work. Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Acetic acid 64-19-7	TWA: 25 mg/m ³ ; TWA: 10 ppm; STEL: 50 mg/m ³ ; STEL: 20 ppm;

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Aerosol
Appearance	Paste
Colour	Black
Odour	Acetic acid.

Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

Initial boiling point and boiling range	No data available	None known
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	100 °C	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	
Water solubility	Insoluble in water. Product cures with moisture	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	1.03 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Product cures with moisture.
------------	------------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Heating causes rise in pressure with risk of bursting.
------------------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze.
---------------------	---

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents. Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Based on available data, the classification criteria are not met. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	128,403.90 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/L
ATEmix (inhalation-vapour)	>20 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silanetriol, methyl-, triacetate	LD50 = 1600 mg/kg (Rattus) OECD 401	-	-
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m ³ (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

	Rabbit	Dermal		6	Product score <=1 Non-irritant
	Rabbit	Dermal		6	Product score <=1 Non-irritant
	Rabbit	Dermal		6 days	Product score <=1 Non-irritant

Serious eye damage/eye irritation By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye		6 days	Product score <=1 Non-irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

12.1. Toxicity

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Triacetoxyp(ropyl)silane 17865-07-5	EC50 (72h): approx. 24 mg/l(Pseudokirc henriella subpicata)	LC50 (96h) = 108.89 mg/L	-	EC50 (48h) = 89.59 mg/L		
Silanetriol, methyl-, triacetate 4253-34-3	EC50 (72h): >500 mg/l (Pseudokirchnerella subcapitata)	LC50 (96h) >500 mg/l (Brachydanio rerio)	-	EC50 (48h) >500 mg/l (Daphnia magna)		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10

12.2. Persistence and degradability

Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Triacetoxyp(ropyl)silane	1.23
Silanetriol, methyl-, triacetate	-2.4
Octamethylcyclotetrasiloxane [D4]	6.49

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Triacetoxyp(ropyl)silane	Not PBT/vPvB
Silanetriol, methyl-, triacetate	Not PBT/vPvB
Octamethylcyclotetrasiloxane [D4]	PBT / vPvB substance

12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment

Based on available data, the classification criteria are not met.

12.7. Other adverse effects Other adverse effects

Other adverse effects

No information available.

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2
Labels	2.2
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (E)
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5A
Tunnel restriction code	(E)
Limited quantity (LQ)	1 L

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.2
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.2
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No.	F-D, S-U

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols, non-flammable
14.3 Transport hazard class(es)	2.2
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, non-flammable, 2.2
14.5 Environmental hazards	No
14.6 Special precautions for user	

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

Special Provisions	A145, A167, A98, A802
Limited quantity (LQ)	30 kg G
ERG Code	2L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) which are regulated pursuant to the EU regulations on drug precursors [(EC) No. 111/2005 and (EC) No. 273/2004] above levels that can be easily used or extracted by readily applicable or economically viable means.

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

Regulation (EU) 2024/573 on fluorinated greenhouse gases
Contains fluorinated greenhouse gases.

Gas	HFO-1234ze
Global warming potential (GWP)	1.37
Tonne of CO2 equivalent	0.000003425

National regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV
No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

TRGS - 510 Storage Class Storage Class 2B : Aerosols
TA Luft (German Air Pollution Control Regulation)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)
Not Listed

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH014 - Reacts violently with water
EUH071 - Corrosive to the respiratory tract
H226 - Flammable liquid and vapour
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H361f - Suspected of damaging fertility
H410 - Very toxic to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA: International Air Transport Association
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

IMDG: International Maritime Dangerous Goods
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	On basis of test data
Serious eye damage/eye irritation	On basis of test data
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
U.S. Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Nov-2023

Revision Note SDS sections updated 15

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in

SAFETY DATA SHEET

BERAL UNI-SEAL HIGH TEMP GASKET BLACK
Supersedes date 24-Oct-2023

Revision date 13-Nov-2023
Revision Number 3

combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet