Page 1/9

*

*



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 43

Revision: 04.12.2017

SECTION 1: Identification of th	e substance/mixture and of the company/undertaking
· 1.1 Product identifier	
· Trade name: <u>MOTIP® ANTI GRAVE</u>	L OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR
No further relevant information availab • Sector of Use SU21 Consumer uses: Private househo	olds / general public / consumers n (administration, education, entertainment, services, craftsmen) aint removers ing clay
 1.3 Details of the supplier of the safety Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com 	data sheet
• Further information obtainable from: • 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)	Department Product Safety
UK: NPIS National Poisons Information	n Centre Tel: +44 0344 892 0111
SECTION 2: Hazards identifica	tion
• 2.1 Classification of the substance or n • Classification according to Regulation	
GHS02 flame	
Flam. Liq. 2 H225 Highly flamm	able liquid and vapour.
GHS09 environment	
Aquatic Chronic 2 H411 Toxic to aqua	tic life with long lasting effects.
GHS07	
•	(Contd. on page 2) GB

Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 04.12.2017

Printing date 16.05.2018 Version number 43 Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR (Contd. of page 1) Skin Irrit. 2 H315 Causes skin irritation. H319 Causes serious eye irritation. Eye Irrit. 2 STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling: Naphtha (petroleum), hydrotreated light ethyl acetate Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Hydrocarbons, C9, aromatics · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. *P337+P313* If eye irritation persists: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents / container in accordance with regional regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

0 1		
EC number: 927-510-4	Naphtha (petroleum), hydrotreated light	25-<50%
Reg.nr.: 01-2119475515-33	 Flam. Liq. 2, H225 Asp. Tox. 1, H304 	
	Aquatic Chronic 2, H411	
	🚯 Skin Irrit. 2, H315; STOT SE 3, H336	
	(C	ontd. on page 3)

Printing date 16.05.2018

Version number 43

Revision: 04.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR

CAS: 141-78-6	ethyl acetate	(Contd. of page 12.5-<20%)
EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	
EC number: 920-750-0 Index number: 649-328-00-1 Reg.nr.: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	2.5-<5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -

*

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources. Ensure adequate ventilation Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

(Contd. on page 4)

GB

Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 43

Revision: 04.12.2017

(Contd. of page 3)

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm Long-term value: 200 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

Avoid contact with the eyes.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Printing date 16.05.2018

Version number 43

Revision: 04.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



*

Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information	
Appearance:	
Form:	Fluid
Colour:	Whitish
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling rang	ge: 60 °C (140 °F)
Flash point:	-5 °C (23 °F)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C (>392 °F)
	200 °C (392 °F)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
Explosion limits:	
Lower:	0.9 Vol %
	0.6 %
Upper:	11.5 Vol %
	10.5 %
Vapour pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)
	97 hPa (72.8 mm Hg)
Daugity at 20 $\bullet C$ (68 $\bullet E$).	
Density at 20 °C (68 °F): Relative density	1.04 g/cm³ (8.68 lbs/gal) Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
•	
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

Printing date 16.05.2018

Version number 43

Revision: 04.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR

		(Contd. of page 5)
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 $^{\circ}C$ (68 $^{\circ}F$):	690 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	62.9 %	
· EU-VOC:	654.2 g/l	
• EU-VOC in %:	62.90%	
\cdot VOC (EC)		
	654.2 g/l	
· VOC-EU%	62.90 %	
· Solids content:	47.1 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish

(Contd. on page 7)

Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 43

Revision: 04.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.


· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

15 01 04 metallic packaging

· Uncleaned packaging:

• *Recommendation:* Non contaminated packagings may be recycled.



(Contd. of page 6)

Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 43

Revision: 04.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR

	(Contd. of pa
Label	3
IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	В
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1139 COATING SOLUTION, SPECIAL PROVISION 640D, 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40

(Contd. on page 9)

Printing date 16.05.2018

Version number 43

Revision: 04.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID WHITE 1 LTR

(Contd. of page 8)

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: K. Smedeman

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 $\cdot \ast$ Data compared to the previous version altered.