

Page 1 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020

PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Fuel additive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard Statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
STOT RE	2	H373-May cause damage to organs through prolonged
		or repeated exposure.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137



H225-Highly flammable liquid and vapour. H373-May cause damage to organs through prolonged or repeated exposure. H335-May cause respiratory irritation. H315-Causes skin irritation. H318-Causes serious eye damage. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves and eye protection / face protection.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P315-Get immediate medical advice / attention. P331-Do NOT induce vomiting.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Alcohols, C12-14, ethoxylated

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

OIZ MIXEGO	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	
content %	40-<50
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Asp. Tox. 1, H304
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Aquatic Chronic 2, H411

Xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119488216-32-XXXX
Index	601-022-00-9
EINECS, ELINCS, NLP	215-535-7
CAS	1330-20-7



Page 3 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL Art.: 5137

content %	20-<30
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	Acute Tox. 4, H312
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Acute Tox. 4, H332
	STOT SE 3, H335
	STOT RE 2, H373

Ethanol	Substance with specific conc. limit(s) acc. to REACh-registration
Registration number (REACH)	01-2119457610-43-XXXX
Index	603-002-00-5
EINECS, ELINCS, NLP	200-578-6
CAS	64-17-5
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Eve Irrit, 2, H319

2-butoxyethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP	203-905-0
CAS	111-76-2
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Eye Irrit. 2, H319
	Skin Irrit. 2, H315
	Acute Tox. 4, H312
	Acute Tox. 4, H332

Alcohols, C12-14, ethoxylated	
Registration number (REACH)	01-2119487984-16-XXXX
Index	
EINECS, ELINCS, NLP	500-213-3 (NLP)
CAS	68439-50-9
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 3, H412

Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	01-2119463588-24-XXXX
Index	
EINECS, ELINCS, NLP	919-284-0 (REACH-IT List-No.)
CAS	(64742-94-5)
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Carc. 2, H351
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures



Œ

Page 4 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

Headaches

Dizziness

Effects/damages the central nervous system

Unconsciousness

Product removes fat.

Dermatitis (skin inflammation)

Liver and kidney damage

Blood count modifications

Ingestion:

Oedema of the lungs

Lung damage

Chemical pneumonitis (condition similar to pneumonia)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures



Page 5 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020

PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Use explosion-proof equipment.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

Exposed employees should have regular medical check-ups.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Observe special storage conditions.

Solvent resistant floor

Do not store with oxidizing agents.

Store in a well ventilated place.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 600 mg/m3

©® Chemical Name	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Content %:40- <50
WEL-TWA: 600 mg/m3	WEL-STEL:	



(B)

Page 6 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Art.: 5137					
Monitoring procedures:	-	Compur - KITA-187 S (551 174)			
BMGV:			Other information: (C paragraphs 84-87, EH-		RCP-method,
Chemical Name	Xylene				Content %:20- <30
WEL-TWA: 220 mg/m3 (50 ppm) (221 mg/m3) (EU)	(WEL), 50 ppm	WEL-STEL: 100 ppm (441 mg. (442 mg/m3) (EU)	/m3 (WEL), 100 ppm		
Monitoring procedures:	- -	Compur - KITA-143 SA (550 325) Compur - KITA-143 SB (505 998) Draeger - Xylene 10/a (67 33 161) MTA/MA-030/A92 (Determination o ethylbenzene, p-xylene, 1,2,4-trime chromatography) - 1992 - EU projec	thylbenzene) in air - Cha	arcoal tube	method / Gas
BMGV: 650 mmol methyl hippurio , p- or mixed isomers) (BMGV)	acid/mol creatinine	in urine, post shift (Xylene, o-, m-	Other information: Sk	k (WEL)	
Chemical Name	Ethanol				Content %:10- <20
WEL-TWA: 1000 ppm (1920 mg/r	m3)	WEL-STEL:			
Monitoring procedures:	- -	Compur - KITA-104 SA (549 210) Draeger - Alcohol 25/a Ethanol (81 DFG (D) (Loesungsmittelgemische) 2002 - EU project BC/CEN/ENTR/0	, Methode Nr. 6 DFG (E		mixtures) - 1998,
BMGV:		, ,	Other information:		
Chemical Name	2-butoxyethanol				Content %:1-<10
WEL-TWA: 25 ppm (123 mg/m3) mg/m3) (EU)		WEL-STEL: 50 ppm (246 mg/r	n3) (WEL, EU)		
Monitoring procedures:	-	Compur - KITA-190 U(C) (548 873)		'	
Monitoring procedures.	_	DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-16	3), DFG (E) (Solvent mix	xtures 3) -	1998, 2002 - EU
	- cid/mol creatinine in	DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-16	3), DFG (E) (Solvent mix 6 card 32-2 (2004)	xtures 3) -	1998, 2002 - EU
BMGV: 240 mmol butoxyacetic ad Chemical Name	Hydrocarbons, C	DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-10 urine, post shift (BMGV) 10, aromatics, >1% naphthalene	3), DFG (E) (Solvent mix 6 card 32-2 (2004)		
BMGV: 240 mmol butoxyacetic ac Chemical Name WEL-TWA: 500 mg/m3 (Aromatic	Hydrocarbons, C	DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-10 urine, post shift (BMGV) 10, aromatics, >1% naphthalene WEL-STEL:	3), DFG (E) (Solvent mix 6 card 32-2 (2004) Other information: Sk		
	Hydrocarbons, C	DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-10 urine, post shift (BMGV) 10, aromatics, >1% naphthalene	3), DFG (E) (Solvent mix 6 card 32-2 (2004) Other information: Sk	k (WEL)	1998, 2002 - EU Content %:0,1-<

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

Xylene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	•	<u></u>	<u>'</u>	•		



Page 7 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

	Environment - periodic release		PNEC	0,327	mg/l
	Environment - sewage treatment plant		PNEC	6,58	mg/l
	Environment - freshwater		PNEC	0,327	mg/l
	Environment - marine		PNEC	0,327	mg/l
	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw
	Environment - sediment, marine		PNEC	12,46	mg/kg dw
	Environment - soil		PNEC	2,31	mg/kg dw
	Environment - water, sporadic (intermittent) release		PNEC	0,327	mg/l
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m3
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,75	mg/l	
	Environment - sewage treatment plant		PNEC	580	mg/l	
	Environment - sediment, freshwater		PNEC	3,6	mg/kg	
	Environment - soil		PNEC	0,63	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	0,38	g/kg feed	
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight	
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3	



Page 8 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m3

2-butoxyethanol Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental compartment		-			
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment.		PNEC	34,6	mg/kg dw	
	freshwater		0	0 .,0	g,g u	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage		PNEC	463	mg/l	
	treatment plant		_			
	Environment - sediment,		PNEC	3,46	mg/kg dw	
	marine		_		3.3.	
	Environment - sporadic		PNEC	9,1	mg/l	
	(intermittent) release					
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal		PNEC	20	mg/kg	
	feed)					
Consumer	Human - inhalation	Long term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Short term, systemic	DNEL	44,5	mg/kg bw/d	
		effects				
Consumer	Human - inhalation	Short term, systemic	DNEL	426	mg/m3	
		effects				
Consumer	Human - oral	Short term, systemic	DNEL	13,4	mg/kg bw/d	
		effects				
Consumer	Human - inhalation	Short term, local	DNEL	123	mg/m3	
		effects				
Consumer	Human - dermal	Long term, systemic	DNEL	38	mg/kg bw/d	
		effects				
Consumer	Human - inhalation	Long term, systemic	DNEL	49	mg/m3	
		effects				
Consumer	Human - oral	Long term, systemic	DNEL	3,2	mg/kg bw/d	
		effects				
Workers / employees	Human - dermal	Short term, systemic	DNEL	89	mg/kg bw/d	
		effects			, ,	
Workers / employees	Human - inhalation	Short term, systemic	DNEL	663	mg/m3	
		effects	51151	0.10		
Workers / employees	Human - inhalation	Short term, local	DNEL	246	mg/m3	
Markey / amarkey	I I I I I I I I I I I I I I I I I I I	effects	DNE	75		
Workers / employees	Human - dermal	Long term, systemic	DNEL	75	mg/kg bw/d	
Markey / amarkey	I I I I I I I I I I I I I I I I I I I	effects	DNE	00		
Workers / employees	Human - inhalation	Long term, systemic	DNEL	98	mg/m3	
		effects				

Hydrocarbons, C10, aron	natics, >1% naphthalene					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	



(B)

Page 9 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

>= 0,4

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective Viton® / fluoroelastomer gloves (EN 374)

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.



Œ

Page 10 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour threshold:

Liquid

Blue, Clear

Characteristic

Not determined

pH-value: n.a.

Melting point/freezing point:

Initial boiling point and boiling range:

Flash point:

Evaporation rate:

Not determined

100 °C

18 °C

Not determined

Evaporation rate:

Flammability (solid, gas):

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Not determined

Not determined

Not determined

Vapour pressure:

Not determined

Vapour density (air = 1): Vapours heavier than air.

Density: 0,789 g/ml (15°C) Bulk density: Not determined Solubility(ies): Not determined Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined <7 mm2/s (40°C) Viscosity: Explosive properties: Not determined

Oxidising properties: No

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No decomposition if used as intended.

10.4 Conditions to avoid

Heating, open flame, ignition sources Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products



③B)·

Page 11 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL Art.: 5137

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Pro-Line Jet Clean Tankreinige		,	,			
Art.: 5137						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value,
						Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C6-C7, n-alkane	s, isoalkanes	s, cyclics, <5%	6 n-hexane			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Aspiration hazard:						Yes



Page 12 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Symptoms:			drowsiness,
Symptoms.			unconsciousness
			unconsciousness
			heart/circulatory
			disorders,
			headaches,
			cramps,
			drowsiness,
			mucous
			membrane
			irritation,
			dizziness,
			nausea and
			vomiting.
Specific target organ toxicity -			Not irritant
single exposure (STOT-SE),			(respiratory tract).
inhalative:			

Xylene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3523	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	12126	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LD50	27,6	mg/l/4h	Rat		Does not conform with EU classification., Vapours
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						Yes
Symptoms:						breathing difficulties, headaches, dizziness
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	124,7	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Irritant
					Irritation/Corrosion)	



Page 13 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Respiratory or skin sensitisation:	Mouse	OECD 429 (Skin Sensitisation - Local	No (skin contact)
		Lymph Node Assay)	
Germ cell mutagenicity:	Salmonella	OECD 471 (Bacterial	Negative
Cerm con matagernony.	typhimuriun		Nogativo
Germ cell mutagenicity:	Mouse	OECD 476 (In Vitro	Negative
Germ cen mutagementy.	Wouse	Mammalian Cell Gene	INEGative
		Mutation Test)	
Germ cell mutagenicity:		OECD 473 (In Vitro	Negative
Germ cen mutagementy.			ivegative
		Mammalian Chromosome	
		Aberration Test)	
Germ cell mutagenicity:		OECD 475 (Mammalian	Negative
		Bone Marrow	
		Chromosome	
		Aberration Test)	
Aspiration hazard:	Human beir	ng	No indications of
			such an effect.
Symptoms:			respiratory
			distress,
			drowsiness,
			unconsciousnes
			, drop in blood
			pressure,
			vomiting,
			coughing,
			headaches,
			intoxication,
			drowsiness,
			mucous
			membrane
			irritation,
			dizziness,
			nausea
Other information:			Excessive
			alcohol
			consumption
			during
			pregnancy
			induces the
			foetus alcohol
			foetus alcohol syndrome
			foetus alcohol syndrome (reduced weight
			foetus alcohol syndrome (reduced weight at birth, physica
			foetus alcohol syndrome (reduced weight at birth, physica and mental
			foetus alcohol syndrome (reduced weight at birth, physical and mental disorders).,
			foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign
			foetus alcohol syndrome (reduced weight at birth, physica and mental disorders)., There is no sign that this
			foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also
			foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by
			foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also
			foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or
			foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or inhalative
			foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or

2-butoxyethanol										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Acute toxicity, by oral route:	LD50	1746	mg/kg	Rat	OECD 401 (Acute Oral					
					Toxicity)					
Acute toxicity, by oral route:	LD50	1300	mg/kg	Guinea pig						
Acute toxicity, by dermal route:	LD50	1060	mg/kg	Rabbit						



Page 14 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	10-20	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:	2000	10 20		Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSI ON)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Aspiration hazard:						No
Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	

Alcohols, C12-14, ethoxylated						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Serious eye damage/irritation:				Rabbit		Eye Dam. 1
Symptoms:						eyes, reddened, watering eyes, blisters by skin- contact, stomach pain



(B)

Page 15 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026 Valid from: 21.01.2020

PDF print date: 22.01.2020 Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	CONCIGOION
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 416 (Two- generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):				Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative, Analogous conclusion
Aspiration hazard: Symptoms:						Yes drowsiness, headaches, drowsiness, dizziness



③B)·

Page 16 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL Art.: 5137

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							as possible with
							an oil separator
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							
Other information:							According to the
							recipe, contains
							no AOX.

Hydrocarbons, C6-C7, n-							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other information:	DOC						DOC-elimination
							degree(complex
							ng organic
							substance)>=
							80%/28d:
12.3. Bioaccumulative							Concentration in
potential:							organisms
							possible.
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	LOEC/LOEL	21d	0,32	mg/l	Daphnia magna		
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus		
					mykiss		
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OECD 203 (Fish,	
						Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	81	%	activated sludge	OECD 301 F	Readily
degradability:						(Ready	biodegradable,
						Biodegradability -	Analogous
						Manometric	conclusion
						Respirometry Test)	
12.3. Bioaccumulative	BCF		242-253				
potential:							



Page 17 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

12.4. Mobility in soil:					Adsorption in ground., Product is slightly volatile.
12.5. Results of PBT and vPvB assessment					No PBT substance, No vPvB substance
Other information:	AOX	0	%		

Xylene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	IC50	72h	4,36	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	2,6	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		3,16			, ,	
12.3. Bioaccumulative potential:	BCF		25,9				
12.4. Mobility in soil:	H (Henry)		665	Pa*m3/m ol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:	·	30d	80-85	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.1. Toxicity to fish:	NOEC/NOEL	120h	250	mg/l	Brachydanio rerio	OECD 212 (Fish, Short- term Toxicity Test on Embryo and Sac- fry Stages)	
12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	12340	mg/l	Daphnia magna	,	
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to daphnia:	LC50	48h	5012	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	97	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,32			,	Bioaccumulation is unlikely (LogPow < 1).
12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				, , ,



Page 18 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL Art.: 5137

Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	

2-butoxyethanol	Fuducint	Time	Value	I Imit	Ouncuions	Toot mostle and	Mataa
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity	
					,	Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish,	
,				g, .	=:::::, =:::::	Prolonged Toxicity	
						Test - 14-Day	
						Study)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202	
·=···· romenty to daprimar			.555		2 45	(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211	
12.11 Foxiony to daprima.	11020/11022	2.0	1.00	1119/1	Dapriilla magna	(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
12.11. Toxicity to digac.	2000	1211	1040	1119/1	a subcapitata	Growth Inhibition	
					a subsupitata	Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
12.1. Toxicity to algae.	NOLO/NOLL	7211	200	1119/1	a subcapitata	Growth Inhibition	
					a subcapitata	Test)	
12.2. Persistence and		28d	95	%		OECD 301 E	Readily
degradability:		200	33	/0		(Ready	biodegradable
degradability.						Biodegradability -	biodegradable
						Modified OECD	
						Screening Test)	
12.2. Persistence and		28d	>99	%		OECD 302 B	Readily
degradability:		20u	799	/0		(Inherent	biodegradable
degradability.						Biodegradability -	biodegradable
						Zahn-	
						Wellens/EMPA	
						Test)	
12.3. Bioaccumulative	BCF		3,2			1 (51)	Slight
potential:	BOI		5,2				Slight
12.3. Bioaccumulative	Log Pow		0,81			OECD 107	Not to be
potential:			'			(Partition	expected
•						Coefficient (n-	'
						octanol/water) -	
						Shake Flask	
						Method)	
12.4. Mobility in soil:	H (Henry)		0,00000	atm*m3/m		,	
40.4.14.1.11111111111111111111111111111			16	ol			
12.4. Mobility in soil:	Koc		67				Expert judgeme
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
Tandalous back 1	F040	401	700		Decodes	DIN 00440 T 0	vPvB substance
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas	DIN 38412 T.8	
					putida		

Alcohols, C12-14, ethoxylated



(B)

Page 19 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and	BOD	5d	1176	mg/g			
degradability:							
12.2. Persistence and	BOD	14d	>60	%		OECD 301 D	Readily
degradability:						(Ready	biodegradable
g ,						Biodegradability -	Ü
						Closed Bottle Test)	
12.2. Persistence and	COD		2283	mg/g		DIN 38409-H41	
degradability:							
12.1. Toxicity to fish:	LC50	96h	1,1	mg/l	Oncorhynchus	OECD 203 (Fish,	
,			'		mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,52	mg/l		OECD 202	
, ,			,			(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	0,41	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
, 3			,		a subcapitata	Growth Inhibition	
					· ·	Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,31	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
, 0					a subcapitata	Growth Inhibition	
					,	Test)	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus		
-					mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriell		
					a subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell		
					a subcapitata		
12.2. Persistence and		28d	58	%		OECD 301 F	Analogous
degradability:						(Ready	conclusion
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative	Log Pow		2,8-6,5				High
potential:							
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.



Page 20 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Residues may present a risk of explosion.

SECTION 14: Transport information

General statements

14.1. UN number: 1993

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1993 FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), ETHANOL)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Classification code: F1 LQ: 1 L

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), ETHANOL)

14.3. Transport hazard class(es): 3 14.4. Packing group: Ш EmS: F-E, S-E

Marine Pollutant: 14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Flammable liquid, n.o.s. (NAPHTHA (PETROLEUM), ETHANOL) 14.3. Transport hazard class(es): 3 14.4. Packing group: Ш

Not applicable 14.5. Environmental hazards:

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000
E2		200	500











Page 21 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

95,4 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

3, 11, 12

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Flam. Liq. 2, H225	Classification based on test data.
STOT RE 2, H373	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid STOT RE — Specific target organ toxicity - repeated exposure

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - dermal



Page 22 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

Eye Irrit. — Eye irritation

Acute Tox. — Acute toxicity - inhalation Acute Tox. — Acute toxicity - oral

Aquatic Acute — Hazardous to the aquatic environment - acute

Carc. — Carcinogenicity

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

The International Bromine Council BSEF

body weight bw

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

ΕČ **Furopean Community** ECHA European Chemicals Agency European Economic Community EEC

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

ΕN European Norms

EPA United States Environmental Protection Agency (United States of America)

et cetera etc. FU **European Union**

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

International Agency for Research on Cancer IARC International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

IΩ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. n.av. not available not checked n.c. no data available n.d.a.

OECD Organisation for Economic Co-operation and Development

organic org.

PBT persistent, bioaccumulative and toxic PΕ Polyethylene

PNEC Predicted No Effect Concentration

parts per million ppm **PVC** Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)



Page 23 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.01.2020 / 0027

Replacing version dated / version: 12.07.2019 / 0026

Valid from: 21.01.2020 PDF print date: 22.01.2020

Pro-Line Jet Clean Tankreiniger 500 mL

Art.: 5137

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No.

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

Volatile organic compounds VOC

vPvB very persistent and very bioaccumulative

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.