

Printing date 29.10.2020 Version: 4.01 Revision: 15.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Tyre Fix

Article number: 04323000, 04325000

UFI: S278-6PR9-Q24N-JQ8E

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC0 Other PC1 Adhesives, sealants

Application of the substance / the mixture Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety E-mail: erp@sonax.de Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Danger

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.



Printing date 29.10.2020 Version: 4.01 Revision: 15.05.2020

Trade name: SONAX Tyre Fix

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and aqueous emulsion of synthetic polymers

Dangerous components:		
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	20 - 25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ♦ Flam. Gas 1, H220; Press. Gas (Comp.), H280	12.5 - 20%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	12.5 - 20%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Water spray

Foam

Fire-extinguishing powder

Carbon dioxide

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)



Printing date 29.10.2020 Version: 4.01 Revision: 15.05.2020

Trade name: SONAX Tyre Fix

(Contd. of page 2)

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Highly volatile, flammable constituents are released during processing.



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane

WEL (Great Britain) Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

Regulatory information WEL (Great Britain): EH40/2020

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

(Contd. on page 4)



Version: 4.01 Printing date 29.10.2020 Revision: 15.05.2020

Trade name: SONAX Tyre Fix

(Contd. of page 3)

Respiratory protection: Not required in normal cases

Ensure good ventilation/exhaustion at the workplace. Protection of hands: Not required in normal cases. Eye protection: Not required in normal cases

SECTION 9: Ph	ysical and	l chemical	proper	ties
---------------	------------	------------	--------	------

General Information

Appearance:

Form: Aerosol Colour: White Odour: Characteristic Odour threshold: Not determined.

Important information on protection of health and

environment, and on safety. data of the content without propellant

pH-value at 20 °C: 9.5

Change in condition

Melting point/freezing point: Undetermined. 100 °C Initial boiling point and boiling range:

Flash point: 101 °C (ISO 2719:2002)

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Not determined.

In use, may form flammable/explosive vapour-air

mixture.

Explosion limits:

Vapour pressure:

2.6 Vol % Lower: 12.6 Vol % Upper: Not determined.

Density at 20 °C: 1.00 - 1.01 g/cm3 Relative density Not determined. Not determined. Vapour density Evaporation rate Not applicable.

Solubility in / Miscibility with

Not miscible or difficult to mix. water:

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.
- 10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

(Contd. on page 5)



Printing date 29.10.2020 Version: 4.01 Revision: 15.05.2020

Trade name: SONAX Tyre Fix

(Contd. of page 4)

Keep ignition sources away - Do not smoke. See Section 7 for information on safe handling.

10.5 Incompatible materials: No known incompatible materials.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:				
CAS: 74-98-6 propane				
LC50 / 96 h	27.98 mg/l (fish)			
EC50 / 96 h	27.98 mg/l (fish) 7.71 mg/l (algae)			
CAS: 75-28-5 isobutane				

LC50 / 96 h 27.98 mg/l (fish) EC50 / 4 d 7.71 mg/l (algae)

CAS: 106-97-8 butane

LC50 / 96 h | 27.98 mg/l (fish)

EC50 / 4 d | 7.71 mg/l (algae)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: The product may not be released into the environment without control.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation

Waste must be disposed of while observing the local, official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)



Printing date 29.10.2020 Version: 4.01 Revision: 15.05.2020

Trade name: SONAX Tyre Fix

(Contd. of page 5)

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport informat	ЮП	
14.1 UN-Number ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label IMDG, IATA	2.1	
Class	2.1	
Label	2.1	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.	
Transport/Additional information:		
ADR Limited quantities (LQ) Transport category Tunnel restriction code	1L 2 D	
UN "Model Regulation":	UN1950, AEROSOLS, 2.1	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

EC/1907/2006 (REACh) EC/1272/2008 (CLP) EC/648/2004

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

(Contd. on page 7)



Printing date 29.10.2020 Version: 4.01 Revision: 15.05.2020

Trade name: SONAX Tyre Fix

(Contd. of page 6)

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Classification according to Regulation (EC) No 1272/2008

Aerosols On basis of test data

Abbreviations and acronyms:

NOEL = No Observed Effect Level NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage

of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

IOELV = indicative occupational exposure limit values

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Version history and indication of changes: Replaces version 4.00.

* Data compared to the previous version altered.