

Page 1 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.07.2019 / 0027
Replacing version dated / version: 29.06.2018 / 0026
Valid from: 12.07.2019
PDF print date: 12.07.2019
Schnellrostloeser 300 mL
Art.: 1612

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Schnellrostloeser 300 mL

Art.: 1612

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Rust remover

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC24 - Lubricants, greases, release products

PC35 - Washing and cleaning products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC11 - Non industrial spraying

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany

Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.07.2019 / 0027

Replacing version dated / version: 29.06.2018 / 0026

Valid from: 12.07.2019

PDF print date: 12.07.2019

Schnellrostloeser 300 mL

Art.: 1612

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	(64742-48-9)
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Carbon dioxide		Substance for which an EU exposure limit value applies.
Registration number (REACH)	---	
Index	---	
EINECS, ELINCS, NLP	204-696-9	
CAS	124-38-9	

Page 3 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

content %	1-<20
Classification according to Regulation (EC) 1272/2008 (CLP)	---

2-butoxyethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP	203-905-0
CAS	111-76-2
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Acute Tox. 4, H312 Acute Tox. 4, H332

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

with long-term contact:

Product removes fat.

Irritation of the skin.

Frostbite

Reddening

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Page 4 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.07.2019 / 0027
Replacing version dated / version: 29.06.2018 / 0026
Valid from: 12.07.2019
PDF print date: 12.07.2019
Schnellrostloeser 300 mL
Art.: 1612

Adapt to the nature and extent of fire.
Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Hydrocarbons

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store in a well-ventilated place.

Observe special regulations for aerosols!

Not to be stored in gangways or stair wells.

Do not store with oxidizing agents.

Page 5 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:50-70
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Carbon dioxide	Content %:1-20
WEL-TWA: 5000 ppm (9150 mg/m ³) (WEL), 5000 ppm (9000 mg/m ³) (EU)	WEL-STEL: 15000 ppm (27400 mg/m ³) (WEL)	---
Monitoring procedures:	- Compur - KITA-126 B (549 475) - Compur - KITA-126 SA (549 467) - Compur - KITA-126 SB (548 816) - Compur - KITA-126 SF (549 491) - Compur - KITA-126 SG (550 210) - Compur - KITA-126 SH (549 509) - Compur - KITA-126 UH (549 517) - Draeger - Carbon Dioxide 100/a (81 01 811) - Draeger - Carbon Dioxide 0,1%/a (CH 23 501) - Draeger - Carbon Dioxide 0,5%/a (CH 31 401) - Draeger - Carbon Dioxide 1%/a (CH 25 101) - Draeger - Carbon Dioxide 5%/A (CH 20 301) - OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 1990 - NIOSH 6603 (Carbon dioxide) - 1994	
BMGV: ---	Other information: ---	

Chemical Name	2-butoxyethanol	Content %:1-10
WEL-TWA: 25 ppm (123 mg/m ³) (WEL), 20 ppm (98 mg/m ³) (EU)	WEL-STEL: 50 ppm (246 mg/m ³) (WEL, EU)	---
Monitoring procedures:	- Compur - KITA-190 U(C) (548 873) DFG (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)	
BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Sk (WEL)	

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)	
BMGV: ---	Other information: ---	

2-butoxyethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	

Page 6 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. BS EN 14042.
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Page 7 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

With danger of contact with eyes.
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Solvent resistant protective gloves (EN 374).
 If applicable
 Protective nitrile gloves (EN 374).
 Minimum layer thickness in mm:
 0,3
 Permeation time (penetration time) in minutes:
 > 120
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If OES or MEL is exceeded.
 Filter A P3 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, liquid.
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,829-0,86 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined

Page 8 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.07.2019 / 0027
Replacing version dated / version: 29.06.2018 / 0026
Valid from: 12.07.2019
PDF print date: 12.07.2019
Schnellrostloeser 300 mL
Art.: 1612

Viscosity: Not determined
Explosive properties: Product is not explosive.
Oxidising properties: No

9.2 Other information

Miscibility: Not determined
Fat solubility / solvent: Not determined
Conductivity: Not determined
Surface tension: Not determined
Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

In use, may form flammable/explosive vapour-air mixture.
This product is not reactive based on experiences.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Pressure increase will result in danger of bursting.
Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Schnellrostloeser 300 mL

Art.: 1612

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	

Page 9 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Aspiration hazard:						Yes

2-butoxyethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1746	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	1300	mg/kg	Guinea pig		
Acute toxicity, by dermal route:	LD50	1060	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	2-20	mg/l	Rat		
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Aspiration hazard:						No

Page 10 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Schnellrostloeser 300 mL

Art.: 1612

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.

Page 11 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

12.5. Results of PBT and vPvB assessment						n.d.a.
12.6. Other adverse effects:						n.d.a.
Other information:	AOX					According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,1	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2				Product floats on the water surface.
12.4. Mobility in soil:	Log Koc		>3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:			~10	mg/l			Slight

2-butoxyethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Page 12 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,2				
12.3. Bioaccumulative potential:	Log Pow		0,83				Negative
12.4. Mobility in soil:	H (Henry)		0,00000 16	atm*m3/m ol			
12.4. Mobility in soil:	Koc		67				Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC0	16h	700	mg/l	Pseudomonas putida	DIN 38412 T.8	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Return to manufacturer with residual pressure.

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: Not applicable



Page 13 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.07.2019 / 0027
Replacing version dated / version: 29.06.2018 / 0026
Valid from: 12.07.2019
PDF print date: 12.07.2019
Schnellrostloeser 300 mL
Art.: 1612

Tunnel restriction code: D
Transport by sea (IMDG-code)
14.2. UN proper shipping name:
AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
EmS: F-D, S-U
Marine Pollutant: n.a.
14.5. Environmental hazards: Not applicable



Transport by air (IATA)
14.2. UN proper shipping name:
Aerosols, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.
Danger code and packing code on request.
Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 58 %

REGULATION (EC) No 648/2004

30 % and more
aliphatic hydrocarbons

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:
Employee training in handling dangerous goods is required.

Page 14 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.07.2019 / 0027
 Replacing version dated / version: 29.06.2018 / 0026
 Valid from: 12.07.2019
 PDF print date: 12.07.2019
 Schnellrostloeser 300 mL
 Art.: 1612

These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.

Aerosol — Aerosols
 Asp. Tox. — Aspiration hazard
 Acute Tox. — Acute toxicity - oral
 Eye Irrit. — Eye irritation
 Skin Irrit. — Skin irritation
 Acute Tox. — Acute toxicity - dermal
 Acute Tox. — Acute toxicity - inhalation

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 etc. et cetera
 EU European Union

Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.07.2019 / 0027

Replacing version dated / version: 29.06.2018 / 0026

Valid from: 12.07.2019

PDF print date: 12.07.2019

Schnellrostloeser 300 mL

Art.: 1612

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.